

Feature	Virtual Servers	Supported Policies	Policy Bind Points	How You Use the Policies
System features, Authentication	None	Authentication policies	Global	For the Authentication feature, policies contain authentication schemes for different authentication methods. For example, you can configure LDAP and certificate-based authentication schemes.
SSL	None	SSL policies	<ul style="list-style-type: none"> • Global • Load Balancing virtual server 	<p>To determine when to apply an encryption function and add certificate information to clear text.</p> <p>To provide end-to-end security. After a message is decrypted, the SSL feature re-encrypts clear text and uses SSL to communicate with back-end Web servers.</p>
Content Switching (Can use either classic or default syntax policies, but not both)	Content Switching virtual server	Content Switching policies	<ul style="list-style-type: none"> • Content Switching virtual server • Cache Redirection virtual server 	<p>To determine what server or group of servers is responsible for serving responses, based on characteristics of an incoming request.</p> <p>Request characteristics include device type, language, cookies, HTTP method, and content type and associated cache server.</p>
Compression	None	HTTP Compression policies	<ul style="list-style-type: none"> • Global • Content Switching virtual server • Load Balancing virtual server • SSL Offload virtual server • Service 	To determine what type of HTTP traffic is compressed.

Protection features, Filter	None	Content Filtering policies	<ul style="list-style-type: none"> • Global • Content Switching virtual server • Load Balancing virtual server • SSL Offload virtual server • Service 	To configure the behavior of the filter function.
Protection features, SureConnect	None	SureConnect policies	<ul style="list-style-type: none"> • Load Balancing virtual server • SSL Offload virtual server • Service 	To configure the behavior of the SureConnect function.
Protection features, Priority Queuing	None	Priority Queuing policies	<ul style="list-style-type: none"> • Load Balancing virtual server • SSL Offload virtual server 	To configure the behavior of the Priority Queuing function.
HTML Injection	None	HTML Injection Policies	<ul style="list-style-type: none"> • Global • Load Balancing virtual server • Content Switching virtual server • SSL Offload virtual server 	To enable the NetScaler to insert text or scripts into an HTTP response that it serves to a client.
AAA - Traffic Management	None	Authentication, Authorization, Auditing, and Session policies	<ul style="list-style-type: none"> • Authentication virtual server (authentication, session, and auditing policies) • Load Balancing or Content Switching virtual server (authorization and auditing policies) • Global (session and audit policies) • AAA group or user (session, auditing, and authorization policies) 	To configure rules for user access to specific sessions and auditing of user access.

Cache Redirection	Cache Redirection virtual server	Cache Redirection policies Map policies	Cache Redirection virtual server	To determine whether HTTP responses are served from a cache or an origin server.
Application firewall	VPN server	Pre-Authentication policies	<ul style="list-style-type: none"> • AAA Global • VPN vserver 	To determine how the NetScaler Gateway performs authentication, authorization, auditing, and other functions, and to define rewrite rules for general Web access using theNetScaler Gateway.
		Authentication policies	<ul style="list-style-type: none"> • System Global • AAA Global • VPN vserver 	
		Auditing policies	<ul style="list-style-type: none"> • User • User group • VPN vserver 	
		Session policies	<ul style="list-style-type: none"> • VPN Global • User • User Group • VPN vserver 	
		Authorization policies	<ul style="list-style-type: none"> • User • User Group 	
		Traffic policies	<ul style="list-style-type: none"> • VPN Global • User • User Group • VPN vserver 	
		TCP Compression policies	VPN Global	