

Audit server commands	Specifies
audserver -help	The available Audit Server options.
audserver -addns -f <path to configuration file>	<p>The system that gathers the log transaction data.</p> <p>You are prompted to enter the IP address of the NetScaler appliance.</p> <p>Enter the valid user name and password.</p>
audserver -verify -f<path to configuration file>	Check for syntax or semantic errors in the configuration file (for example, auditlog.conf).
audserver -start -f<path to configuration file>	<p>Start audit server logging based on the settings in the configuration file (auditlog.conf).</p> <p>Linux only: To start the audit server as a background process, type the ampersand sign (&) at the end of the command.</p>
audserver -stop (Linux only)	Stops audit server logging when audit server is started as a background process. Alternatively, use the Ctrl+C key to stop audit server logging.
audserver -install -f <path to configuration file> (Windows only)	Installs the audit server logging client as a service on Windows.
audserver -startservice (Windows Only)	<p>Start the audit server logging service, when you enter this command at a command prompt.</p> <p>You can also start audit server logging from Start > Control Panel > Services.</p> <p>Note: Audit server logging starts by using the configuration settings in the configuration file, for example, auditlog.conf file specified in the audit server install option.</p>
audserver -stopservice (Windows Only)	Stop audit server logging.
audserver -remove	Removes the audit server logging service from the registry.