

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
ee55b223-38eb-430f-bf63-2cc157425472	Broker service failed to connect to Delegated Administration Service	The Citrix Broker Service couldn't connect to the Citrix Delegated Administration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Broker Service couldn't connect to the Citrix Delegated Administration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		To resolve this issue, perform the following actions: 1. Click **Start** , type **services.msc** , and then press ENTER. 2. From the Services console, select **Citrix Broker Service** and then click **Restart** . 3. Select **Citrix Delegated Administration Service** and then click **Restart** .	Error
66878435-35f8-4c3a-9f6d-4d2dceeb65b	Broker service failed to connect to Configuration Logging Service	The Citrix Broker Service couldn't connect to the Citrix Configuration Logging Service. The Broker Service takes care of VDA registration, resource allocation, connection brokering, and licensing enforcement, among other tasks. Additionally, it takes care of all communication to and from the Delivery Controller. It does this by communicating with the VDA, Citrix Desktop Service, and the Citrix XenApp and XenDesktop Services.		The Citrix Broker Service couldn't connect to the Citrix Configuration Logging Service. The Broker Service takes care of VDA registration, resource allocation, connection brokering, and licensing enforcement, among other tasks. Additionally, it takes care of all communication to and from the Delivery Controller. It does this by communicating with the VDA, Citrix Desktop Service (BrokerAgent.exe), which is part of the desktop as well as server VDA.	[Bas Van Kaam](http://www.basvankaam.com), Citrix Technology Professional	To resolve this issue, perform the following actions: 1. Restart the Citrix Configuration Logging Service: Click **Start** , type **services.msc** , and then press **ENTER** . From the Services console, select **Citrix Configuration Logging Service** , and then click **Restart** . 2. Restart the Citrix Broker Service: Click **Start** , type **services.msc** , and then press **ENTER** . From the Services console, select **Citrix Broker Service** and then click **Restart** . 3. If restarting the services does not resolve the issue, rebuild the Delivery Controller.	Error
a1159377-4016-4d66-9409-3d60b05e8637	Broker service failed to connect to Configuration Service	The Citrix Broker Service failed to connect to the Citrix Configuration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Broker Service failed to connect to the Citrix Configuration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		Restart the Citrix Configuration Service: 1. Click **Start** , type **services.msc** , and then press ENTER. 2. From the Services console, select **Citrix Configuration Service** and then click **Restart** . 3. Select **Citrix Broker Service** and then click **Restart** .	Error
c570d86-03d7-4954-a2ac-e92a1635ae6	Broker service not registered with Configuration service	The service instance ([serviceinstance]) published by the Broker service is not registered with the Configuration Service. For a list of services that are registered with the configuration, use the Get-ConfigRegisteredServiceInstance cmdlet. For more information about this cmdlet, see the [Citrix SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Get-ConfigRegisteredServiceInstance/).	The unregistered service instance is ([serviceinstance]).	The service instance published by the Broker service is not registered with the Configuration Service. For a list of services that are registered with the configuration, use the Get-ConfigRegisteredServiceInstance cmdlet. For more information about this cmdlet, see the [Citrix SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Get-ConfigRegisteredServiceInstance/).		Register the service instance with the Citrix Configuration Service. To do this, use the Register-ConfigServiceInstance cmdlet. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Register-ConfigServiceInstance/).	Error
c9428221-7d6d-4458-943e-6145a84846a5	No recent backup for Site database	Smart Tools couldn't find a recent backup for the Site database. The database ([dbName]) on server ([dbServer]) has not been backed up for ([daysWithoutBackup]) days. If you have configured mirroring for the Site database, this alert could appear if the mirror has not been backed up recently.	The number of days without a backup is ([daysWithoutBackup]). The Database Name is ([dbName]) and the Server Name is ([dbServer]).	Smart Check couldn't find a recent backup of the Site database. If you have configured mirroring for the Site database, this alert could appear if the mirror has not been backed up recently.		Create a backup of the Site database. Additionally, consider creating a maintenance backup plan for Microsoft SQL Server, if one doesn't exist already. A maintenance backup plan ensures administrative tasks, like backups, are performed at scheduled intervals. For more information, see [How To: Create a Maintenance Plan](https://technet.microsoft.com/en-us/library/ms189953(v=sql.105).aspx) on the Microsoft TechNet web site. As a best practice, Citrix recommends performing full daily backups of all three XenDesktop databases (Site, Configuration Logging, and Monitoring), depending on the frequency of configuration changes in the Site.	Warning
a0695ae-e6d4-4301-a7ce-d486e620c7d	Incorrect firewall configuration for Citrix AD Identity Service	The Citrix firewall rule **CitrixADIdentityService** might be missing, disabled, or might refer to the wrong network port. This alert might appear if the Site installation partially failed, the port was manually changed in the service's configuration file, or the firewall rule was either manually removed or removed through Group Policy.		The Citrix firewall rule **CitrixADIdentityService** might be missing, disabled, or might refer to the wrong network port. This alert might appear if the Site installation partially failed, the port was manually changed in the service's configuration file, or the firewall rule was either manually removed or removed through Group Policy. Possible impact: Missing Firewall rules can prevent calls to the AD Identity Service on the affected Delivery Controller. The AD Identity Service handles all computer	[Bas Van Kaam](http://www.basvankaam.com), Citrix Technology Professional	If your organization manages firewall rules through Group Policy, consult your Group Policy administrator to resolve this issue. To repair the firewall configuration: 1. Open the command prompt as an administrator. 2. At the command prompt, navigate to the AD Identity Service directory. Example: cd C:\ProgramFiles\Citrix\ADIdentity\Service 3. Run Citrix AD Identity service executable with the argument -CONFIGUREFIREWALL. Example: Citrix.ADIdentity.exe -configurefirewall	Warning
b37dab85-6f65-403c-a59f-4eebb7be8da	Incorrect firewall configuration for Citrix Analytics Service	The Citrix firewall rule **CitrixAnalytics** might be missing, disabled, or might refer to the wrong network port.		The Citrix firewall rule **CitrixAnalytics** might be missing, disabled, or might refer to the wrong network port.		Run the service executable with the command line argument -CONFIGUREFIREWALL to repair the firewall configuration.	Warning
6088dcae-6d5f-4604-88a2-10ea7c2db0c1	Incorrect firewall configuration for Citrix ApplLibrary Service	The Citrix firewall rule **CitrixAppLibrary** might be missing, disabled, or might refer to the wrong network port.		The Citrix firewall rule **CitrixAppLibrary** might be missing, disabled, or might refer to the wrong network port.		Run the service executable with the command line argument -CONFIGUREFIREWALL to repair the firewall configuration.	Warning
cccd56b-d8bc-4c57-a5a0-6cc6e40e39f	Incorrect firewall configuration for Citrix Broker Service	The Citrix firewall rule **Citrix Broker Service (TCP-In)** might be missing, disabled, or might refer to the wrong network port.		The Citrix firewall rule **Citrix Broker Service (TCP-In)** might be missing, disabled, or might refer to the wrong network port.		Run the service executable with the command line argument -CONFIGUREFIREWALL to repair the firewall configuration.	Warning
c68D426-2ffa-4b8c-a23f-7668a9a903a3	Incorrect firewall configuration for Citrix Configuration Service	The Citrix firewall rule **CitrixConfigurationService** might be missing, disabled, or might refer to the wrong network port.		The Citrix firewall rule **CitrixConfigurationService** might be missing, disabled, or might refer to the wrong network port.		Run the service executable with the command line argument -CONFIGUREFIREWALL to repair the firewall configuration.	Warning
4571f91a-606d-475d-829e-e17b33095e4	Incorrect firewall configuration for Citrix Configuration Logging Service	The Citrix firewall rule **Citrix Configuration Logging** might be missing, disabled, or might refer to the wrong network port.		The Citrix firewall rule **Citrix Configuration Logging** might be missing, disabled, or might refer to the wrong network port.		Run the service executable with the command line argument -CONFIGUREFIREWALL to repair the firewall configuration.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
4c701c81-6d38-4e9b-a97f-f58b1ed7271	Incorrect firewall configuration for Citrix Delegated Administration Service	The Citrix firewall rule **CitrixDelegatedAdmin** might be missing, disabled, or might refer to the wrong network port.		The Citrix firewall rule **CitrixDelegatedAdmin** might be missing, disabled, or might refer to the wrong network port.		Run the service executable with the command line argument -CONFIGUREFIREWALL to repair the firewall configuration.	Warning
9b9844b5-6334-4bac-8759-e629020e718b	Incorrect firewall configuration for Citrix Environment Test Service	The Citrix firewall rule **CitrixEnvTest** might be missing, disabled, or might refer to the wrong network port.		The Citrix firewall rule **CitrixEnvTest** might be missing, disabled, or might refer to the wrong network port.		Run the service executable with the command line argument -CONFIGUREFIREWALL to repair the firewall configuration.	Warning
20a7b02f-68a7-48a5-a815-04e38092cd9c	Incorrect firewall configuration for Citrix Host Availability Service	The Citrix firewall rule **CitrixHostService** might be missing, disabled, or might refer to the wrong network port.		The Citrix firewall rule **CitrixHostService** might be missing, disabled, or might refer to the wrong network port.		Run the service executable with the command line argument -CONFIGUREFIREWALL to repair the firewall configuration.	Warning
b8a82511-ba11-4b1f-ad68-ad3f35ccdae4	Incorrect firewall configuration for Citrix Machine Creation Service	The Citrix firewall rule **CitrixMachineCreationService** might be missing, disabled, or might refer to the wrong network port.		The Citrix firewall rule **CitrixMachineCreationService** might be missing, disabled, or might refer to the wrong network port.		Run the service executable with the command line argument -CONFIGUREFIREWALL to repair the firewall configuration.	Warning
fe9361e1-434c-4d89-bb0a-20ed341235f	Incorrect firewall configuration for Citrix Monitor Service	The Citrix firewall rule **CitrixMonitor** might be missing, disabled, or might refer to the wrong network port.		The Citrix firewall rule **CitrixMonitor** might be missing, disabled, or might refer to the wrong network port.		Run the service executable with the command line argument -CONFIGUREFIREWALL to repair the firewall configuration.	Warning
83184dea-5cf4-49cd-b437-61eb8b63aa7	Incorrect firewall configuration for Citrix Storefront Service	The Citrix firewall rule **CitrixStorefront** might be missing, disabled, or might refer to the wrong network port.		The Citrix firewall rule **CitrixStorefront** might be missing, disabled, or might refer to the wrong network port.		Run the service executable with the command line argument -CONFIGUREFIREWALL to repair the firewall configuration.	Warning
45bd71ef-b9f2-471e-9716-7c5a9ab24f35	Citrix AD Identify Service cannot reach the database	The Citrix AD Identify Service failed to connect to the database {{dbName}} on server {{dbServerName}} with the current connection details. This issue affects all Delivery Controllers in the Site.	The database name is {{dbName}} ; the database server name is {{dbServerName}} .	The Citrix AD Identify Service failed to connect to the database with the current connection details. This issue affects all Delivery Controllers in the Site.		Verify the database connection settings and user permissions are correct. Additionally, specify a valid connection string for Citrix {{ServiceName}} Service. To do this, run the Set-ServicePrefxDmConnection cmdlet to set the connection string to \$null and then reset the connection string.	Error
fe945783-c1bc-42be-a0b0-68451cdd9d17	Citrix Analytics Service cannot reach the database	The Citrix Analytics Service failed to connect to the database {{dbName}} on server {{dbServerName}} with the current connection details. This issue affects all Delivery Controllers in the Site.	The database name is {{dbName}} ; the database server name is {{dbServerName}} .	The Citrix Analytics Service failed to connect to the database with the current connection details. This issue affects all Delivery Controllers in the Site.		Verify the database connection settings and user permissions are correct.	Error
230e77ef-0091-4f1f51e8-789b173f5a4	Citrix App Library Service cannot reach the database	The Citrix App Library Service failed to connect to the database {{dbName}} on server {{dbServerName}} with the current connection details. This issue affects all Delivery Controllers in the Site.	The database name is {{dbName}} ; the database server name is {{dbServerName}} .	The Citrix App Library Service failed to connect to the database with the current connection details. This issue affects all Delivery Controllers in the Site.		Verify the database connection settings and user permissions are correct.	Error
9d3d38e-d433-4f25-90bd-728a894b9506	Citrix Broker Service cannot reach the database	The Citrix Broker Service failed to connect to the database {{dbName}} on server {{dbServerName}} with the current connection details. This issue affects all Delivery Controllers in the Site.	The database name is {{dbName}} ; the database server name is {{dbServerName}} .	The Citrix Broker Service failed to connect to the database with the current connection details. This issue affects all Delivery Controllers in the Site.		Verify the database connection settings and user permissions are correct.	Error
f08e90ed-e17c-4a8a-8314-3384cf3a016	Citrix Configuration Service cannot reach the database	The Citrix Configuration Service failed to connect to the database {{dbName}} on server {{dbServerName}} with the current connection details. This issue affects all Delivery Controllers in the Site.	The database name is {{dbName}} ; the database server name is {{dbServerName}} .	The Citrix Configuration Service failed to connect to the database with the current connection details. This issue affects all Delivery Controllers in the Site.		Verify the database connection settings and user permissions are correct.	Error
96e6194d-a9d9-4874-bf0c-3f5485c68b33	Citrix Configuration Logging Service cannot reach the database	The Citrix Configuration Logging Service failed to connect to the database {{dbName}} on server {{dbServerName}} with the current connection details. This issue affects all Delivery Controllers in the Site.	The database name is {{dbName}} ; the database server name is {{dbServerName}} .	The Citrix Configuration Logging Service failed to connect to the database with the current connection details. This issue affects all Delivery Controllers in the Site.		Verify the database connection settings and user permissions are correct.	Error

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
dbdf10a4-e3a2-4f08-ab5b-9d61213ec9aa	Citrix Delegated Administration Service cannot reach the database	The Citrix Delegated Administration Service failed to connect to the database {{dbName}} on server {{dbServerName}} with the current connection details. This issue affects all Delivery Controllers in the Site.	The database name is {{dbName}}; the database server name is {{dbServerName}}.	The Citrix Delegated Administration Service failed to connect to the database with the current connection details. This issue affects all Delivery Controllers in the Site.		Verify the database connection settings and user permissions are correct.	Error
82bd0969-a080-4369-a1a8-97f809d7a52	Citrix Environment Test Service cannot reach the database	The Citrix Environment Test Service failed to connect to the database {{dbName}} on server {{dbServerName}} with the current connection details. This issue affects all Delivery Controllers in the Site.	The database name is {{dbName}}; the database server name is {{dbServerName}}.	The Citrix Environment Test Service failed to connect to the database with the current connection details. This issue affects all Delivery Controllers in the Site.		Verify the database connection settings and user permissions are correct.	Error
24882f0f-7093-4496-a3ee-133012aae1b9	Citrix Host Availability Service cannot reach the database	The Citrix Host Availability Service failed to connect to the database {{dbName}} on server {{dbServerName}} with the current connection details. This issue affects all Delivery Controllers in the Site.	The database name is {{dbName}}; the database server name is {{dbServerName}}.	The Citrix Host Availability Service failed to connect to the database with the current connection details. This issue affects all Delivery Controllers in the Site.		Verify the database connection settings and user permissions are correct.	Error
3ca1229d-f57-4c10-8372-821ac9948412	Citrix Machine Creation Service cannot reach the database	The Citrix Machine Creation Service failed to connect to the database {{dbName}} on server {{dbServerName}} with the current connection details. This issue affects all Delivery Controllers in the Site.	The database name is {{dbName}}; the database server name is {{dbServerName}}.	The Citrix Machine Creation Service failed to connect to the database with the current connection details. This issue affects all Delivery Controllers in the Site.		Verify the database connection settings and user permissions are correct.	Error
0be97ac5-5183-4caa-b2ed-fba675b0a2e	Citrix Monitor Service cannot reach the database	The Citrix Monitor Service failed to connect to the database {{dbName}} on server {{dbServerName}} with the current connection details. This issue affects all Delivery Controllers in the Site.	The database name is {{dbName}}; the database server name is {{dbServerName}}.	The Citrix Monitor Service failed to connect to the database with the current connection details. This issue affects all Delivery Controllers in the Site.		Verify the database connection settings and user permissions are correct.	Error
d2874859-8172-453a-beaa-a393baee1ca	Citrix Storefront Service cannot reach the database	The Citrix Storefront Service failed to connect to the database {{dbName}} on server {{dbServerName}} with the current connection details. This issue affects all Delivery Controllers in the Site.	The database name is {{dbName}}; the database server name is {{dbServerName}}.	The Citrix Storefront Service failed to connect to the database with the current connection details. This issue affects all Delivery Controllers in the Site.		Verify the database connection settings and user permissions are correct.	Error
db3e5b8b-beba-4a93-acdf-f70a440ca17	Database updates are not present in database for Citrix ADIdentity Service	Database updates (XDU's) on the file system have not been applied to the database for the Citrix AD Identity Service. The Citrix AD Identity Service handles all Active Directory computer accounts (identities) related to XenApp and XenDesktop virtual and physical machines.		Database updates (XDU's) on the file system have not been applied to the database for the Citrix AD Identity Service. The Citrix AD Identity Service handles all Active Directory computer accounts (identities) related to XenApp and XenDesktop virtual and physical machines.	[Bas Van Kaam](http://www.basvankaam.com), Citrix Technology Professional	To resolve this issue, perform the following actions: 1. On the affected machine, restart the Citrix AD Identity Service to discover the XDU's: Click **Start**, type **services.msc**, and then press **ENTER**. From the Services console, select **Citrix AD Identity Service**, and then click **Restart**. 2. To apply the XDU's, perform a Site upgrade from Citrix Studio. For more information, see [CTX215948](http://support.citrix.com/article/CTX215948). 3. If the XDU files are corrupted, repair the service: On the command line, enter <code>msiexec /f D:\XDMage\64\Citrix Desktop Delivery Controller\ADIdentity_Service_x64.msi</code> 4. If installing the service does not resolve this issue, rebuild the Desktop Controller	Warning
7a92b1a4-69d4-46d9-830a-097862bd09	Database updates are not present in database for Citrix Analytics Service	Database updates (XDU's) on the file system have not been applied to the database for Citrix Analytics Service.		Database updates (XDU's) on the file system have not been applied to the database for Citrix Analytics Service.		Verify the database connection settings for the service are correct and restart the service to discover the XDU's. To apply the XDU's, perform a Site upgrade from Citrix Studio. For more information, see [CTX215948](http://support.citrix.com/article/CTX215948).	Warning
6106962-885f-4c42-8c42-a6d2712a717d	Database updates are not present in database for Citrix App Library Service	Database updates (XDU's) on the file system have not been applied to the database for Citrix App Library Service.		Database updates (XDU's) on the file system have not been applied to the database for Citrix App Library Service.		Verify the database connection settings for the service are correct and restart the service to discover the XDU's. To apply the XDU's, perform a Site upgrade from Citrix Studio. For more information, see [CTX215948](http://support.citrix.com/article/CTX215948).	Warning
54746746-876d-4a58-a86d-6857c643131	Database updates are not present in database for Citrix Broker Service	Database updates (XDU's) on the file system have not been applied to the database for Citrix Broker Service.		Database updates (XDU's) on the file system have not been applied to the database for Citrix Broker Service.		Verify the database connection settings for the service are correct and restart the service to discover the XDU's. To apply the XDU's, perform a Site upgrade from Citrix Studio. For more information, see [CTX215948](http://support.citrix.com/article/CTX215948).	Warning
c205e6b9-98cd-44a2-9726-1c83a3360f51	Database updates are not present in database for Citrix Configuration Service	Database updates (XDU's) on the file system have not been applied to the database for Citrix Configuration Service.		Database updates (XDU's) on the file system have not been applied to the database for Citrix Configuration Service.		Verify the database connection settings for the service are correct and restart the service to discover the XDU's. To apply the XDU's, perform a Site upgrade from Citrix Studio. For more information, see [CTX215948](http://support.citrix.com/article/CTX215948).	Warning
5e252446-693d-4478-8be5-f79211555d32	Database updates are not present in database for Citrix Configuration Logging Service	Database updates (XDU's) on the file system have not been applied to the database for Citrix Configuration Logging Service.		Database updates (XDU's) on the file system have not been applied to the database for Citrix Configuration Logging Service.		Verify the database connection settings for the service are correct and restart the service to discover the XDU's. To apply the XDU's, perform a Site upgrade from Citrix Studio. For more information, see [CTX215948](http://support.citrix.com/article/CTX215948).	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
6933065f-ac26-433a-8b4f-86a83ff9da7	Database updates are not present in database for Citrix Delegated Administration Service	Database updates (XDU)s on the file system have not been applied to the database for Citrix Delegated Administration Service.		Database updates (XDU)s on the file system have not been applied to the database for Citrix Delegated Administration Service.		Verify the database connection settings for the service are correct and restart the service to discover the XDU. To apply the XDU, perform a Site upgrade from Citrix Studio. For more information, see [CTX215948](https://support.citrix.com/article/CTX215948).	Warning
7a768514-6d24-44a9-b5bd-385e5abac8a3	Database updates are not present in database for Citrix Environment Test Service	Database updates (XDU)s on the file system have not been applied to the database for Citrix ADIdentity Service.		Database updates (XDU)s on the file system have not been applied to the database for Citrix ADIdentity Service.		Verify the database connection settings for the service are correct and restart the service to discover the XDU. To apply the XDU, perform a Site upgrade from Citrix Studio. For more information, see [CTX215948](https://support.citrix.com/article/CTX215948).	Warning
f5994775-451e-48ef-9509-1b1d1867ce17	Database updates are not present in database for Citrix Host Availability Service	Database updates (XDU)s on the file system have not been applied to the database for Citrix Host Availability Service.		Database updates (XDU)s on the file system have not been applied to the database for Citrix Host Availability Service.		Verify the database connection settings for the service are correct and restart the service to discover the XDU. To apply the XDU, perform a Site upgrade from Citrix Studio. For more information, see [CTX215948](https://support.citrix.com/article/CTX215948).	Warning
a8870db-9891-4247-95c8-075fa887d93	Database updates are not present in database for Citrix Machine Creation Service	Database updates (XDU)s on the file system have not been applied to the database for Citrix Machine Creation Service.		Database updates (XDU)s on the file system have not been applied to the database for Citrix Machine Creation Service.		Verify the database connection settings for the service are correct and restart the service to discover the XDU. To apply the XDU, perform a Site upgrade from Citrix Studio. For more information, see [CTX215948](https://support.citrix.com/article/CTX215948).	Warning
e14dbe8d-b057-4237-a70d-6956191b7d46	Database updates are not present in database for Citrix Monitor Service	Database updates (XDU)s on the file system have not been applied to the database for Citrix Monitor Service.		Database updates (XDU)s on the file system have not been applied to the database for Citrix Monitor Service.		Verify the database connection settings for the service are correct and restart the service to discover the XDU. To apply the XDU, perform a Site upgrade from Citrix Studio. For more information, see [CTX215948](https://support.citrix.com/article/CTX215948).	Warning
b68995c2-c979-4ec9-967a-65bf64da65f	Database updates are not present in database for Citrix Storefront Service	Database updates (XDU)s on the file system have not been applied to the database for Citrix Storefront Service.		Database updates (XDU)s on the file system have not been applied to the database for Citrix Storefront Service.		Verify the database connection settings for the service are correct and restart the service to discover the XDU. To apply the XDU, perform a Site upgrade from Citrix Studio. For more information, see [CTX215948](https://support.citrix.com/article/CTX215948).	Warning
5e7b3960-e9f7-4156-bf76-fa30b9f3720c	LogToCDF key is missing for Citrix AD Identity Service	The LogToCDF key is missing for the Citrix AD Identity Service. This key is required to enable CDF tracing.		The LogToCDF key is missing for the Citrix AD Identity Service. This key is required to enable CDF tracing.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX200341](https://support.citrix.com/article/CTX200341) and [CTX11961](https://support.citrix.com/article/CTX11961) in the Citrix Knowledge Center.	Warning
7d4eb0ee-fa39-4e03-a3de-ee367ce0b0c4	LogToCDF key is missing for Citrix Analytics Service	The LogToCDF key is missing for the Citrix Analytics Service. This key is required to enable CDF tracing.		The LogToCDF key is missing for the Citrix Analytics Service. This key is required to enable CDF tracing.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX200341](https://support.citrix.com/article/CTX200341) and [CTX11961](https://support.citrix.com/article/CTX11961) in the Citrix Knowledge Center.	Warning
88c58059-7927-4c04-9ca0-d38b8ee25aed	LogToCDF key is missing for Citrix App Library Service	The LogToCDF key is missing for the Citrix App Library Service. This key is required to enable CDF tracing.		The LogToCDF key is missing for the Citrix App Library Service. This key is required to enable CDF tracing.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX200341](https://support.citrix.com/article/CTX200341) and [CTX11961](https://support.citrix.com/article/CTX11961) in the Citrix Knowledge Center.	Warning
f03bf81-b562-43c5-8e46-a9573864538	LogToCDF key is missing for Citrix Broker Service	The LogToCDF key is missing for Citrix Broker Service. This key is required to enable CDF tracing.		The LogToCDF key is missing for Citrix Broker Service. This key is required to enable CDF tracing.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX200341](https://support.citrix.com/article/CTX200341) and [CTX11961](https://support.citrix.com/article/CTX11961) in the Citrix Knowledge Center.	Warning
2b242728-7bb8-40f5-8019-f6f69296be64	LogToCDF key is missing for Citrix Configuration Service	The LogToCDF key is missing for the Citrix Configuration Service. This key is required to enable CDF tracing.		The LogToCDF key is missing for the Citrix Configuration Service. This key is required to enable CDF tracing.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX200341](https://support.citrix.com/article/CTX200341) and [CTX11961](https://support.citrix.com/article/CTX11961) in the Citrix Knowledge Center.	Warning
489e7b2f-5748-43fe-aaf4-d51047bbe3ef	LogToCDF key is missing for Citrix Configuration Logging Service	The LogToCDF key is missing for the Citrix Configuration Logging Service. This key is required to enable CDF tracing.		The LogToCDF key is missing for the Citrix Configuration Logging Service. This key is required to enable CDF tracing.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX200341](https://support.citrix.com/article/CTX200341) and [CTX11961](https://support.citrix.com/article/CTX11961) in the Citrix Knowledge Center.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
5e0afe1-39bb-47b3-9031-e335affb1d0c	LogToCDF key is missing for Citrix Delegated Administration Service	The LogToCDF key is missing for the Citrix Delegated Administration Service. This key is required to enable CDF tracing.		The LogToCDF key is missing for the Citrix Delegated Administration Service. This key is required to enable CDF tracing.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX20034]([https://support.citrix.com/article/CTX20034]) and [CTX11961]([https://support.citrix.com/article/CTX11961]) in the Citrix Knowledge Center.	Warning
a66985d3-7538-4f19-ad06-32765a2bbe8f	LogToCDF key is missing for Citrix Environment Test Service	The LogToCDF key is missing for the Citrix Environment Test Service. This key is required to enable CDF tracing.		The LogToCDF key is missing for the Citrix Environment Test Service. This key is required to enable CDF tracing.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX20034]([https://support.citrix.com/article/CTX20034]) and [CTX11961]([https://support.citrix.com/article/CTX11961]) in the Citrix Knowledge Center.	Warning
aea95cd-8996-4e09-9769-e54ab47cb15d	LogToCDF key is missing for Citrix Host Availability Service	The LogToCDF key is missing for the Citrix Host Availability Service. This key is required to enable CDF tracing.		The LogToCDF key is missing for the Citrix Host Availability Service. This key is required to enable CDF tracing.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX20034]([https://support.citrix.com/article/CTX20034]) and [CTX11961]([https://support.citrix.com/article/CTX11961]) in the Citrix Knowledge Center.	Warning
1522aded-1216-403e-a5ca-69691377bb51	LogToCDF key is missing for Citrix Machine Creation Service	The LogToCDF key is missing for the Citrix Machine Creation Service. This key is required to enable CDF tracing.		The LogToCDF key is missing for the Citrix Machine Creation Service. This key is required to enable CDF tracing.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX20034]([https://support.citrix.com/article/CTX20034]) and [CTX11961]([https://support.citrix.com/article/CTX11961]) in the Citrix Knowledge Center.	Warning
e01ce064-06e8-41ac-938b-3cfe422d78d4	LogToCDF key is missing for Citrix Monitor Service	The LogToCDF key is missing for the Citrix Monitor Service. This key is required to enable CDF tracing.		The LogToCDF key is missing for the Citrix Monitor Service. This key is required to enable CDF tracing.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX20034]([https://support.citrix.com/article/CTX20034]) and [CTX11961]([https://support.citrix.com/article/CTX11961]) in the Citrix Knowledge Center.	Warning
ba4023b-ebfc-46fe-9e47-39d581b0b04	LogToCDF key is missing for Citrix Storefront Service	The LogToCDF key is missing for the Citrix Storefront Service. This key is required to enable CDF tracing.		The LogToCDF key is missing for the Citrix Storefront Service. This key is required to enable CDF tracing.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX20034]([https://support.citrix.com/article/CTX20034]) and [CTX11961]([https://support.citrix.com/article/CTX11961]) in the Citrix Knowledge Center.	Warning
0e280dbe-e95c-4909-8242-8d57237153f5	LogToCDF key is not enabled for Citrix AD Identity Service	The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix AD Identity Service.		The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix AD Identity Service.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX20034]([https://support.citrix.com/article/CTX20034]) and [CTX11961]([https://support.citrix.com/article/CTX11961]) in the Citrix Knowledge Center.	Warning
19757ac2-6659-49730-b131abb6caae	LogToCDF key is not enabled for Citrix Analytics Service	The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Analytics Service.		The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Analytics Service.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX20034]([https://support.citrix.com/article/CTX20034]) and [CTX11961]([https://support.citrix.com/article/CTX11961]) in the Citrix Knowledge Center.	Warning
aa5f7abd-237e-4c9d-920f-5d618959a02f	LogToCDF key is not enabled for Citrix AppLibrary Service	The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix App Library Service.		The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix App Library Service.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX20034]([https://support.citrix.com/article/CTX20034]) and [CTX11961]([https://support.citrix.com/article/CTX11961]) in the Citrix Knowledge Center.	Warning
4e772ba9-e96e-4c6b-a105-084f2614457e	LogToCDF key is not enabled for Citrix Broker Service	The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Broker Service.		The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Broker Service.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX20034]([https://support.citrix.com/article/CTX20034]) and [CTX11961]([https://support.citrix.com/article/CTX11961]) in the Citrix Knowledge Center.	Warning
a0e4440-005b-4f57-872c-d8868d1773d5	LogToCDF key is not enabled for Citrix Configuration Service	The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Configuration Service.		The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Configuration Service.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX20034]([https://support.citrix.com/article/CTX20034]) and [CTX11961]([https://support.citrix.com/article/CTX11961]) in the Citrix Knowledge Center.	Warning
d617777a-c0d6-4601-ade7-a24f0f12a05	LogToCDF key is not enabled for Citrix Configuration Logging Service	The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Configuration Logging Service.		The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Configuration Logging Service.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX20034]([https://support.citrix.com/article/CTX20034]) and [CTX11961]([https://support.citrix.com/article/CTX11961]) in the Citrix Knowledge Center.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
35d08679-91cc-42d3-abde-1e8f21116654	LogToCDF key is not enabled for Citrix Delegated Administration Service	The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Delegated Administration Service.		The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Delegated Administration Service.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX20034]([https://support.citrix.com/article/CTX20034]) and [CTX11961]([https://support.citrix.com/article/CTX11961]) in the Citrix Knowledge Center.	Warning
21943019-7303-47cc-ba20-b9608c107788	LogToCDF key is not enabled for Citrix Environment Test Service	The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Environment Test Service.		The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Environment Test Service.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX20034]([https://support.citrix.com/article/CTX20034]) and [CTX11961]([https://support.citrix.com/article/CTX11961]) in the Citrix Knowledge Center.	Warning
82870350-722e-488c-a09c-cdf8e456dea	LogToCDF key is not enabled for Citrix Host Availability Service	The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Host Availability Service.		The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Host Availability Service.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX20034]([https://support.citrix.com/article/CTX20034]) and [CTX11961]([https://support.citrix.com/article/CTX11961]) in the Citrix Knowledge Center.	Warning
e0029081-3793-46d9-95c-6b286274a1d	LogToCDF key is not enabled for Citrix Machine Creation Service	The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Machine Creation Service.		The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Machine Creation Service.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX20034]([https://support.citrix.com/article/CTX20034]) and [CTX11961]([https://support.citrix.com/article/CTX11961]) in the Citrix Knowledge Center.	Warning
b688515-532a-4520-8a51-37a46100e3e4	LogToCDF key is not enabled for Citrix Monitor Service	The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Monitor Service.		The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Monitor Service.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX20034]([https://support.citrix.com/article/CTX20034]) and [CTX11961]([https://support.citrix.com/article/CTX11961]) in the Citrix Knowledge Center.	Warning
bda4046-684c-49c9-9f79-6e75f588e24	LogToCDF key is not enabled for Citrix Storefront Service	The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Storefront Service.		The LogToCDF key value is not set correctly to enable CDF tracing for the Citrix Storefront Service.		Use the New-XdLogTrace.ps1 script to enable persistent CDF tracing or use the CDFControl tool to capture CDF traces in your deployment. For more information, see [CTX20034]([https://support.citrix.com/article/CTX20034]) and [CTX11961]([https://support.citrix.com/article/CTX11961]) in the Citrix Knowledge Center.	Warning
4e2fcb3-57a4-48a2-a9d0-31e99de3757f	Database not configured for Citrix AD Identity Service	Database connection settings for the Citrix AD Identity Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Database connection settings for the Citrix AD Identity Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Use the Set-AcctDBConnection cmdlet to set the connection string to \$null and then specify a valid connection string for the Citrix AD Identity Service. For example: Set-AcctDBConnection \$null Set-AcctDBConnection "Server={SERVERNAME};Initial Catalog={CATALOG};Integrated Security=True"	Error
f89fe9c1-ecdd-4b15-a564-616601469940	Database not configured for Citrix Analytics Service	Database connection settings for the Citrix Analytics Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Database connection settings for the Citrix Analytics Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Use the Set-AnalyticsDBConnection cmdlet to set the connection string to \$null and then specify a valid connection string for the Citrix Analytics Service. For example: Set-AnalyticsDBConnection \$null Set-AnalyticsDBConnection "Server={SERVERNAME};Initial Catalog={CATALOG};Integrated Security=True"	Error
4e3a7fcb-e6f0-49cb-82c0-e2bb60626d58	Database not configured for Citrix App Library Service	Database connection settings for the Citrix App Library Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Database connection settings for the Citrix App Library Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Use the Set-AppLibDBConnection cmdlet to set the connection string to \$null and then specify a valid connection string for the Citrix App Library Service. For example: Set-AppLibDBConnection \$null Set-AppLibDBConnection "Server={SERVERNAME};Initial Catalog={CATALOG};Integrated Security=True"	Error
351c99e1-4aca-4bbe-a7d3-b670cdeb919	Database not configured for Citrix Broker Service	Database connection settings for the Citrix Broker Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Database connection settings for the Citrix Broker Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Use the Set-BrokerDBConnection cmdlet to set the connection string to \$null and then specify a valid connection string for the Citrix Broker Service. For example: Set-BrokerDBConnection \$null Set-BrokerDBConnection "Server={SERVERNAME};Initial Catalog={CATALOG};Integrated Security=True"	Error
16821422-4432-40b9-a869-e28551ae3834	Database not configured for Citrix Configuration Service	Database connection settings for the Citrix Configuration Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Database connection settings for the Citrix Configuration Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Use the Set-ConfigDBConnection cmdlet to set the connection string to \$null and then specify a valid connection string for the Citrix Configuration Service. For example: Set-ConfigDBConnection \$null Set-ConfigDBConnection "Server={SERVERNAME};Initial Catalog={CATALOG};Integrated Security=True"	Error
1369854f-612b-4f68-b095-9cc3a9c36c92	Database not configured for Citrix Configuration Logging Service	Database connection settings for the Citrix Configuration Logging Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Database connection settings for the Citrix Configuration Logging Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Use the Set-LogDBConnection cmdlet to set the connection string to \$null and then specify a valid connection string for the Citrix Configuration Logging Service. For example: Set-LogDBConnection \$null Set-LogDBConnection "Server={SERVERNAME};Initial Catalog={CATALOG};Integrated Security=True"	Error

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
aadee56-8c0d-4079-82c-313dc98a898	Database not configured for Citrix Delegated Administration Service	Database connection settings for the Citrix Delegated Administration Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Database connection settings for the Citrix Delegated Administration Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Use the Set-AdminDBConnection cmdlet to set the connection string to \$null and then specify a valid connection string for the Citrix Delegated Administration Service. For example: Set-AdminDBConnection \$null Set-AdminDBConnection "Server={SERVERNAME};Initial Catalog={CATALOG};Integrated Security=True"	Error
89c5edab-093d-44b2-9ef0-f6f434b979c9	Database not configured for Citrix Environment Test Service	Database connection settings for the Citrix Environment Test Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Database connection settings for the Citrix Environment Test Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Use the Set-EnvTestDBConnection cmdlet to set the connection string to \$null and then specify a valid connection string for the Citrix Environment Test Service. For example: Set-EnvTestDBConnection \$null Set-EnvTestDBConnection "Server={SERVERNAME};Initial Catalog={CATALOG};Integrated Security=True"	Error
574630d-6611-4e87-8f06-77731435ed27	Database not configured for Citrix Host Availability Service	Database connection settings for the Host Availability Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Database connection settings for the Host Availability Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Use the Set-HypDBConnection cmdlet to set the connection string to \$null and then specify a valid connection string for the Citrix Host Availability Service. For example: Set-HypDBConnection \$null Set-HypDBConnection "Server={SERVERNAME};Initial Catalog={CATALOG};Integrated Security=True"	Error
1c7d60f8-f52d-4ab6-8ef2-9c7e7775eb01	Database not configured for Citrix Machine Creation Service	Database connection settings for the Citrix Machine Creation Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Database connection settings for the Citrix Machine Creation Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Use the Set-ProviderDBConnection cmdlet to set the connection string to \$null and then specify a valid connection string for the Citrix Machine Creation Service. For example: Set-ProviderDBConnection \$null Set-ProviderDBConnection "Server={SERVERNAME};Initial Catalog={CATALOG};Integrated Security=True"	Error
c27d04df-41cb-4662-a27c-88ce19188f74	Database not configured for Citrix Monitor Service	Database connection settings for the Citrix Monitor Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Database connection settings for the Citrix Monitor Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Use the Set-MonitorDBConnection cmdlet to set the connection string to \$null and then specify a valid connection string for the Citrix Monitor Service. For example: Set-MonitorDBConnection \$null Set-MonitorDBConnection "Server={SERVERNAME};Initial Catalog={CATALOG};Integrated Security=True"	Error
7796cd89-8472-4e33-bf9a-b02f25352c6b	Database not configured for Citrix Storefront Service	Database connection settings for the Citrix Storefront Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Database connection settings for the Citrix Storefront Service are either invalid or not configured. This issue affects all Delivery Controllers in the Site.		Use the Set-SDBConnection cmdlet to set the connection string to \$null and then specify a valid connection string for the Citrix Storefront Service. For example: Set-SDBConnection \$null Set-SDBConnection "Server={SERVERNAME};Initial Catalog={CATALOG};Integrated Security=True"	Error
18f0382-1319-4666-978f-0fb7dbafef40	Hypervisor connection in maintenance mode for Citrix Host Service	The hypervisor connection for the Citrix Host Service is in maintenance mode. This issue affects all Delivery Controllers in the Site.		The hypervisor connection for the Citrix Host Service is in maintenance mode. This issue affects all Delivery Controllers in the Site.		Turn off maintenance mode for the connection. For more information, see [Connections and resources](http://docs.citrix.com/en-us/learnapp-and-xmddesktop/7-11/manage-deployment/connections.html#ipar_anchor_title_3c29) on the Citrix Product Documentation web site.	Error
2268e61e-9f5e-4cac-a526-92eb37a060a0	Hypervisor connection could not be resolved for Citrix Host Service	The hypervisor connection ([HypervisorConnection]) for the Citrix Host Service could not be found on the system. This issue affects all Delivery Controllers in the Site.	The connection is ([HypervisorConnection]).	The hypervisor connection ([HypervisorConnection]) for the Citrix Host Service could not be found on the system. This issue affects all Delivery Controllers in the Site.		Verify the database is being used by this Delivery Site. Ensure that the user has sufficient permissions to retrieve hypervisor connections.	Error
c09623bb-9085-444c-b535-80224aca7289	Unexpected error for Citrix Host Service test	The Citrix Host Service test failed for an unknown reason. This issue affects all Delivery Controllers in the Site.		The Citrix Host Service test failed for an unknown reason. This issue affects all Delivery Controllers in the Site.		Contact Citrix Support for assistance.	Error
1ba09ec5-1c97-4c57-b574-6b2350b064b0	Null object for Citrix Host Service test	A host connection or hosting unit was not specified for Citrix Host Service tests. This issue affects all Delivery Controllers in the Site.		A host connection or hosting unit was not specified for Citrix Host Service tests. This issue affects all Delivery Controllers in the Site.		Specify a host connection or hosting unit for the test.	Error
365a69fe-6eaa-45df-95ec-57c599548eb	Invalid host connection identifier for the Citrix Host Service	The host connection or hosting unit for the Citrix Host Service uses an invalid identifier. The Host Service manages all connections between the physical hosts, Delivery Controllers, and the underlying hypervisor or cloud host platform. The Host Service is also responsible for discovering and managing the connections and configurations of the hypervisor, network and storage that are required and used by machine provisioning operations.		The host connection or hosting unit for the Citrix Host Service uses an invalid identifier. The Host Service manages all connections between the physical hosts, Delivery Controllers, and the underlying hypervisor or cloud host platform. The Host Service is also responsible for discovering and managing the connections and configurations of the hypervisor, network and storage that are required and used by machine provisioning operations.	[Bas Van Kaam](http://www.basvankaam.com), Citrix Technology Professional	Specify the correct GUID of the host connection or hosting unit.	Error
91d27add-0202-49b9-81c2-6d1d3282b968	Object not found for Citrix Host Service	The host connection or hosting unit for the Citrix Host Service was not found. This issue affects all Delivery Controllers in the Site.		The host connection or hosting unit for the Citrix Host Service was not found. This issue affects all Delivery Controllers in the Site.	<i>Revised from 7.3.3 version that makes on the Citrix XenDesktop 7.3.3</i>	Specify the GUID for an existing host connection or hosting unit.	Error

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
64abc13e-62b7-421f-b230-1e63aa25e94d	SCVMM console not installed for Citrix Host Service	The SCVMM Administrator Console is not installed on the same machine as the Citrix Host Service. This issue affects all Delivery Controllers in the Site.		The SCVMM Administrator Console is not installed on the same machine as the Citrix Host Service. This issue affects all Delivery Controllers in the Site.		Install the SCVMM Administrator Console (2012 minimum) on the same machine as all instances of the Citrix Host Service.	Error
4963692d-7262-4982-9f05-d24f24206077	Hypervisor connection could not be established for Citrix Host Service	A connection could not be established with the hypervisor for the Citrix Host Service. This issue affects all Delivery Controllers in the Site.		A connection could not be established with the hypervisor for the Citrix Host Service. This issue affects all Delivery Controllers in the Site.		Verify the host connection details for the hypervisor are correct.	Error
2825d47f-89f8-4918-a16f-7de6e5f0628	Hypervisor plug-in does not support Citrix Host Service environment testing	The environment test was not run because the hypervisor plug-in for the connection does not support environment tests for the Citrix Host Service. This issue affects all Delivery Controllers in the Site.		The environment test was not run because the hypervisor plug-in for the connection does not support environment tests for the Citrix Host Service. This issue affects all Delivery Controllers in the Site.		This test is not applicable to the Site configuration.	Error
b6124a3e-9c47-42df-bd9f-4c6b48b2f096	Wrong hypervisor for Citrix Host Service environment testing	The environment test for the Citrix Host Service was not run because the test is not supported for this hypervisor type. This issue affects all Delivery Controllers in the Site.		The environment test for the Citrix Host Service was not run because the test is not supported for this hypervisor type. This issue affects all Delivery Controllers in the Site.		This test is not applicable to the Site configuration.	Error
b25d66b0-47e3-4b84-a75d-4c9256342834	Unexpected plug-in test result	The plug-in that was used to create the hypervisor connection did not run a test on the object type. This issue affects all Delivery Controllers in the Site.		The plug-in that was used to create the hypervisor connection did not run a test on the object type. This issue affects all Delivery Controllers in the Site.		If the plug-in used is owned by Citrix, contact Citrix Support for assistance. If the plug-in used was created by a third party, contact the owner of the plug-in for assistance.	Error
7886007-cfb8-4d7e-be33-3566e912c621	VMware vCenter endpoint expected	A connection made to the supplied address found a VMware ESX server where a vCenter server was expected. This issue affects all Delivery Controllers in the Site.		A connection made to the supplied address found a VMware ESX server where a vCenter server was expected. This issue affects all Delivery Controllers in the Site.		Specify the address of a VMware vCenter server for this connection.	Error
7e191cc4-6c55-4ebb-9ebb-d61889c7b0f	Invalid credentials for hypervisor connection	The user name and password combination supplied for the hypervisor connection were not recognized. This issue affects all Delivery Controllers in the Site.		The user name and password combination supplied for the hypervisor connection were not recognized. This issue affects all Delivery Controllers in the Site.		In Citrix Studio, edit the hypervisor connection and update the user name & password for the hypervisor. For more information, see Connections and resources (http://docs.citrix.com/en-us/xenapp-and-xendesktop/7-11/manage-deployment/connections.html) on the Citrix Product Documentation web site.	Error
5e73f287-4f7-4610-aa1e-05ca7f2c40e	Credentials insufficient for hypervisor connection creation	The credentials supplied for the connection do not have sufficient permissions to create the connection to the hypervisor. This issue affects all Delivery Controllers in the Site.		The credentials supplied for the connection do not have sufficient permissions to create the connection to the hypervisor. This issue affects all Delivery Controllers in the Site.		In Citrix Studio, edit the hypervisor connection and update the user name & password for the hypervisor. For more information, see Connections and resources (http://docs.citrix.com/en-us/xenapp-and-xendesktop/7-11/manage-deployment/connections.html) on the Citrix Product Documentation web site.	Error
f2c649a-907f-479a-aba2-95bc7bae896	Hypervisor connection timeout	The attempt to create a connection to the hypervisor timed out. This issue affects all Delivery Controllers in the Site.		The attempt to create a connection to the hypervisor timed out. This issue affects all Delivery Controllers in the Site.		Check the status and network connection of the target hypervisor. Verify that the hypervisor is reachable from every Delivery Controller in the Site.	Error
4ba10d16-558d-4c32-8129-0b6617f3b62	Name resolution failure for hypervisor connection	The address provided for the hypervisor connection could not be resolved. This issue affects all Delivery Controllers in the Site.		The address provided for the hypervisor connection could not be resolved. This issue affects all Delivery Controllers in the Site.		Verify that the address provided for the connection is correct. Ensure that the name supplied for the connection resolves to an address.	Error
c441f88-b0f2-4bdd-9ffa-6c90fe3ca1fb	VMware vCenter connection endpoint failure	The host failed to connect to the vCenter server with an HTTP connection address because the vCenter server is configured for HTTPS connections. This issue affects all Delivery Controllers in the Site.		The host failed to connect to the vCenter server with an HTTP connection address because the vCenter server is configured for HTTPS connections. This issue affects all Delivery Controllers in the Site.		Specify an HTTPS connection address.	Error
b69f0a44-285a-4cdc-9af6-f779e87edaf	SSL connection failure to VMware vCenter server	The host failed to connect to the vCenter server due to a certificate error. This issue affects all Delivery Controllers in the Site.		The host failed to connect to the vCenter server due to a certificate error. This issue affects all Delivery Controllers in the Site.		Verify that the appropriate certificates are installed on the vCenter server and on all machines hosting instances of the Citrix Host Service.	Error

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
e79bac6-783c-46dd-8d13-af3fbc6c6240	Broker client not running for environment test	The Citrix Monitor Service could not connect to the Citrix Broker Service Admin endpoint.		The Citrix Monitor Service could not connect to the Citrix Broker Service Admin endpoint.		Verify the Citrix Broker Service is installed and then restart it.	Warning
aca314bc-1331-4285-ac68-18dc50a6719b	Invalid worker for Citrix Monitor service	The Citrix Monitor Service worker ([worker]) is not running.	The invalid worker is [worker].	The Citrix Monitor Service worker is not running.		Verify the Citrix.Monitor.exe.Config file is present at %ProgramFiles%\Citrix\Monitor\Service. If necessary, restore the file. Verify data collection is enabled and restart the Citrix Monitor Service.	Warning
856e75df-9b92-4bd7-adf3-1e53c83d6dca	Data collection not started for Citrix Monitor service	Citrix Monitor Service data collection is either disabled or failed to start.		Citrix Monitor Service data collection is either disabled or failed to start.		Verify data collection is enabled and restart the Citrix Monitor service.	Warning
99fe189-4a81-450f-3c66-697d678cabd3	Grooming setting misconfigured for Citrix Monitor Service	The Citrix Monitor Service grooming setting ([settingKey]) is misconfigured.	The misconfigured setting is ([settingKey]).	The Citrix Monitor Service grooming setting is misconfigured.		Use the Set-MonitorConfiguration cmdlet to change the setting. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/Monitor/Set-MonitorConfiguration/).	Warning
a49baa5e-3a9d-4149-a068-75cd9287661	Grooming setting misconfigured for Citrix Monitor Service	The Citrix Monitor Service grooming data setting ([settingKey]) no longer matches its default value. This setting cannot be adjusted using cmdlets.	The misconfigured setting is ([settingKey]).	The Citrix Monitor Service grooming data setting no longer matches its default value. This setting cannot be adjusted using cmdlets.		Contact Citrix Support for assistance with adjusting this setting.	Warning
5899ef28-be2d-492e-b8c3-a4fd1ab63c6e	Environment test exception occurred	The ([errorType]) error occurred while running the ([test]) environment test for the Citrix Monitor Service. Error message: ([errorMessage]).	The error type is ([errorType]). The test is ([test]). The error message is ([errorMessage]).	An error occurred while running an environment test for the Citrix Monitor Service.		Contact Citrix Support for assistance.	Warning
f1267841-7a80-49ad-80b-ecfe7d97b8a	Reaping setting misconfigured for Citrix Monitor Service	The Citrix Monitor Service reaping setting ([settingKey]) is misconfigured.	The misconfigured setting is ([settingKey]).	The Citrix Monitor Service reaping setting is misconfigured.		Use the Set-MonitorConfiguration cmdlet to change the setting. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/Monitor/Set-MonitorConfiguration/).	Warning
60066880-614-4838-a0ef-95a63705e4db	Reaping setting misconfigured for Citrix Monitor Service	The Citrix Monitor Service reaping data setting ([settingKey]) no longer matches its default value.	The misconfigured setting is ([settingKey]).	The Citrix Monitor Service reaping data setting no longer matches its default value.		Contact Citrix Support to adjust this setting.	Warning
7bc2ba37-8d32-4924-9d3c-5a13d99cb94	Consolidation setting misconfigured for Citrix Monitor Service	The Citrix Monitor Service consolidation setting ([settingKey]) is misconfigured.	The misconfigured setting is ([settingKey]).	The Citrix Monitor Service consolidation setting is misconfigured.		Use the Set-MonitorConfiguration cmdlet to change the setting. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/Monitor/Set-MonitorConfiguration/).	Warning
1dc21194-4f9c-4d32-9ec8-bd24e4f3af14	Consolidation setting misconfigured for Citrix Monitor Service	The Citrix Monitor Service consolidation data setting ([settingKey]) no longer matches its default value.	The misconfigured setting is ([settingKey]).	The Citrix Monitor Service consolidation data setting no longer matches its default value.		Contact Citrix Support to adjust this setting.	Warning
1d5f2172-ddff-45ca-9a82-d9cd5654eb69	OData API not started for Citrix Monitor Service	The OData API is not started for the Citrix Monitor Service.		The OData API is not started for the Citrix Monitor Service.		Ensure the OData API is configured correctly and restart the Citrix Monitor Service.	Warning
3ea3d881-cabe-4145-83d3-03b06e973d0	Database access denied for Citrix Monitor Service	The Citrix Monitor Service was unable to access a required database table.		The Citrix Monitor Service was unable to access a required database table.		Ensure the Citrix Monitor Service's database schema is correct and restart the service.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
43e8413c-1119-4c3d-a1cb-d93a5eb202b2	Unspecified target for the Machine Creation test	No target was specified for the Machine Creation test. This issue affects all Delivery Controllers in the Site.		No target was specified for the Machine Creation test. This issue affects all Delivery Controllers in the Site.		Specify a target for the test.	Warning
a818667c-e7f8-46fa-860e-754d93ac3569	Incorrect object identifier for the Machine Creation test	The object identifier [objectId] is incorrect for the [objectType] object type specified in the Machine Creation test. This issue affects all Delivery Controllers in the Site.	The object type is [objectType]; The objectId is [objectId]	An object identifier is incorrect for the object type specified in the Machine Creation test. This issue affects all Delivery Controllers in the Site.		Specify master image objects by GUID. Specify Virtual Machine objects by SID (as a string in SDDL format).	Warning
289c1631-2a99-4730-b596-a1af6fb890d7	Schema database error for Citrix Machine Creation Service	A database error occurred while looking up the [scheme] provisioning scheme in the Citrix Machine Creation Service. Error message: [errorMessage] This issue affects all Delivery Controllers in the Site.	The error message is [errorMessage]; The provisioning scheme is [scheme]	A database error occurred while looking up the provisioning scheme in the Citrix Machine Creation Service. This issue affects all Delivery Controllers in the Site.		Check the service log and the database log to determine the cause of the failure.	Warning
52539a1a-5688-41d0-911d-08bd21c26a99	VM database error for Citrix Machine Creation Service	A database error occurred while looking up the [virtualMachine] VM in the Citrix Machine Creation Service. Error message: [errorMessage] This issue affects all Delivery Controllers in the Site.	The error message is [errorMessage]; The Virtual Machine is [virtualMachine]	A database error occurred while looking up the VM in the Citrix Machine Creation Service. This issue affects all Delivery Controllers in the Site.		Check the service log and the database log to determine the cause of the failure.	Warning
fec3c611-229f-4a99-a773-79bea80a80d	Identity database error for Citrix Machine Creation Service	A database error occurred while looking up the [identity] identity in the Citrix Machine Creation Service. Error message: [errorMessage] This issue affects all Delivery Controllers in the Site.	The error message is [errorMessage]; The identity is [identity]	A database error occurred while looking up the identity in the Citrix Machine Creation Service. This issue affects all Delivery Controllers in the Site.		Check the service log and the database log to determine the cause of the failure.	Warning
b8f76434-00ba-4210-b452-61c96f470069	Identity not found for Citrix Machine Creation Service	The [account] account was not found in the Citrix Machine Creation Service. This issue affects all Delivery Controllers in the Site.	The account is [account].	An account was not found in the Citrix Machine Creation Service. This issue affects all Delivery Controllers in the Site.		The account may refer to a valid account that is not part of an MCS provisioned catalog.	Warning
1ed62c20-710e-43cc-bf6f-40e55bae6e11	Machine not found for Citrix Machine Creation Service	The machine with the account [machineAccount] was not found in the Citrix Machine Creation Service. This issue affects all Delivery Controllers in the Site.	The machine account is [machineAccount].	A machine account was not found in the Citrix Machine Creation Service. This issue affects all Delivery Controllers in the Site.		The account may not be assigned to an MCS provisioned machine catalog.	Warning
4555a3ff-e8d9-4978-9926-b968127aa328	Object scheme not found for Citrix Machine Creation Service	The master image with the identifier [identifier] was not found in the Citrix Machine Creation Service. This issue affects all Delivery Controllers in the Site.	The scheme identifier is [identifier].	A master image was not found in the Citrix Machine Creation Service. This issue affects all Delivery Controllers in the Site.		The machine catalog may have been deleted.	Warning
222c58a0-c1a4-412e-ba9e-68e47963a62f	Object scheme locked for Citrix Machine Creation Service	The master image [masterImage] is locked by another operation in the Citrix Machine Creation Service. This issue affects all Delivery Controllers in the Site.	The master image is [masterImage].	A master image is locked by another operation in the Citrix Machine Creation Service. This issue affects all Delivery Controllers in the Site.		An operation in progress has locked this master image. Wait for the operation to complete. To unlock the master image, use one of the following cmdlets: <code>New-ProvVM</code> , <code>Publish-ProvMasterVMImage</code> , <code>Remove-ProvScheme</code> . For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop Powershell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Warning
99221b44-6071-4869-ba27-7e655d994bbe	Storage not found for provisioning scheme for Citrix Machine Creation Service	The provisioning scheme [provisioningSchemeName] cannot find storage for the associated host in the Citrix Machine Creation Service. This issue affects all Delivery Controllers in the Site.	The provisioning scheme is [provisioningSchemeName].	A provisioning scheme cannot find storage for the associated host in the Citrix Machine Creation Service. This issue affects all Delivery Controllers in the Site.		Reconfigure the host or hypervisor to locate storage for the master image.	Warning
ca13a599-37aa-499d-abe6-f284e38a5a6	PVD storage not found for Citrix Machine Creation Service	Compatible storage for Personal vDisks and the associated master image [masterImageName] could not be found in the Citrix Machine Creation Service. This issue affects all Delivery Controllers in the Site.	The associated master image is [masterImageName].	Compatible storage for Personal vDisks and the associated master image could not be found in the Citrix Machine Creation Service. This issue affects all Delivery Controllers in the Site.		Reconfigure the host or the hypervisor to find compatible storage for the master image.	Warning
a6f81723-b01f457d-90d9-42b1e7dca17	Temporary storage not found for Citrix Machine Creation Service	Compatible storage for Temporary Storage disks and the associated master image [masterImageName] could not be found in the Citrix Machine Creation Service. This issue affects all Delivery Controllers in the Site.	The associated master image is [masterImageName].	Compatible storage for Temporary Storage disks and the associated master image could not be found in the Citrix Machine Creation Service. This issue affects all Delivery Controllers in the Site.		Reconfigure the host or the hypervisor to find compatible storage for the master image.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
88e9d9fc-057a-44b7-a873-b5cae8ba0561	Error finding scheme hosting unit in Citrix Machine Creation Service	The provisioning scheme ([provisioning SchemeName]) is associated with the hosting unit ([hostingUnitId]), but trying to find this object resulted in the error "[errorMsg]". This issue affects all Delivery Controllers in the Site.	The provisioning scheme is ([provisioning SchemeName]); The Hosting Unit is ([hostingUnitId]); The error message is ([errorMsg]).	A provisioning scheme is associated with a hosting unit, but trying to find this object resulted in an error. This issue affects all Delivery Controllers in the Site.		Make sure that there is an active Host Service instance registered with the Site, and that the connection designated in the machine exists.	Warning
e9465d7-5ba9-41ad-a729-3bd7518d8073	Invalid network map for provisioning scheme in Citrix Machine Creation Service	The provisioning scheme ([provisioning SchemeName]) has an invalid network path in the map of the template virtual machine to the corresponding hypervisor network from each NIC. The resulting error is "[errorMsg]". This issue affects all Delivery Controllers in the Site.	The provisioning scheme is ([provisioning SchemeName]); The error message is ([errorMsg]).	A provisioning scheme has an invalid network path in the map of the template virtual machine to the corresponding hypervisor network from each NIC. This issue affects all Delivery Controllers in the Site.		Recreate networks to match the paths assigned for each NIC.	Warning
90082cd-0857-44a9-8b40-b589e68624ad	Invalid network map for virtual machine in Citrix Machine Creation Service	The virtual machine ([VMName]) has an invalid network path in the map to the corresponding hypervisor network from each NIC. The resulting error message is "[errorMsg]". This issue affects all Delivery Controllers in the Site.	The virtual machine is ([VMName]); The error message is ([errorMsg]).	A virtual machine has an invalid network path in the map to the corresponding hypervisor network from each NIC. This issue affects all Delivery Controllers in the Site.		Recreate networks to match the paths assigned for each NIC.	Warning
97af2ba-31f8-4d1e-ad1e-bea1b9100da	Error finding virtual machine hosting unit in Citrix Machine Creation Service	The virtual machine ([VMName]) is associated with the hosting unit ([hostingUnitId]), but trying to find this object resulted in the error, "[errorMsg]". This issue affects all Delivery Controllers in the Site.	The virtual machine is ([VMName]); The hosting unit is ([hostingUnitId]); The error message is ([errorMsg]).	A virtual machine is associated with an hosting unit, but trying to find this object resulted in an error. This issue affects all Delivery Controllers in the Site.		Make sure that there is an active Host Service instance registered with the Site, and that the connection designated in the machine exists.	Warning
e0928a9-a9a3-4b75-9226-495afaae4186	Invalid security group for provisioning scheme in Citrix Machine Creation Service	The provisioning scheme ([provisioning SchemeName]) is referencing a security group that does not exist in the cloud. Error message: ([errorMsg]). This issue affects all Delivery Controllers in the Site.	The provisioning scheme is ([provisioning SchemeName]); The error message is ([errorMsg]).	A provisioning scheme is referencing a security group that does not exist in the cloud. This issue affects all Delivery Controllers in the Site.		Use the cloud management facilities to recreate any missing security groups.	Warning
6b287801-8a80-44af-8af5-623a8a77d926	Invalid security group for virtual machine in Citrix Machine Creation Service	The virtual machine ([VMName]) is using a security group that does not exist in the cloud. Error message: ([errorMsg]). This issue affects all Delivery Controllers in the Site.	The virtual machine is ([VMName]); The error message is ([errorMsg]).	A virtual machine is using a security group that does not exist in the cloud. This issue affects all Delivery Controllers in the Site.		Use the cloud management facilities to recreate any missing security groups.	Warning
5442bc37-2ae4-46b9-8660-359f522ac456	Invalid service offering for provisioning scheme in Citrix Machine Creation Service	The provisioning scheme ([provisioning SchemeName]) is referencing a service offering that does not exist in the cloud. Error message: ([errorMsg]). This issue affects all Delivery Controllers in the Site.	The provisioning scheme is ([provisioning SchemeName]); The error message is ([errorMsg]).	A provisioning scheme is referencing a service offering that does not exist in the cloud. This issue affects all Delivery Controllers in the Site.		Use the cloud management facilities to recreate the missing service offering.	Warning
e15b59ef-797f-42c5-a84d-952494fc6d1c	Identity pool not found in Citrix Machine Creation Service	The provisioning scheme ([provisioning SchemeName]) is associated with the identity pool ([identityPoolId]), but the identity pool object could not be found. This issue affects all Delivery Controllers in the Site.	The provisioning scheme is ([provisioning SchemeName]); The identity pool is ([identityPoolId]).	A provisioning scheme is associated with an identity pool, but the identity pool object could not be found. This issue affects all Delivery Controllers in the Site.		Check the AD Identity Service logs for database or other errors. If there is no failure state on the AD Identity Service, use another provisioning scheme to provision new VMs.	Warning
fe170a47-9a6f-4bf1-aab0-99f51d516335	Error finding Identity Pool in Citrix Machine Creation Service	The provisioning scheme ([provisioning SchemeName]) is associated with the identity pool ([identityPoolId]), but trying to find the identity pool object resulted in the error, "[errorMsg]". This issue affects all Delivery Controllers in the Site.	The provisioning scheme is ([provisioning SchemeName]); The identity pool is ([identityPoolId]); The error message is ([errorMsg]).	A provisioning scheme is associated with the identity pool, but trying to find the identity pool object resulted in an error. This issue affects all Delivery Controllers in the Site.		Make sure that there is an active AD Identity Service instance registered with the Site, and that the identity pool named in the master image exists.	Warning
e45151af-6032-4de7-bd41-6c36f0505629	Scheme hosting unit not found in Citrix Machine Creation Service	The provisioning scheme ([provisioning SchemeName]) is associated with the hosting unit ([hostingUnitId]), but the hosting unit object could not be found. This issue affects all Delivery Controllers in the Site.	The provisioning scheme is ([provisioning SchemeName]); The hosting unit is ([hostingUnitId]).	A provisioning scheme is associated with a hosting unit, but the hosting unit object could not be found. This issue affects all Delivery Controllers in the Site.		Check the Host Service logs for database or other errors. If there was no failure on the Host Service, use another master image to provision new VMs.	Warning
23046056-57f6-4077-bd41-6c36f0505629	Error finding scheme hypervisor in Citrix Machine Creation Service	The provisioning scheme ([provisioning SchemeName]) cannot contact the associated hypervisor. The attempt resulted in the error "[errorMsg]". This issue affects all Delivery Controllers in the Site.	The provisioning scheme is ([provisioning SchemeName]); The error message is ([errorMsg]).	A provisioning scheme cannot contact the associated hypervisor. This issue affects all Delivery Controllers in the Site.		Reconfigure the host to specify a valid hypervisor connection.	Warning
d66bca3d-a3cd-489e-8a4c-6ffce10b9ec3	AD Identity Service in Citrix Machine Creation Service could not be contacted	Failed to contact an AD Identity Service instance from the same Site on the host ([hostname]).	The host is ([hostname]).	Failed to contact an AD Identity Service instance from the same Site on the host.		Make sure that there is an AD Identity Service registered with the Site, and that it is running on the same host as this service instance.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
7aae246f-a73f-44ce-9561-5a8374171866	Error finding identity for virtual machine	The identity {ADAccountSid} for the virtual machine {VMName} in the AD Identity Service could not be found. There might have been an AD Identity Service failure. This issue affects all Delivery Controllers in the Site.	The virtual machine is {VMName}; The account is {ADAccountSid}.	An identity for a virtual machine in the AD Identity Service could not be found. There might have been an AD Identity Service failure. This issue affects all Delivery Controllers in the Site.		Check the AD Identity Service logs for database errors or other errors. If the AD Identity Service was not in a failure state, then the VM account cannot be recycled if the VM is deleted at a later time.	Warning
01e93d67-1690-4e0d-aaed-3f57f3c41471	Identity not found for Virtual Machine	Cannot find the identity {ADAccountSid} for the {VMName} virtual machine in the AD Identity Service. This issue affects all Delivery Controllers in the Site.	The virtual machine is {VMName}; The account is {ADAccountSid}.	Cannot find an identity for a virtual machine in the AD Identity Service. This issue affects all Delivery Controllers in the Site.		Make sure that an AD Identity Service instance is available for communication, and that the service can communicate with the database. If the AD Identity Service and database are available, then no account with this SID was found.	Warning
b233c9bd-720d-4c86-a854-d01fa7b8d3f7	Identity available for provisioning	The account {ADAccountName} with the SID {ADAccountSid} is available for provisioning. This issue affects all Delivery Controllers in the Site.	The account name is {ADAccountName}; The account SID is {ADAccountSid}.	An account is available for provisioning. This issue affects all Delivery Controllers in the Site.		Confirm account availability by verifying there is no VM using this account. If the system is in an inconsistent state with a VM, delete the VM to bring the system into a consistent state.	Warning
4c4d6d9-9699-4c24-946d-9d47485997ca	Identity in use by a virtual machine	The account {ADAccountName} with the SID {ADAccountSid} is marked as in use. This issue affects all Delivery Controllers in the Site.	The account name is {ADAccountName}; The account SID is {ADAccountSid}.	An account is marked as in use. This issue affects all Delivery Controllers in the Site.		Verify there is a VM using this account. If no matching VM is found in the database, delete the account.	Warning
4839821e-9631-4626-a6fc-b10542d0c68	Identity tainted by a virtual machine	The account {ADAccountName} with the SID {ADAccountSid} is marked as having been in use for a VM. This issue affects all Delivery Controllers in the Site.	The account name is {ADAccountName}; The account SID is {ADAccountSid}.	An account is marked as having been in use for a VM. This issue affects all Delivery Controllers in the Site.		If the account is marked as having previously been in use for a VM which has since been removed, but the matching VM still exists, then the system is in an inconsistent state. Delete the VM to bring the system into a consistent state.	Warning
74aa191a-6e34-42ac-93eb-654f6c51a56	Identity error found	There is an error with the account {ADAccountName} with the SID {ADAccountSid}. This issue affects all Delivery Controllers in the Site.	The account name is {ADAccountName}; The account SID is {ADAccountSid}.	There is an error with an account. This issue affects all Delivery Controllers in the Site.		Repair the account. This might require additional action in Active Directory.	Warning
e95efdc0-9cd1-4232-a5a3-93e8aad3020	Virtual machine not found in hosting environment	Smart Tools couldn't find the virtual machine {VMName} in the hosting environment. While attempting to find the machine, the error "[errorMsg]" occurred. The virtual machine might not exist. This issue affects all Delivery Controllers in the Site.	The virtual machine is {VMName}; The error message is {errorMsg}.	Smart Tools couldn't find a virtual machine in the hosting environment. While attempting to find the machine, an error occurred. The virtual machine might not exist. This issue affects all Delivery Controllers in the Site.		Delete the phantom database records using the Remove-ProvVM cmdlet. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/MachineCreation/Remove-ProvVM/).	Warning
468476d2-1586-40ef-bb2d-843354735a50	Error contacting associated hypervisor for VM	The virtual machine {VMName} cannot contact the associated hypervisor. The attempt resulted in the error "[errorMsg]". This issue affects all Delivery Controllers in the Site.	The virtual machine is {VMName}; The error message is {errorMsg}.	A virtual machine cannot contact the associated hypervisor. The attempt resulted in an error. This issue affects all Delivery Controllers in the Site.		Reconfigure the host to use a valid hypervisor connection.	Warning
face748e-0487-446c-bc3f-d61d80552295	VM disk not found	There is no attached virtual disk for the virtual machine {VMName}. This issue affects all Delivery Controllers in the Site.	The virtual machine is {VMName}.	There is no attached virtual disk for a virtual machine. This issue affects all Delivery Controllers in the Site.		If the virtual machine cannot be restored to a working state through the hypervisor, then delete the virtual machine.	Warning
500c07a7-4c01-40c3-a597-c809819a74be	VM being clean on boot not linked to the correct base disk	This VM is not linked to the correct base disk and the provisioning scheme shows it is clean on boot. If the master VM that was used to create the catalog is deleted, then all VMs belonging to this catalog will stop working. This issue affects all Delivery Controllers in the Site.		This VM is not linked to the correct base disk and the provisioning scheme shows it is clean on boot. If the master VM that was used to create the catalog is deleted, then all VMs belonging to this catalog will stop working. This issue affects all Delivery Controllers in the Site.		Update the master image for the machine catalog that contains this VM. For more information, see [CTX141366](http://support.citrix.com/article/CTX141366).	Warning
8c837dbb-959f-41a2-ae10-4197aac0b55	VM not linked to the correct base disk	This VM is not linked to the correct base disk and it is not clean on boot. If the master VM that was used to create the catalog is deleted, then all VMs belonging to this catalog will stop working and will need to be restored from a backup. This issue affects all Delivery Controllers in the Site.		This VM is not linked to the correct base disk and it is not clean on boot. If the master VM that was used to create the catalog is deleted, then all VMs belonging to this catalog will stop working and will need to be restored from a backup. This issue affects all Delivery Controllers in the Site.		This VM needs to be repaired. For more information, see [CTX141366](https://support.citrix.com/article/CTX141366) in the Citrix Knowledge Center.	Warning
b2e164a6-f10b-43ae-8a29-845f33d03dd	Error reading Citrix administrators	The error "[errorMsg]" occurred while attempting to read the Citrix administrators in the Site. This issue affects all Delivery Controllers in the Site.	The error message is {errorMsg}.	An error occurred while attempting to read the Citrix administrators in the Site. This issue affects all Delivery Controllers in the Site.		Contact Citrix Support for assistance.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
a394746d-1941-47b7-b79a-796c8546698	Administrator missing from Active Directory	Failed to find the Active Directory account for the Citrix administrator with the SID ([adminSID]). The account might have been deleted. This issue affects all Delivery Controllers in the Site.	The SID for the missing administrator account is [adminSID].	Failed to find the Active Directory account for a Citrix administrator. The account might have been deleted. This issue affects all Delivery Controllers in the Site.		Consult your Active Directory Administrator and delete the Citrix administrator if the account no longer exists in Active Directory.	Warning
f62e2a0d-4dfb-43fc-98b8-9a1f546c9f75	Role configuration file language is inconsistent	Role configuration files are found in [numberOfLanguages] different languages. This issue affects all Delivery Controllers in the Site.	There are [numberOfLanguages] different languages;	Role configuration files are found in several different languages. This issue affects all Delivery Controllers in the Site.		Check the language of the role configuration files and ensure the language is consistent across all files. Use the Import-AdminRoleConfiguration cmdlet to re-import the configuration files in the correct language.	Warning
88ea47a-5c8e-498a-a5c0-4efc5825185	Citrix administrator missing from Domain Users group	Smart Tools couldn't find the Citrix administrator account ([adminName]) in the Domain Users group. If you are using an earlier version of the Smart Tools Agent (earlier than 2.5.0), this alert could occur because the agent installation added the NT AUTHORITY\SYSTEM account as a Read Only Administrator to the Site.	The missing Citrix administrator account name is [adminName];	Smart Tools couldn't find a Citrix administrator account in the Domain Users group. If you are using an earlier version of the Smart Tools Agent (earlier than 2.5.0), this alert could occur because the NT AUTHORITY\SYSTEM account was added as a Read Only Administrator to your Site. This issue affects all Delivery Controllers in the Site.		To resolve this issue, perform the following actions: 1. If the NT AUTHORITY\SYSTEM account is present as a Read Only Administrator in Citrix Studio (Configuration > Administrators), delete the account from Studio. 2. Consult your Active Directory administrator to determine whether or not the affected account should be added to the Domain Users group.	Warning
f010475f-10f7-4b57-a78c-15aa9970446	Disabled Citrix administrator found	The Citrix administrator account ([adminName]) is disabled. This issue affects all Delivery Controllers in the Site.	The disabled administrator account name is [adminName];	A Citrix administrator account is disabled. This issue affects all Delivery Controllers in the Site.		Verify whether or not the Citrix administrator account should be disabled. Enable or delete the account as appropriate for your organization.	Warning
2a43048a-245b-4946-bf94-a5ac44d6bc27	No rights for administrator	The Citrix administrator [adminName] has no roles or scopes assigned. This issue affects all Delivery Controllers in the Site.	The administrator account name is [adminName];	A Citrix administrator has no roles or scopes assigned. This issue affects all Delivery Controllers in the Site.		Add roles and scopes to the Citrix administrator account.	Warning
a44b9c7b-11a8-4477-8a6b-17dcd0f5ee	Role found with no permissions	The role [roleName] has no permissions. This issue affects all Delivery Controllers in the Site.	The role name is [roleName];	A Citrix administrator role has no permissions. This issue affects all Delivery Controllers in the Site.		Add one or more permissions to the role.	Warning
80f9becb-ad24-4466-9978-36a5fac777be	Unsupported custom roles found	[numberOfCustomRoles] custom roles were found, but the product edition does not support custom roles. This issue affects all Delivery Controllers in the Site.	The number of custom roles is [numberOfCustomRoles];	Several custom roles were found, but the product edition does not support custom roles. This issue affects all Delivery Controllers in the Site.		Verify your Citrix product license supports custom roles. Only certain product editions support custom roles. For more information, see the [XenApp and XenDesktop feature matrix](https://www.citrix.com/go/products/xendesktop/feature-matrix).	Warning
3de5580-dca3-411f-ba8c-609e84180fc6	Error reading roles	The error "[errorMsg]" occurred while attempting to read roles. This issue affects all Delivery Controllers in the Site.	The error message is [errorMsg];	An error occurred while attempting to read roles. This issue affects all Delivery Controllers in the Site.		Verify the Delivery Controller(s) can communicate with the database. If applicable, use the Import-AdminRoleConfiguration cmdlet to re-import the role configuration file.	Warning
abc2020-b8e4-45ee-8f0c-c238ead408b3	Site object not found for Citrix Configuration Service	The Citrix Configuration Service is unable to retrieve Site information.		The Citrix Configuration Service is unable to retrieve Site information.		Make sure the Site is properly configured. Run the Get-ConfigSite cmdlet to verify there is a Site object. Otherwise, contact Citrix Support for assistance.	Error
e20e394e-907b-4d4c-814b-6abfaa7d955a	License server address mismatch	The LicenseServerName and the LicenseServerUri host name do not match in the Configuration Service Site object.		The LicenseServerName and the LicenseServerUri host name do not match in the Configuration Service Site object.		Use the Set-ConfigSite cmdlet to change the LicenseServerName or LicenseServerUri values in the Configuration Service Site object so that the host names match in both settings.	Error
50c3bcfb-fbf6-496a-uc3-f8a0e011602	No logging database connection	There is no connection to the Configuration Logging database. The Configuration Logging state is currently "Disabled." This issue affects all Delivery Controllers in the Site.		There is no connection to the Configuration Logging database. The Configuration Logging state is currently "Disabled." This issue affects all Delivery Controllers in the Site.		If logging is required, perform the following actions: 1. Ensure there is a database connection by running the 'Set-LogDBConnection -DataStore Logging -DBConnection \$connection' command. 2. Enable logging by running the 'Set-LogSite -State "Enabled"' command.	Error
8f0ec49-7d0f-4b60-bf0f-c8aa10973a8	No logging database connection while mandatory Configuration Logging is enabled	The Configuration Logging state is "Mandatory," but there is no connection to the Configuration Logging database. Configuration changes will not be executed. This issue affects all Delivery Controllers in the Site.		The Configuration Logging state is "Mandatory," but there is no connection to the Configuration Logging database. Configuration changes will not be executed. This issue affects all Delivery Controllers in the Site.		To create a connection to the Configuration Logging database, run the 'Set-LogDBConnection -DataStore Logging -DBConnection \$connection' command. If Configuration Logging is not required, disable it by running the 'Set-LogSite -State "Disabled"' command.	Error

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
7470eaf-1a52-4a02-bc94-95a064a067e5	No logging database connection while Configuration Logging is enabled	Configuration Logging is 'Enabled', but there is no connection to the Configuration Logging database. Configuration changes cannot be logged. This issue affects all Delivery Controllers in the Site.		Configuration Logging is 'Enabled', but there is no connection to the Configuration Logging database. Configuration changes cannot be logged. This issue affects all Delivery Controllers in the Site.		To create a connection to the Configuration Logging database, run the 'Set-LogDBConnection -DataStore Logging -DBConnection \$connStr' command. If Configuration Logging is not required, disable it by running the 'Set-LogSite -State "Disabled"' command.	Error
0d1484df-4edd-40aa-9b7e-1c080692853e	Invalid locale for Configuration Logging	The current Configuration Logging locale ([locale]) is invalid. This issue affects all Delivery Controllers in the Site.	The current locale is {locale}.	A current Configuration Logging locale is invalid. This issue affects all Delivery Controllers in the Site.		To set a valid locale, run the 'Set-LogSite -Locale \$locale' command.	Warning
40ae45de-3dfe-4206-a901-98319f1512	User SIDs missing from Active Directory	The Configuration Logging user SID identities ([userSIDs]) cannot be resolved from Active Directory. This issue affects all Delivery Controllers in the Site.	The missing user SIDs are ([userSIDs]).	Configuration Logging user SID identities cannot be resolved from Active Directory. This issue affects all Delivery Controllers in the Site.		Ensure that Active Directory is configured correctly.	Warning
22a25fb-6339-4e46-90b9-8b431c5ae8ce	Machine SIDs missing from Active Directory	The Configuration Logging machine SID identities ([machineSIDs]) cannot be resolved from Active Directory. This issue affects all Delivery Controllers in the Site.	The missing machine SIDs are ([machineSIDs]).	Configuration Logging machine SID identities cannot be resolved from Active Directory. This issue affects all Delivery Controllers in the Site.		Ensure that Active Directory is configured correctly.	Warning
472522af-35ab-4ee7-9c11-473b574030a8	Configuration Logging not supported	The Configuration Logging feature is not supported in the current product edition. This issue affects all Delivery Controllers in the Site.		The Configuration Logging feature is not supported in the current product edition. This issue affects all Delivery Controllers in the Site.		If Configuration Logging is required, change the product edition to one that supports Configuration Logging. For more information, see the [XenApp and XenDesktop Feature Matrix](https://www.citrix.com/go/products/xendesktop/feature-matrix.html).	Warning
0bed55db-5d85-4558-8d58-d3c5c9d0d078	Configuration Logging state unknown	The Configuration Logging state is unknown. This issue affects all Delivery Controllers in the Site.		The Configuration Logging state is unknown. This issue affects all Delivery Controllers in the Site.		To set Configuration Logging to a valid state, run the 'Set-LogSite -State <Enabled/Disabled/Mandatory>' command.	Warning
c6dadac6-4c8e-4131-a0a9-5dec5c091190	Null database connection string for Citrix AD Identity Service	The database connection string has not been specified for the Citrix AD Identity Service.		The database connection string has not been specified for the Citrix AD Identity Service.		Use the Set-AcctDBConnection cmdlet to set the connection string to \$null and then reset the database connection string. For example, where '\$connStr' is the connection string, use the following commands: Set-AcctDBConnection \$null Set-AcctDBConnection -DBConnection \$connStr	Warning
4888b7bc-465f-4a0e-bd1c-57c96492a5cf	Null database connection string for Citrix Analytics Service	The database connection string has not been specified for the Citrix Analytics Service.		The database connection string has not been specified for the Citrix Analytics Service.		Use the Set-AnalyticsDBConnection cmdlet to set the connection string to \$null and then reset the database connection string. For example, where '\$connStr' is the connection string, use the following commands: Set-AnalyticsDBConnection \$null Set-AnalyticsDBConnection -DBConnection \$connStr	Warning
db8f077-9538-4147-8b7f-3db0c23916d9	Null database connection string for Citrix App Library Service	The database connection string has not been specified for the Citrix App Library Service.		The database connection string has not been specified for the Citrix App Library Service.		Use the Set-AppLibDBConnection cmdlet to set the connection string to \$null and then reset the database connection string. For example, where '\$connStr' is the connection string, use the following commands: Set-AppLibDBConnection \$null Set-AppLibDBConnection -DBConnection \$connStr	Warning
a9511f51-4694-4e4a-a9a9-019a371b8339	Null database connection string for Citrix Broker Service	The database connection string has not been specified for the Citrix Broker Service.		The database connection string has not been specified for the Citrix Broker Service.		Use the Set-BrokerDBConnection cmdlet to set the connection string to \$null and then reset the database connection string. For example, where '\$connStr' is the connection string, use the following commands: Set-BrokerDBConnection \$null Set-BrokerDBConnection -DBConnection \$connStr	Warning
5d0df5db-c581-4c2e-9522-7307507b31d	Null database connection string for Citrix Configuration Service	The database connection string has not been specified for the Citrix Configuration Service.		The database connection string has not been specified for the Citrix Configuration Service.		Use the Set-ConfigDBConnection cmdlet to set the connection string to \$null and then reset the database connection string. For example, where '\$connStr' is the connection string, use the following commands: Set-ConfigDBConnection \$null Set-ConfigDBConnection -DBConnection \$connStr	Warning
a47c3c3d-10de-4456-ab02-79598d8597bc	Null database connection string for Citrix Configuration Logging Service	The database connection string has not been specified for the Citrix Configuration Logging Service.		The database connection string has not been specified for the Citrix Configuration Logging Service.		Use the Set-LogDBConnection cmdlet to set the connection string to \$null and then reset the database connection string. For example, where '\$connStr' is the connection string, use the following commands: Set-LogDBConnection \$null Set-LogDBConnection -DBConnection \$connStr	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
a813969-3392-44e7-af6d-b494b9377c69	Null database connection string for Citrix Delegated Administration Service	The database connection string has not been specified for the Citrix Delegated Administration Service.		The database connection string has not been specified for the Citrix Delegated Administration Service.		Use the Set-AdminDBConnection cmdlet to set the connection string to \$null and then reset the database connection string. For example, where '\$connStr' is the connection string, use the following commands: Set-AdminDBConnection \$null Set-AdminDBConnection -DBConnection \$connStr	Warning
d1e431f1-0ae6-44e7-a03c-86208a12275e	Null database connection string for Citrix Environment Test Service	The database connection string has not been specified for the Citrix Environment Test Service.		The database connection string has not been specified for the Citrix Environment Test Service.		Use the Set-EnvTestDBConnection cmdlet to set the connection string to \$null and then reset the database connection string. For example, where '\$connStr' is the connection string, use the following commands: Set-EnvTestDBConnection \$null Set-EnvTestDBConnection -DBConnection \$connStr	Warning
dfe5fa78-48c9-4260-4910-677acce3a585	Null database connection string for Citrix Host Availability Service	The database connection string has not been specified for the Citrix Host Availability Service.		The database connection string has not been specified for the Citrix Host Availability Service.		Use the Set-HypDBConnection cmdlet to set the connection string to \$null and then reset the database connection string. For example, where '\$connStr' is the connection string, use the following commands: Set-HypDBConnection \$null Set-HypDBConnection -DBConnection \$connStr	Warning
ee9e371e-31b8-44c7-907c-68f29c764023	Null database connection string for Citrix Machine Creation Service	The database connection string has not been specified for the Citrix Machine Creation Service.		The database connection string has not been specified for the Citrix Machine Creation Service.		Use the Set-ProdDBConnection cmdlet to set the connection string to \$null and then reset the database connection string. For example, where '\$connStr' is the connection string, use the following commands: Set-ProdDBConnection \$null Set-ProdDBConnection -DBConnection \$connStr	Warning
a88067da-ee9b-4b47-b3fb-55898988547b	Null database connection string for Citrix Monitor Service	The database connection string has not been specified for the Citrix Monitor Service.		The database connection string has not been specified for the Citrix Monitor Service.		Use the Set-MonitorDBConnection cmdlet to set the connection string to \$null and then reset the database connection string. For example, where '\$connStr' is the connection string, use the following commands: Set-MonitorDBConnection \$null Set-MonitorDBConnection -DBConnection \$connStr	Warning
b730a3c5-3295-44a6-9445-b283532a1c3a	Null database connection string for Citrix Storefront Service	The database connection string has not been specified for the Citrix Storefront Service.		The database connection string has not been specified for the Citrix Storefront Service.		Use the Set-sfDBConnection cmdlet to set the connection string to \$null and then reset the database connection string. For example, where '\$connStr' is the connection string, use the following commands: Set-sfDBConnection \$null Set-sfDBConnection -DBConnection \$connStr	Warning
fa54d040-5477-429e-a4ad-a3d7ce13a5ae	Broken database connection for Citrix ADIdentity Service	A database connection string has been specified for the Citrix AD Identity Service, but the database is not compatible or working properly.		A database connection string has been specified for the Citrix AD Identity Service, but the database is not compatible or working properly.		Contact Citrix Support and provide the CDF logs for the service.	Warning
728e65b4-195d-4c04-bc3f-1b69128425c	Broken database connection for Citrix Analytics Service	A database connection string has been specified for the Citrix Analytics Service, but the database is not compatible or working properly.		A database connection string has been specified for the Citrix Analytics Service, but the database is not compatible or working properly.		Contact Citrix Support and provide the CDF logs for the service.	Warning
7c2c1f71-09d5-4c9f-8198-dc24edf37651a	Broken database connection for Citrix AppLibrary Service	A database connection string has been specified for the Citrix App Library Service, but the database is not compatible or working properly.		A database connection string has been specified for the Citrix App Library Service, but the database is not compatible or working properly.		Contact Citrix Support and provide the CDF logs for the service.	Warning
b85d009a-d76a-4a29-a8fd-e95114279427	Broken database connection for Citrix Broker Service	A database connection string has been specified for the Citrix Broker Service, but the database is not compatible or working properly.		A database connection string has been specified for the Citrix Broker Service, but the database is not compatible or working properly.		Contact Citrix Support and provide the CDF logs for the service.	Warning
50e532be-4825-451a-af7a-1ac30218f760	Broken database connection for Citrix Configuration Service	A database connection string has been specified for the Citrix Configuration Service, but the database is not compatible or working properly.		A database connection string has been specified for the Citrix Configuration Service, but the database is not compatible or working properly.		Contact Citrix Support and provide the CDF logs for the service.	Warning
b2653159-1445-4e46-9543-dfccc8224f	Broken database connection for Citrix Configuration Logging Service	A database connection string has been specified for the Citrix Configuration Logging Service, but the database is not compatible or working properly.		A database connection string has been specified for the Citrix Configuration Logging Service, but the database is not compatible or working properly.		Contact Citrix Support and provide the CDF logs for the service.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
631d76cc-587b-4e2c-b59c-a582183e5a	Broken database connection for Citrix Delegated Administration Service	A database connection string has been specified for the Citrix Delegated Administration Service, but the database is not compatible or working properly.		A database connection string has been specified for the Citrix Delegated Administration Service, but the database is not compatible or working properly.		Contact Citrix Support and provide the CDF logs for the service.	Warning
79643190-336d-4e7b-9440-3f64b22a89a	Broken database connection for Citrix Environment Test Service	A database connection string has been specified for the Citrix Environment Test Service, but the database is not compatible or working properly.		A database connection string has been specified for the Citrix Environment Test Service, but the database is not compatible or working properly.		Contact Citrix Support and provide the CDF logs for the service.	Warning
f66d9ff6-7f27-411f-9aa4-7d5cc3651c30	Broken database connection for Citrix Host Availability Service	A database connection string has been specified for the Citrix Host Availability Service, but the database is not compatible or working properly.		A database connection string has been specified for the Citrix Host Availability Service, but the database is not compatible or working properly.		Contact Citrix Support and provide the CDF logs for the service.	Warning
06a2ffba-f117-47cd-8245-4530b3d2a996	Broken database connection for Citrix Machine Creation Service	A database connection string has been specified for the Citrix Machine Creation Service, but the database is not compatible or working properly.		A database connection string has been specified for the Citrix Machine Creation Service, but the database is not compatible or working properly.		Contact Citrix Support and provide the CDF logs for the service.	Warning
f051d418-415a-4efb-a248-0ad095eda281	Broken database connection for Citrix Monitor Service	A database connection string has been specified for the Citrix Monitor Service, but the database is not compatible or working properly.		A database connection string has been specified for the Citrix Monitor Service, but the database is not compatible or working properly.		Contact Citrix Support and provide the CDF logs for the service.	Warning
4a6f06d3-ed96-418a-beb2-13de98bd64d4	Broken database connection for Citrix Storefront Service	A database connection string has been specified for the Citrix Storefront Service, but the database is not compatible or working properly.		A database connection string has been specified for the Citrix Storefront Service, but the database is not compatible or working properly.		Contact Citrix Support and provide the CDF logs for the service.	Warning
0371979b-32ea-4358-a04d-6b254aaf1957	Site isolated for Citrix AD Identity Service	The database is compatible and the service group for the Citrix AD Identity Service is available for registration.		The database is compatible and the service group for the Citrix AD Identity Service is available for registration.		Run the following commands to register with the Central Configuration Service: Get-AccServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-AccServiceGroupMembership	Warning
89e88672-ebd3-4b2e-a270-2a8d3092d81b	Site isolated for Citrix Analytics Service	The database is compatible and the service group for the Citrix Analytics Service is available for registration.		The database is compatible and the service group for the Citrix Analytics Service is available for registration.		Run the following commands to register with the Central Configuration Service: Get-AnalyticsServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-AnalyticsServiceGroupMembership	Warning
685f5b2c-241b-421b-b132-73883cfd6e1	Site isolated for Citrix App Library Service	The database is compatible and the service group for the Citrix App Library Service is available for registration.		The database is compatible and the service group for the Citrix App Library Service is available for registration.		Run the following commands to register with the Central Configuration Service: Get-AppLibServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-AppLibServiceGroupMembership	Warning
2d58f7a5-1d69-4b77-8adf-c9fe751329a	Site isolated for Citrix Broker Service	The database is compatible and the service group for the Citrix Broker Service is available for registration.		The database is compatible and the service group for the Citrix Broker Service is available for registration.		Run the following commands to register with the Central Configuration Service: Get-BrokerServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-BrokerServiceGroupMembership	Warning
d106411-2d2a-4c4a-a7db-d46d82b99c9f	Site isolated for Citrix Configuration Service	The database is compatible and the service group for the Citrix Configuration Service is available for registration.		The database is compatible and the service group for the Citrix Configuration Service is available for registration.		Run the following commands to register with the Central Configuration Service: Get-ConfigServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-ConfigServiceGroupMembership	Warning
ba73681d-32f2-4c22-8fcb-d4626081fec6	Site isolated for Citrix Configuration Logging Service	The database is compatible and the service group for the Citrix Configuration Logging Service is available for registration.		The database is compatible and the service group for the Citrix Configuration Logging Service is available for registration.		Run the following commands to register with the Central Configuration Service: Get-LogServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-LogServiceGroupMembership	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
21dea587-4770-44ef-8aa5-a299473ea056	Site isolated for Citrix Delegated Administration Service	The database is compatible and the service group for the Citrix Delegated Administration Service is available for registration.		The database is compatible and the service group for the Citrix Delegated Administration Service is available for registration.		Run the following commands to register with the Central Configuration Service: Get-AdminServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Register-AdminServiceGroupMembership	Warning
f018db1-d630-40c4-a748-2df1416d84eb	Site isolated for Citrix Environment Test Service	The database is compatible and the service group for the Citrix Environment Test Service is available for registration.		The database is compatible and the service group for the Citrix Environment Test Service is available for registration.		Run the following commands to register with the Central Configuration Service: Get-EnvTestServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Register-EnvTestServiceGroupMembership	Warning
a078080c-4163-4d64-837f-e4099666cb0e	Site isolated for Citrix Host Availability Service	The database is compatible and the service group for the Citrix Host Availability Service is available for registration.		The database is compatible and the service group for the Citrix Host Availability Service is available for registration.		Run the following commands to register with the Central Configuration Service: Get-HypServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Register-HypServiceGroupMembership	Warning
90c270f1-a108-4ca7-9711-321d098aa75	Site isolated for Citrix Machine Creation Service	The database is compatible and the service group for the Citrix Machine Creation Service is available for registration.		The database is compatible and the service group for the Citrix Machine Creation Service is available for registration.		Run the following commands to register with the Central Configuration Service: Get-ProdServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Register-ProdServiceGroupMembership	Warning
0c1745cb-d0d0-44bc-8aea-98416ef511be	Site isolated for Citrix Monitor Service	The database is compatible and the service group for the Citrix Monitor Service is available for registration.		The database is compatible and the service group for the Citrix Monitor Service is available for registration.		Run the following commands to register with the Central Configuration Service: Get-MonitorServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Register-MonitorServiceGroupMembership	Warning
55e663bf-69d3-4185-9861-262b04d1b2d0	Site isolated for Citrix Storefront Service	The database is compatible and the service group for the Citrix Storefront Service is available for registration.		The database is compatible and the service group for the Citrix Storefront Service is available for registration.		Run the following commands to register with the Central Configuration Service: Get-sServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Register-sServiceGroupMembership	Warning
ca96172d-c64d-404f-abf6-91458bb308a3	Incomplete configuration for Citrix AD Identity Service	The service group for the Citrix AD Identity Service has been registered with the Site. Additional configuration is required for this service.		The service group for the Citrix AD Identity Service has been registered with the Site. Additional configuration is required for this service.		Complete the service configuration.	Warning
8db8ee8-d6e4-44b6-bdc2-1fb27479616f	Incomplete configuration for Citrix Analytics Service	The service group for the Citrix Analytics Service has been registered with the Site. Additional configuration is required for this service.		The service group for the Citrix Analytics Service has been registered with the Site. Additional configuration is required for this service.		Complete the service configuration.	Warning
6abb4b06-3da9-458c-bdc3-ec3b212ae88c	Incomplete configuration for Citrix App Library Service	The service group for the Citrix App Library Service has been registered with the Site. Additional configuration is required for this service.		The service group for the Citrix App Library Service has been registered with the Site. Additional configuration is required for this service.		Complete the service configuration.	Warning
8e8b1093-77d0-4588-bdff-f7d09413c1d2	Incomplete configuration for Citrix Broker Service	The service group for the Citrix Broker Service has been registered with the Site. Additional configuration is required for this service.		The service group for the Citrix Broker Service has been registered with the Site. Additional configuration is required for this service.		Complete the service configuration.	Warning
929900a8-2261-4f2e-b120-a03a14be9f45	Incomplete configuration for Citrix Configuration Service	The service group for the Citrix Configuration Service has been registered with the Site. Additional configuration is required for this service.		The service group for the Citrix Configuration Service has been registered with the Site. Additional configuration is required for this service.		Complete the service configuration.	Warning
510d878e-26d0-4055-92b1-e3e5f4c25032	Incomplete configuration for Citrix Configuration Logging Service	The service group for the Citrix Configuration Logging Service has been registered with the Site. Additional configuration is required for this service.		The service group for the Citrix Configuration Logging Service has been registered with the Site. Additional configuration is required for this service.		Complete the service configuration.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
3c37c5cb-d210-4fae-b2ef-af6a88cde422	Incomplete configuration for Citrix Delegated Administration Service	The service group for the Citrix Delegated Administration Service has been registered with the Site. Additional configuration is required for this service.		The service group for the Citrix Delegated Administration Service has been registered with the Site. Additional configuration is required for this service.		Complete the service configuration.	Warning
ee03d16-4c0d-4381-bef-6216a44d251c	Incomplete configuration for Citrix Environment Test Service	The service group for the Citrix Environment Test Service has been registered with the Site. Additional configuration is required for this service.		The service group for the Citrix Environment Test Service has been registered with the Site. Additional configuration is required for this service.		Complete the service configuration.	Warning
70f148fb-2b48-4ee0-9572-9633208ca97	Incomplete configuration for Citrix Host Availability Service	The service group for the Citrix Host Availability Service has been registered with the Site. Additional configuration is required for this service.		The service group for the Citrix Host Availability Service has been registered with the Site. Additional configuration is required for this service.		Complete the service configuration.	Warning
bae6633-65ab-4161-99b0-9c9f0b95ba85	Incomplete configuration for Citrix Machine Creation Service	The service group for the Citrix Machine Creation Service has been registered with the Site. Additional configuration is required for this service.		The service group for the Citrix Machine Creation Service has been registered with the Site. Additional configuration is required for this service.		Complete the service configuration.	Warning
24825f36-682d-493c-a061-609bf973b221	Incomplete configuration for Citrix Monitor Service	The service group for the Citrix Monitor Service has been registered with the Site. Additional configuration is required for this service.		The service group for the Citrix Monitor Service has been registered with the Site. Additional configuration is required for this service.		Complete the service configuration.	Warning
ba32a676-2b0e-428f-86ea-05f9b854f01b	Incomplete configuration for Citrix Storefront Service	The service group for the Citrix Storefront Service has been registered with the Site. Additional configuration is required for this service.		The service group for the Citrix Storefront Service has been registered with the Site. Additional configuration is required for this service.		Complete the service configuration.	Warning
146a94df-a4fe-477f-b759-7448ba4fb603	Unknown registration state for Citrix AD Identity Service	The registration state for the Citrix AD Identity Service is unknown.		The registration state for the Citrix AD Identity Service is unknown.		Check that the database is running and that you can connect to the database from the server by running sqlcmd. Contact Citrix Support and provide them with the CDF logs for the service.	Warning
2f295c4-9188-463f-be87-48007635d468	Unknown registration state for Citrix Analytics Service	The registration state for the Citrix Analytics Service is unknown.		The registration state for the Citrix Analytics Service is unknown.		Check that the database is running and that you can connect to the database from the server by running sqlcmd. Contact Citrix Support and provide them with the CDF logs for the service.	Warning
937c02a-c508-4702-9950-f1e59978d366	Unknown registration state for Citrix App Library Service	The registration state for the Citrix App Library Service is unknown.		The registration state for the Citrix App Library Service is unknown.		Check that the database is running and that you can connect to the database from the server by running sqlcmd. Contact Citrix Support and provide them with the CDF logs for the service.	Warning
8bae05a3-4c53-494c-ba70-7d03b10a288f	Unknown registration state for Citrix Broker Service	The registration state for the Citrix Broker Service is unknown.		The registration state for the Citrix Broker Service is unknown.		Check that the database is running and that you can connect to the database from the server by running sqlcmd. Contact Citrix Support and provide them with the CDF logs for the service.	Warning
9f1812e8-c5aa-4ece-87d1-322134faab89	Unknown registration state for Citrix Configuration Service	The registration state for the Citrix Configuration Service is unknown.		The registration state for the Citrix Configuration Service is unknown.		Check that the database is running and that you can connect to the database from the server by running sqlcmd. Contact Citrix Support and provide them with the CDF logs for the service.	Warning
59082b17-5170-42e8-a4a8-d749304a4dac	Unknown registration state for Citrix Configuration Logging Service	The registration state for Citrix Configuration Logging Service is unknown.		The registration state for Citrix Configuration Logging Service is unknown.		Check that the database is running and that you can connect to the database from the server by running sqlcmd. Contact Citrix Support and provide them with the CDF logs for the service.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
b6895ba9-477b-4447-984f-99b19a49b41d	Unknown registration state for Citrix Delegated Administration Service	The registration state for the Citrix Delegated Administration Service is unknown.		The registration state for the Citrix Delegated Administration Service is unknown.		Check that the database is running and that you can connect to the database from the server by running sqlcmd. Contact Citrix Support and provide them with the CDF logs for the service.	Warning
2302aa5c-60b5-4ab6-9645-5e3c9c6d5332e	Unknown registration state for Citrix Environment Test Service	The registration state for the Citrix Environment Test Service is unknown.		The registration state for the Citrix Environment Test Service is unknown.		Check that the database is running and that you can connect to the database from the server by running sqlcmd. Contact Citrix Support and provide them with the CDF logs for the service.	Warning
37dfc8ba-6841-4200-bbce-d3129f90a05	Unknown registration state for Citrix Host Availability Service	The registration state for the Citrix Host Availability Service is unknown.		The registration state for the Citrix Host Availability Service is unknown.		Check that the database is running and that you can connect to the database from the server by running sqlcmd. Contact Citrix Support and provide them with the CDF logs for the service.	Warning
b71ecb88-a669-4b28-8272-cb59f79e0e4	Unknown registration state for Citrix Machine Creation Service	The registration state for the Citrix Machine Creation Service is unknown.		The registration state for the Citrix Machine Creation Service is unknown.		Check that the database is running and that you can connect to the database from the server by running sqlcmd. Contact Citrix Support and provide them with the CDF logs for the service.	Warning
b88003db-9d50-4e6e-9920-53d20c4413c1	Unknown registration state for Citrix Monitor Service	The registration state for the Citrix Monitor Service is unknown.		The registration state for the Citrix Monitor Service is unknown.		Check that the database is running and that you can connect to the database from the server by running sqlcmd. Contact Citrix Support and provide them with the CDF logs for the service.	Warning
90dbd3f3-17e0-4421-a698-ba4886988294	Unknown registration state for Citrix Storefront Service	The registration state for the Citrix Storefront Service is unknown.		The registration state for the Citrix Storefront Service is unknown.		Check that the database is running and that you can connect to the database from the server by running sqlcmd. Contact Citrix Support and provide them with the CDF logs for the service.	Warning
a9f787a-5fb1-48c3-9b06-b3c8916193a	Undefined feature for Citrix Broker Service	The Citrix Broker Service is using the feature {{featureName}} which is not defined in the list of available features.	The undefined feature is {{featureName}}.	The Citrix Broker Service is using a feature which is not defined in the list of available features.		Check the Configuration Service is fully configured and that the correct product edition is set.	Warning
985ca1ab-0540-4bde-a056-4e4aa03d1d6e	Undefined feature for Citrix Delegated Administration Service	The Citrix Delegated Administration Service is using the feature {{featureName}} which is not defined in the list of available features.	The undefined feature is {{featureName}}.	The Citrix Delegated Administration Service is using a feature which is not defined in the list of available features.		Check the Configuration Service is fully configured and that the correct product edition is set.	Warning
f252c249-5d78-458e-a543-199c86804338	File name not valid for Citrix AD Identity Service file-based logging	The file path {{filePath}}, used for file-based logging for the Citrix AD Identity Service, is invalid or does not exist.	The file path is {{filePath}}.	A file path used for file-based logging for the Citrix AD Identity Service is invalid or does not exist.		Specify a valid file path for file-based logging in the App.config file for the service.	Warning
9d9ba047-cfe9-4424-bfb7-a02d9f1f319	File name not valid for Citrix Analytics Service file-based logging	The file path {{filePath}}, used for file-based logging for the Citrix Analytics Service, is invalid or does not exist.	The file path is {{filePath}}.	A file path used for file-based logging for the Citrix Analytics Service is invalid or does not exist.		Specify a valid file path for file-based logging in the App.config file for the service.	Warning
42d3aec0-2b35-42f8-a47b-027b45e1e389	File name not valid for Citrix App Library Service file-based logging	The file path {{filePath}}, used for file-based logging for the Citrix App Library Service, is invalid or does not exist.	The file path is {{filePath}}.	A file path used for file-based logging for the Citrix App Library Service is invalid or does not exist.		Specify a valid file path for file-based logging in the App.config file for the service.	Warning
ccb4bb0e-69f9-443c-9b78-b8e0ff8e750	File name not valid for Citrix Broker Service file-based logging	The file path {{filePath}}, used for file-based logging for the Citrix Broker Service, is invalid or does not exist.	The file path is {{filePath}}.	A file path used for file-based logging for the Citrix Broker Service is invalid or does not exist.		Specify a valid file path for file-based logging in the App.config file for the service.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
5183ba9-e6a4-411a-bce8-609a9c95efdc	File name not valid for Citrix Configuration Service file-based logging	The file path {{FilePath}}, used for file-based logging for the Citrix Configuration Service, is invalid or does not exist.	The file path is {{FilePath}}.	A file path used for file-based logging for the Citrix Configuration Service is invalid or does not exist.		Specify a valid file path for file-based logging in the App.config file for the service.	Warning
21807b57-0798-498a-8716-a9772d578a8	File name not valid for Citrix Configuration Logging Service file-based logging	The file path {{FilePath}}, used for file-based logging for the Citrix Configuration Logging Service, is invalid or does not exist.	The file path is {{FilePath}}.	A file path used for file-based logging for the Citrix Configuration Logging Service is invalid or does not exist.		Specify a valid file path for file-based logging in the App.config file for the service.	Warning
f16d8732-6d51-439e-88a4-f9d7945aca2a	File name not valid for Citrix Delegated Administration Service file-based logging	The file path {{FilePath}}, used for file-based logging for the Citrix Delegated Administration Service, is invalid or does not exist.	The file path is {{FilePath}}.	A file path used for file-based logging for the Citrix Delegated Administration Service is invalid or does not exist.		Specify a valid file path for file-based logging in the App.config file for the service.	Warning
6df7857b-31c7-455f-9243-72a255f614f	File name not valid for Citrix Environment Test Service file-based logging	The file path {{FilePath}}, used for file-based logging for the Citrix Environment Test Service, is invalid or does not exist.	The file path is {{FilePath}}.	A file path used for file-based logging for the Citrix Environment Test Service is invalid or does not exist.		Specify a valid file path for file-based logging in the App.config file for the service.	Warning
6ada8857-94e7-438f-80c1-71369d12261	File name not valid for Citrix Host Availability Service file-based logging	The file path {{FilePath}}, used for file-based logging for the Citrix Host Availability Service, is invalid or does not exist.	The file path is {{FilePath}}.	A file path used for file-based logging for the Citrix Host Availability Service is invalid or does not exist.		Specify a valid file path for file-based logging in the App.config file for the service.	Warning
64432ac8-520e-452f-88a5-cd3728f7d043	File name not valid for Citrix Machine Creation Service file-based logging	The file path {{FilePath}}, used for file-based logging for the Citrix Machine Creation Service, is invalid or does not exist.	The file path is {{FilePath}}.	A file path used for file-based logging for the Citrix Machine Creation Service is invalid or does not exist.		Specify a valid file path for file-based logging in the App.config file for the service.	Warning
aacd11d8-d5e0-461d-8932-f89c2fb16161	File name not valid for Citrix Monitor Service file-based logging	The file path {{FilePath}}, used for file-based logging for the Citrix Monitor Service, is invalid or does not exist.	The file path is {{FilePath}}.	A file path used for file-based logging for the Citrix Monitor Service is invalid or does not exist.		Specify a valid file path for file-based logging in the App.config file for the service.	Warning
72bee29c-57b2-44b5-a19b-d0e8dc65092	File name not valid for Citrix Storefront Service file-based logging	The file path {{FilePath}}, used for file-based logging for the Citrix Storefront Service, is invalid or does not exist.	The file path is {{FilePath}}.	A file path used for file-based logging for the Citrix Storefront Service is invalid or does not exist.		Specify a valid file path for file-based logging in the App.config file for the service.	Warning
3aed50bf-9063-4a68-a996-d36c27b42728	Log file access error for Citrix AD Identity Service	The Citrix AD Identity Service does not have write permissions for the log directory {{FilePath}}.	The log directory is {{FilePath}}.	The Citrix AD Identity Service does not have write permissions for the log directory.		Grant write access permissions to the directory for the log file.	Warning
cb1db60d-8978-46ed-9346-9793906a2b7e	Log file access error for Citrix Analytics Service	The Citrix Analytics Service does not have write permissions for the log directory {{FilePath}}.	The log directory is {{FilePath}}.	The Citrix Analytics Service does not have write permissions for the log directory.		Grant write access permissions to the directory.	Warning
52374a8e-10bf-4619-98ed-bd1c4a46854	Log file access error for Citrix AppLibrary Service	The Citrix App Library Service does not have write permissions for the log directory {{FilePath}}.	The log directory is {{FilePath}}.	The Citrix App Library Service does not have write permissions for the log directory.		Grant write access permissions to the directory.	Warning
e18b979f-6dbf-4462-91dc-0c4539c07a0f	Log file access error for Citrix Broker Service	The Citrix Broker Service does not have write permissions for the log directory {{FilePath}}.	The log directory is {{FilePath}}.	The Citrix Broker Service does not have write permissions for the log directory.		Grant write access permissions to the directory.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
176dd772-dfcb-4d5b-91cb-6a0a42fab193	Log file access error for Citrix Configuration Service	The Citrix Configuration Service does not have write permissions for the log directory {{{filePath}}}.	The log directory is {{{filePath}}}.	The Citrix Configuration Service does not have write permissions for the log directory.		Grant write access permissions to the directory.	Warning
6822e063-7cec-48f1-8472-ac3345751758	Log file access error for Citrix Configuration Logging Service	The Citrix Configuration Logging Service does not have write permissions for the log directory {{{filePath}}}.	The log directory is {{{filePath}}}.	The Citrix Configuration Logging Service does not have write permissions for the log directory.		Grant write access permissions to the directory.	Warning
7f80907-8de3-4987-b98e-531c0a8350e4	Log file access error for Citrix Delegated Administration Service	The Citrix Delegated Administration Service does not have write permissions for the log directory {{{filePath}}}.	The log directory is {{{filePath}}}.	The Citrix Delegated Administration Service does not have write permissions for the log directory.		Grant write access permissions to the directory.	Warning
9c2c598-4aed-4492-b2d5-0847d49310ee	Log file access error for Citrix Environment Test Service	The Citrix Environment Test Service does not have write permissions for the log directory {{{filePath}}}.	The log directory is {{{filePath}}}.	The Citrix Environment Test Service does not have write permissions for the log directory.		Grant write access permissions to the directory.	Warning
432e5666-4840-40d1-aa30-ecf8794e84f8	Log file access error for Citrix Host Availability Service	The Citrix Host Availability Service does not have write permissions for the log directory {{{filePath}}}.	The log directory is {{{filePath}}}.	The Citrix Host Availability Service does not have write permissions for the log directory.		Grant write access permissions to the directory.	Warning
0c1cd4ef-fae8-4456-a9e9-87ee7e99192a	Log file access error for Citrix Machine Creation Service	The Citrix Machine Creation Service does not have write permissions for the log directory {{{filePath}}}.	The log directory is {{{filePath}}}.	The Citrix Machine Creation Service does not have write permissions for the log directory.		Grant write access permissions to the directory.	Warning
472af179-0d66-493a-9994-c05a4f27d2b4	Log file access error for Citrix Monitor Service	The Citrix Monitor Service does not have write permissions for the log directory {{{filePath}}}.	The log directory is {{{filePath}}}.	The Citrix Monitor Service does not have write permissions for the log directory.		Grant write access permissions to the directory.	Warning
5a969e19-6a0f4-479d-832b-1df25f1d28ca	Log file access error for Citrix Storefront Service	The Citrix Storefront Service does not have write permissions for the log directory {{{filePath}}}.	The log directory is {{{filePath}}}.	The Citrix Storefront Service does not have write permissions for the log directory.		Grant write access permissions to the directory.	Warning
9f53d56-8463-4cc4-b45e-7bd3e6109f1a	Low disk space for Citrix AD Identity Service file-based logging	There is insufficient disk space available on the drive {{{driveName}}} for Citrix ADIdentity Service file-based logging. The drive has {{{freeSpace}}} of remaining space. The minimum free space requirement is 100 MB.	The drive is {{{driveName}}}. The remaining space is {{{freeSpace}}}.	There is insufficient disk space available on the drive for Citrix ADIdentity Service file-based logging. The minimum free space requirement is 100 MB.		Ensure there is sufficient free space available on the disk.	Warning
b24ef42-216f-4aac-9e41-c91578482af4	Low disk space for Citrix Analytics Service file-based logging	There is insufficient disk space on the drive {{{driveName}}} available for Citrix Analytics Service file-based logging. The drive has {{{freeSpace}}} of remaining space. The minimum free space requirement is 100 MB.	The drive is {{{driveName}}}. The remaining space is {{{freeSpace}}}.	There is insufficient disk space on the drive available for Citrix Analytics Service file-based logging. The minimum free space requirement is 100 MB.		Ensure there is sufficient free space available on the disk.	Warning
d1c0f2b5-f2a4-419f-bd86-aca716eaf14	Low disk space for Citrix App Library Service file-based logging	There is insufficient disk space available on the drive {{{driveName}}} for Citrix App Library Service file-based logging. The drive has {{{freeSpace}}} of remaining space. The minimum free space requirement is 100 MB.	The drive is {{{driveName}}}. The remaining space is {{{freeSpace}}}.	There is insufficient disk space available on the drive for Citrix App Library Service file-based logging. The minimum free space requirement is 100 MB.		Ensure there is sufficient free space available on the disk.	Warning
2507c3f-3403-42ef-9451-e7d29cc2d660	Low disk space for Citrix Broker Service file-based logging	There is insufficient disk space available on the drive {{{driveName}}} for Citrix Broker Service file-based logging. The drive has {{{freeSpace}}} of remaining space. The minimum free space requirement is 100 MB.	The drive is {{{driveName}}}. The remaining space is {{{freeSpace}}}.	There is insufficient disk space available on the drive for Citrix Broker Service file-based logging. The minimum free space requirement is 100 MB.		Ensure there is sufficient free space available on the disk.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
69cd40e-df89-409f-8329-93774045c5b	Low disk space for Citrix Configuration Service file-based logging	There is insufficient disk space available on the drive {{driveName}} for Citrix Configuration Service file-based logging. The drive has {{freeSpace}} of remaining space. The minimum free space requirement is 100 MB.	The drive is {{driveName}}. The remaining space is {{freeSpace}}.	There is insufficient disk space available on the drive for Citrix Configuration Service file-based logging. The minimum free space requirement is 100 MB.		Ensure there is sufficient free space available on the disk.	Warning
7eb803fa-d132-4572-93ba-13ed895e0a8	Low disk space for Citrix Configuration Logging Service file-based logging	There is insufficient disk space available on the drive {{driveName}} for Citrix Configuration Logging Service file-based logging. The drive has {{freeSpace}} of remaining space. The minimum free space requirement is 100 MB.	The drive is {{driveName}}. The remaining space is {{freeSpace}}.	There is insufficient disk space available on the drive for Citrix Configuration Logging Service file-based logging. The minimum free space requirement is 100 MB.		Ensure there is sufficient free space available on the disk.	Warning
f1303973-5e4d-4be5-8c9f-cf8c0fa0839	Low disk space for Citrix Delegated Administration Service file-based logging	There is insufficient disk space available on the drive {{driveName}} for Citrix Delegated Administration Service file-based logging. The drive has {{freeSpace}} of remaining space. The minimum free space requirement is 100 MB.	The drive is {{driveName}}. The remaining space is {{freeSpace}}.	There is insufficient disk space available on the drive for Citrix Delegated Administration Service file-based logging. The minimum free space requirement is 100 MB.		Ensure there is sufficient free space available on the disk.	Warning
2386d90c-59ed-491f-9c15-a89529fe4cb	Low disk space for Citrix Environment Test Service file-based logging	There is insufficient disk space available on the drive {{driveName}} for Citrix Environment Test Service file-based logging. The drive has {{freeSpace}} of remaining space. The minimum free space requirement is 100 MB.	The drive is {{driveName}}. The remaining space is {{freeSpace}}.	There is insufficient disk space available on the drive for Citrix Environment Test Service file-based logging. The minimum free space requirement is 100 MB.		Ensure there is sufficient free space available on the disk.	Warning
e909d04d-25fb-4c74-9c4f-bab063f1747c	Low disk space for Citrix Host Availability Service file-based logging	There is insufficient disk space available on the drive {{driveName}} for Citrix Host Availability Service file-based logging. The drive has {{freeSpace}} of remaining space. The minimum free space requirement is 100 MB.	The drive is {{driveName}}. The remaining space is {{freeSpace}}.	There is insufficient disk space available on the drive for Citrix Host Availability Service file-based logging. The minimum free space requirement is 100 MB.		Ensure there is sufficient free space available on the disk.	Warning
d6edc13f-c863-4b28-9f4e-f58f8eb93a7	Low disk space for Citrix Machine Creation Service file-based logging	There is insufficient disk space available on the drive {{driveName}} for Citrix Machine Creation Service file-based logging. The drive has {{freeSpace}} of remaining space. The minimum free space requirement is 100 MB.	The drive is {{driveName}}. The remaining space is {{freeSpace}}.	There is insufficient disk space available on the drive for Citrix Machine Creation Service file-based logging. The minimum free space requirement is 100 MB.		Ensure there is sufficient free space available on the disk.	Warning
182da7dd-64b4-47ec-a54-5a3e37120aad	Low disk space for Citrix Monitor Service file-based logging	There is insufficient disk space available on the drive {{driveName}} for Citrix Monitor Service file-based logging. The drive has {{freeSpace}} of remaining space. The minimum free space requirement is 100 MB.	The drive is {{driveName}}. The remaining space is {{freeSpace}}.	There is insufficient disk space available on the drive for Citrix Monitor Service file-based logging. The minimum free space requirement is 100 MB.		Ensure there is sufficient free space available on the disk.	Warning
1ed38784-a7ae-4803-911e-ac1896c31f	Low disk space for Citrix Storefront Service file-based logging	There is insufficient disk space available on the drive {{driveName}} for Citrix Storefront Service file-based logging. The drive has {{freeSpace}} of remaining space. The minimum free space requirement is 100MB.	The drive is {{driveName}}. The remaining space is {{freeSpace}}.	There is insufficient disk space available on the drive for Citrix Storefront Service file-based logging. The minimum free space requirement is 100MB.		Ensure there is sufficient free space available on the disk.	Warning
8dc378b6-1894-417a-8c53-8a43b19301c	Drive information error for Citrix AD Identity Service file-based logging	The drive information for {{filePath}}, used for Citrix AD Identity Service file-based logging, could not be retrieved.	The drive directory is {{filePath}}.	The drive information used for Citrix AD Identity Service file-based logging could not be retrieved.		Ensure the specified location for file-based logging is valid and the drive is accessible.	Warning
c1515418-506b-4acd-a81a-5984af21788	Drive information error for Citrix Analytics Service file-based logging	The drive information for {{filePath}}, used for Citrix Analytics Service file-based logging, could not be retrieved.	The drive directory is {{filePath}}.	The drive information used for Citrix Analytics Service file-based logging could not be retrieved.		Ensure the specified location for file-based logging is valid and the drive is accessible.	Warning
7256dacb-f5a3-4d11-9491-5427a7068b8	Drive information error for Citrix App Library Service file-based logging	The drive information for {{filePath}}, used for Citrix App Library Service file-based logging, could not be retrieved.	The drive directory is {{filePath}}.	The drive information used for Citrix App Library Service file-based logging could not be retrieved.		Ensure the specified location for file-based logging is valid and the drive is accessible.	Warning
8dc2ecba-65d4-4fc9-9d6b-f93a38782f2	Drive information error for Citrix Broker Service file-based logging	The drive information for {{filePath}}, used for Citrix Broker Service file-based logging, could not be retrieved.	The drive directory is {{filePath}}.	The drive information used for Citrix Broker Service file-based logging could not be retrieved.		Ensure the specified location for file-based logging is valid and the drive is accessible.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
f5808700-8f08-4716-8c40-60ac14f18d35	Drive information error for Citrix Configuration Service file-based logging	The drive information for {{filePath}}, used for Citrix Configuration Service file-based logging, could not be retrieved.	The drive directory is {{filePath}}.	The drive information for used for Citrix Configuration Service file-based logging could not be retrieved.		Ensure the specified location for file-based logging is valid and the drive is accessible.	Warning
73b9f2b9-00a5-46c5-a00a-168d78b9194f	Drive information error for Citrix Configuration Logging Service file-based logging	The drive information for {{filePath}}, used for Citrix Configuration Logging Service file-based logging, could not be retrieved.	The drive directory is {{filePath}}.	The drive information for used for Citrix Configuration Logging Service file-based logging could not be retrieved.		Ensure the specified location for file-based logging is valid and the drive is accessible.	Warning
ede1d48d-6d5c-47ef-9741-f503dc3ba19	Drive information error for Citrix Delegated Administration Service file-based logging	The drive information for {{filePath}}, used for Citrix Delegated Administration Service file-based logging, could not be retrieved.	The drive directory is {{filePath}}.	The drive information for used for Citrix Delegated Administration Service file-based logging could not be retrieved.		Ensure the specified location for file-based logging is valid and the drive is accessible.	Warning
3f504099-58d5-4bb4-bcd-d3a331fe4a67	Drive information error for Citrix Environment Test Service file-based logging	The drive information for {{filePath}}, used for Citrix Environment Test Service file-based logging, could not be retrieved.	The drive directory is {{filePath}}.	The drive information for used for Citrix Environment Test Service file-based logging could not be retrieved.		Ensure the specified location for file-based logging is valid and the drive is accessible.	Warning
462b3bc2-5494-4558-b9b7-c81c7536e46c	Drive information error for Citrix Host Availability Service file-based logging	The drive information for {{filePath}}, used for Citrix Host Availability Service file-based logging, could not be retrieved.	The drive directory is {{filePath}}.	The drive information for used for Citrix Host Availability Service file-based logging could not be retrieved.		Ensure the specified location for file-based logging is valid and the drive is accessible.	Warning
5090c86-4b11-45e9-b768-f1d9904dc6ad	Drive information error for Citrix Machine Creation Service file-based logging	The drive information for {{filePath}}, used for Citrix Machine Creation Service file-based logging, could not be retrieved.	The drive directory is {{filePath}}.	The drive information for used for Citrix Machine Creation Service file-based logging could not be retrieved.		Ensure the specified location for file-based logging is valid and the drive is accessible.	Warning
0d66abc3-cd84-4266-93e4-22dbf0bbab1d	Drive information error for Citrix Monitor Service file-based logging	The drive information for {{filePath}}, used for Citrix Monitor Service file-based logging, could not be retrieved.	The drive directory is {{filePath}}.	The drive information for used for Citrix Monitor Service file-based logging could not be retrieved.		Ensure the specified location for file-based logging is valid and the drive is accessible.	Warning
75074bda-4ab6-4d3a-a95b-705519327e13	Drive information error for Citrix Storefront Service file-based logging	The drive information for {{filePath}}, used for Citrix Storefront Service file-based logging, could not be retrieved.	The drive directory is {{filePath}}.	The drive information for used for Citrix Storefront Service file-based logging could not be retrieved.		Ensure the specified location for file-based logging is valid and the drive is accessible.	Warning
52798b71-2e5f-4620-ab43-c6936c0b8f0f	URL not reserved for Citrix AD Identity Service	The service endpoint for the Citrix AD Identity Service - {{serviceEndpointURL}} - is not registered in the HTTP/HTTPS namespace.	The service endpoint URL is {{serviceEndpointURL}}.	The service endpoint for the Citrix AD Identity Service is not registered in the HTTP/HTTPS namespace.		Run Post Install Pre-Configuration (PICP) by running the Citrix AD Identity Service executable.	Warning
4876f23-e334-4b73-85f5-a66644926382	URL not reserved for Citrix Analytics Service	The service endpoint for the Citrix Analytics Service - {{serviceEndpointURL}} - is not registered in the HTTP/HTTPS namespace.	The service endpoint URL is {{serviceEndpointURL}}.	The service endpoint for the Citrix Analytics Service is not registered in the HTTP/HTTPS namespace.		Run Post Install Pre-Configuration (PICP) by running the Citrix Analytics Service executable.	Warning
75a0c70a-87dc-4465-8c5f-5832a0179982	URL not reserved for Citrix App Library Service	The service endpoint for the Citrix App Library Service - {{serviceEndpointURL}} - is not registered in the HTTP/HTTPS namespace.	The service endpoint URL is {{serviceEndpointURL}}.	The service endpoint for the Citrix App Library Service is not registered in the HTTP/HTTPS namespace.		Run Post Install Pre-Configuration (PICP) by running the Citrix App Library Service executable.	Warning
d7f5f6d0-92b3-4018-a394-6e5d969a37e0	URL not reserved for Citrix Broker Service	The service endpoint for the Citrix Broker Service - {{serviceEndpointURL}} - is not registered in the HTTP/HTTPS namespace.	The service endpoint URL is {{serviceEndpointURL}}.	The service endpoint for the Citrix Broker Service is not registered in the HTTP/HTTPS namespace.		Run Post Install Pre-Configuration (PICP) by running the Citrix Broker Service executable.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
5dc08996-aefc-4e93-93a9-c935fa8d60	URL not reserved for Citrix Configuration Service	The service endpoint for the Citrix Configuration Service -- {{serviceEndpointUrl}} -- is not registered in the HTTP/HTTPS namespace.	The service endpoint URL is {{serviceEndpointUrl}}.	The service endpoint for the Citrix Configuration Service is not registered in the HTTP/HTTPS namespace.		Run Post Install Pre-Configuration (PIP) by running the Citrix Configuration Service executable.	Warning
31b2198f-4e87-41d0-8c75-42880a5e2c5	URL not reserved for Citrix Configuration Logging Service	The service endpoint for the Citrix Configuration Logging Service -- {{serviceEndpointUrl}} -- is not registered in the HTTP/HTTPS namespace.	The service endpoint URL is {{serviceEndpointUrl}}.	The service endpoint for the Citrix Configuration Logging Service is not registered in the HTTP/HTTPS namespace.		Run Post Install Pre-Configuration (PIP) by running the Citrix Configuration Logging Service executable.	Warning
39f18ce8-312e-4ec3-977a-ed7d6f6c1e1	URL not reserved for Citrix Delegated Administration Service	The service endpoint for the Citrix Delegated Administration Service -- {{serviceEndpointUrl}} -- is not registered in the HTTP/HTTPS namespace.	The service endpoint URL is {{serviceEndpointUrl}}.	The service endpoint for the Citrix Delegated Administration Service is not registered in the HTTP/HTTPS namespace.		Run Post Install Pre-Configuration (PIP) by running the Citrix Delegated Administration Service executable.	Warning
a627266f-bb9b-4659-bd73-08a7296c548b	URL not reserved for Citrix Environment Test Service	The service endpoint for Citrix Environment Test Service -- {{serviceEndpointUrl}} -- is not registered in the HTTP/HTTPS namespace.	The service endpoint URL is {{serviceEndpointUrl}}.	The service endpoint for Citrix Environment Test Service is not registered in the HTTP/HTTPS namespace.		Run Post Install Pre-Configuration (PIP) by running the Citrix Environment Test Service executable.	Warning
3b15340b-882b-426f-ad64-2d7fa48b37	URL not reserved for Citrix Host Availability Service	The service endpoint for the Citrix Host Availability Service -- {{serviceEndpointUrl}} -- is not registered in the HTTP/HTTPS namespace.	The service endpoint URL is {{serviceEndpointUrl}}.	The service endpoint for the Citrix Host Availability Service is not registered in the HTTP/HTTPS namespace.		Run Post Install Pre-Configuration (PIP) by running the Citrix Host Availability Service executable.	Warning
0d1fa9a7-9525-4ca0-b5e8-f371d99868	URL not reserved for Citrix Machine Creation Service	The service endpoint for Citrix Machine Creation Service -- {{serviceEndpointUrl}} -- is not registered in the HTTP/HTTPS namespace.	The service endpoint URL is {{serviceEndpointUrl}}.	The service endpoint for Citrix Machine Creation Service is not registered in the HTTP/HTTPS namespace.		Run Post Install Pre-Configuration (PIP) by running the Citrix Machine Creation Service executable.	Warning
2a4723a8-2e5d-4b18-8e12-05f8747c848	URL not reserved for Citrix Monitor Service	The service endpoint for the Citrix Monitor Service -- {{serviceEndpointUrl}} -- is not registered in the HTTP/HTTPS namespace.	The service endpoint URL is {{serviceEndpointUrl}}.	The service endpoint for the Citrix Monitor Service is not registered in the HTTP/HTTPS namespace.		Run Post Install Pre-Configuration (PIP) by running the Citrix Monitor Service executable.	Warning
3843da0f-9daa-4b38-b075-583a9d1e99	URL not reserved for Citrix Storefront Service	The service endpoint for the Citrix Storefront Service -- {{serviceEndpointUrl}} -- is not registered in the HTTP/HTTPS namespace.	The service endpoint URL is {{serviceEndpointUrl}}.	The service endpoint for the Citrix Storefront Service is not registered in the HTTP/HTTPS namespace.		Run Post Install Pre-Configuration (PIP) by running the Citrix Storefront Service executable.	Warning
37ae4f81-5a82-4db4-82d0-d90ab9c28de	Peer service instance of Citrix AD Identity Service failed to connect to endpoint	The registered peer service instance of the Citrix AD Identity Service, {{serviceInstanceAddr}}, failed to connect to the endpoint. The instance service type is {{instanceServiceType}} and the service instance account is {{serviceInstanceAccount}}. The AD Identity Service handles all computer accounts (identities) related to XenApp and XenDesktop physical and virtual machines. (Reprinted from The Citrix XenApp & XenDesktop PMA Services complete overview) http://www.basvanikaam.com/2016/12/25/the-citrix-xenapp-xendesktop-fma-services-complete-overview-new-7-12-services-accounts/	The service instance address is {{serviceInstanceAddr}}; The instance service type is {{instanceServiceType}}; The service instance account is {{serviceInstanceAccount}}.	The registered peer service instance of the Citrix AD Identity Service failed to connect to the endpoint. The AD Identity Service handles all computer accounts (identities) related to XenApp and XenDesktop physical and virtual machines. (Reprinted from The Citrix XenApp & XenDesktop PMA Services complete overview) http://www.basvanikaam.com/2016/12/25/the-citrix-xenapp-xendesktop-fma-services-complete-overview-new-7-12-services-accounts/	[Bas Van Kaam] http://www.basvanikaam.com , Citrix Technology Professional	To resolve this issue, perform the following actions: 1. Verify the Delivery Controller is powered on and connected to the Internet. 2. Restart the Citrix AD Identity Service: Click "Start", type "services.msc", and then press "ENTER". From the Services console, select "Citrix AD Identity Service" and then click "Restart". 3. If restarting the service does not resolve the issue, rebuild the Delivery Controller.	Warning
339e0742-9e42-494b-83ca-df9e8938105d	Peer service instance of Citrix AppLibraryService failed to connect to endpoint	The registered peer service instance of the Citrix App Library Service, {{serviceInstanceAddr}}, failed to connect to the endpoint. * Instance service type: {{instanceServiceType}} * Service instance account: {{serviceInstanceAccount}}	The service instance address is {{serviceInstanceAddr}}; The instance service type is {{instanceServiceType}}; The service instance account is {{serviceInstanceAccount}}.	The registered peer service instance of the Citrix App Library Service failed to connect to the endpoint.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix service(s) that cannot be contacted.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
90bd5a8-efb3-4976-9e34-0a5af07d31f2	Peer service instance of Citrix Broker Service failed to connect to endpoint	The registered peer service instance of the Citrix Broker Service. {{serviceinstanceAddr}} failed to connect to the endpoint. The instance service type is {{instanceServiceType}} and the service instance account is {{serviceinstanceAccount}}. The Broker Service takes care of VDA registration, resource allocation, connection brokering, and licensing enforcement, among other tasks. Additionally, it takes care of all communication to and from the Delivery Controller. It does this by communicating with the VDA Citrix Desktop Service (BrokerAgent.exe), which is part of the desktop as well as server VDA. (Reprinted from [The Citrix XenApp & XenDesktop FMA Services complete overview](http://www.basvankaam.com/2016/12/15/the-citrix-xenapp-xendesktop-fma-services-complete-overview-new-7-12-services-included/))	The service instance address is {{serviceinstanceAddr}}; The instance service type is {{instanceServiceType}}; The service instance account is {{serviceinstanceAccount}}.	The registered peer service instance of the Citrix Broker Service failed to connect to the endpoint. The Broker Service takes care of VDA registration, resource allocation, connection brokering, and licensing enforcement, among other tasks. Additionally, it takes care of all communication to and from the Delivery Controller. It does this by communicating with the VDA Citrix Desktop Service (BrokerAgent.exe), which is part of the desktop as well as server VDA. (Reprinted from [The Citrix XenApp & XenDesktop FMA Services complete overview](http://www.basvankaam.com/2016/12/15/the-citrix-xenapp-xendesktop-fma-services-complete-overview-new-7-12-services-included/))	[Bas Van Kaam](http://www.basvankaam.com), Citrix Technology Professional	To resolve this issue, perform the following actions: 1. Verify the Delivery Controller is powered on and connected to the Internet. 2. Restart the Citrix Broker Service: Click "Start", type "services.msc", and then press "ENTER". From the Services console, select "Citrix Broker Service" and then click "Restart". 3. If restarting the service does not resolve the issue, rebuild the Delivery Controller.	Warning
1298a5ba-07ef-49d3-a35b-a5596902bbd5	Peer service instance of Citrix Host Service failed to connect to endpoint	The registered peer service instance of the Citrix Host Service. {{serviceinstanceAddr}} failed to connect to the endpoint. * Instance service type: {{instanceServiceType}} * Service instance account: {{serviceinstanceAccount}}	The service instance address is {{serviceinstanceAddr}}; The instance service type is {{instanceServiceType}}; The service instance account is {{serviceinstanceAccount}}.	The registered peer service instance of the Citrix Host Service failed to connect to the endpoint.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix service(s) that cannot be contacted.	Warning
ae51d2f9-e9dc-4108-8f8f-7028a50aba5	Peer service instance of Citrix Monitor Service failed to connect to endpoint	The registered peer service instance of the Citrix Monitor Service. {{serviceinstanceAddr}} failed to connect to the endpoint. * Instance service type: {{instanceServiceType}} * Service instance account: {{serviceinstanceAccount}}	The service instance address is {{serviceinstanceAddr}}; The instance service type is {{instanceServiceType}}; The service instance account is {{serviceinstanceAccount}}.	The registered peer service instance of the Citrix Monitor Service failed to connect to the endpoint.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix service(s) that cannot be contacted.	Warning
5850e8ab-341e-4468-b899-4c82d693fab3	Mismatched Configuration Service instance for Citrix AD Identity Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix AD Identity Service. The service instance {{serviceinstanceAddr}} does not match the instances stored in the database.	The mismatched service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix AD Identity Service. The service instance does not match the instances stored in the database.		Use the following command to refresh the list of addresses for the Configuration Service instance: Get-Config@RegisteredServiceInstance -ServiceType Config Reset-ActServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Warning
57c5d566-d670-47ee-b9f5-7c0ef15019d	Mismatched Configuration Service instance for Citrix Analytics Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Analytics Service. The service instance {{serviceinstanceAddr}} does not match the instances stored in the database.	The mismatched service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Analytics Service. The service instance does not match the instances stored in the database.		Use the following command to refresh the list of addresses for the Configuration Service instance: Get-Config@RegisteredServiceInstance -ServiceType Config Reset-AnalyticServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Warning
4f3d2e16-d2f1-405d-864e-d0282b03e64c	Mismatched Configuration Service instance for Citrix AppLibrary Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix App Library Service. The service instance {{serviceinstanceAddr}} does not match the instances stored in the database.	The mismatched service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix App Library Service. The service instance does not match the instances stored in the database.		Use the following command to refresh the list of addresses for the Configuration Service instance: Get-Config@RegisteredServiceInstance -ServiceType Config Reset-AppLibServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Warning
2baa35e9-9589-40bd-8016-8428c99c789	Mismatched Configuration Service instance for Citrix Broker Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Broker Service. The service instance {{serviceinstanceAddr}} does not match the instances stored in the database.	The mismatched service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Broker Service. The service instance does not match the instances stored in the database.		Use the following command to refresh the list of addresses for the Configuration Service instance: Get-Config@RegisteredServiceInstance -ServiceType Config Reset-BrokerServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Warning
e6738159-4e74-4463-a981-4feb3930dcb	Mismatched Configuration Service instance for Citrix Configuration Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Configuration Service. The service instance {{serviceinstanceAddr}} does not match the instances stored in the database.	The mismatched service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Configuration Service. The service instance does not match the instances stored in the database.		Use the following command to refresh the list of addresses for the Configuration Service instance: Get-Config@RegisteredServiceInstance -ServiceType Config Reset-ConfigServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Error
e653bd6f-6b17-4dda-8fab-fb97dbb9e9fd	Mismatched Configuration Service instance for Citrix Configuration Logging Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Configuration Logging Service. The service instance {{serviceinstanceAddr}} does not match the instances stored in the database.	The mismatched service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Configuration Logging Service. The service instance does not match the instances stored in the database.		Use the following command to refresh the list of addresses for the Configuration Service instance: Get-Config@RegisteredServiceInstance -ServiceType Config Reset-LogServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Warning
c9c1727e-8405-4cde-8456-76c549a9e5ae	Mismatched Configuration Service instance for Citrix Delegated Administration Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Delegated Administration Service. The service instance {{serviceinstanceAddr}} does not match the instances stored in the database.	The mismatched service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Delegated Administration Service. The service instance does not match the instances stored in the database.		Use the following command to refresh the list of addresses for the Configuration Service instance: Get-Config@RegisteredServiceInstance -ServiceType Config Reset-AdminServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
6883e422-7f54-483b-ba7f-319c9bac01a	Mismatched Configuration Service instance for Citrix Environment Test Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Environment Test Service. The service instance {{serviceinstanceAddr}} does not match the instances stored in the database.	The mismatched service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Environment Test Service. The service instance does not match the instances stored in the database.		Use the following command to refresh the list of addresses for the Configuration Service instance: Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-EnvTestServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Warning
d8941144-8d66-4b78-b2a7-3786807c355e	Mismatched Configuration Service instance for Citrix Host Availability Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Host Availability Service. The service instance {{serviceinstanceAddr}} does not match the instances stored in the database.	The mismatched service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Host Availability Service. The service instance does not match the instances stored in the database.		Use the following command to refresh the list of addresses for the Configuration Service instance: Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-HypervisorGroupMembership cmdlet For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Warning
363e2a48-6e77-4830-8473-d2148789f4d0	Mismatched Configuration Service instance for Citrix Machine Creation Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Machine Creation Service. The service instance {{serviceinstanceAddr}} does not match the instances stored in the database.	The mismatched service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Machine Creation Service. The service instance does not match the instances stored in the database.		Use the following command to refresh the list of addresses for the Configuration Service instance: Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-ProdServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Warning
a4f63c5-f76-42fa-9e97-325c1487d0f4	Mismatched Configuration Service instance for Citrix Monitor Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Monitor Service. The service instance {{serviceinstanceAddr}} does not match the instances stored in the database.	The mismatched service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Monitor Service. The service instance does not match the instances stored in the database.		Use the following command to refresh the list of addresses for the Configuration Service instance: Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-MonitorServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Warning
e0d748a7-2cb7-4d65-b4b5-93b60c2966eb	Mismatched Configuration Service instance for Citrix Storefront Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Storefront Service. The service instance {{serviceinstanceAddr}} does not match the instances stored in the database.	The mismatched service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Storefront Service. The service instance does not match the instances stored in the database.		Use the following command to refresh the list of addresses for the Configuration Service instance: Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-SIServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Warning
8d967589-ae33-414f-a521-7f308850654b	Missing Configuration Service instance for Citrix AD Identity Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix AD Identity Service. The service instance {{serviceinstanceAddr}} does not match the instances stored in the database.	The missing service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix AD Identity Service. The service instance does not match the instances stored in the database.		Use the following command to refresh the list of addresses for the Citrix AD Identity Service: Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-AuthServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Warning
4d5d8638-59b4-4a28-b186-0c11f1c0a9f2	Missing Configuration Service instance for Citrix Analytics Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Analytics Service. The service instance {{serviceinstanceAddr}} does not match the instances stored in the database.	The missing service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Analytics Service. The service instance does not match the instances stored in the database.		Use the Reset-AnalyticsServiceGroupMembership cmdlet to refresh the list of addresses for the Configuration Service instance. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/Analytics/Reset-AnalyticsServiceGroupMembership/).	Warning
35358915-7c1c-4c08-9fca-ad76b4f236dd	Missing Configuration Service instance for Citrix App Library Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix App Library Service. The service instance {{serviceinstanceAddr}} does not match the instances stored in the database.	The missing service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix App Library Service. The service instance does not match the instances stored in the database.		Use the Reset-AppLibServiceGroupMembership cmdlet to refresh the list of addresses for the Configuration Service instance. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/AppLibrary/Reset-AppLibServiceGroupMembership/).	Warning
08c2d10-6cc2-44f1-9985-6ed276ef3443	Missing Configuration Service instance for Citrix Broker Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Broker Service. The service instance {{serviceinstanceAddr}} is missing.	The missing service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Broker Service. The service instance is missing.		Use the Reset-BrokerServiceGroupMembership cmdlet to refresh the list of addresses for the Configuration Service instance. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/Broker/Reset-BrokerServiceGroupMembership/).	Warning
532a690-c320-4ae2-ac39-6675a264d942	Missing Configuration Service instance for Citrix Configuration Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Configuration Service. The service instance {{serviceinstanceAddr}} is missing.	The missing service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Configuration Service. The service instance is missing.		Use the Reset-ConfigServiceGroupMembership cmdlet to refresh the list of addresses for the Configuration Service instance. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Reset-ConfigServiceGroupMembership/).	Error
36a9945-9706-4ae2-9a94-fb5c55557df	Missing Configuration Service instance for Citrix Configuration Logging Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Configuration Logging Service. The service instance {{serviceinstanceAddr}} is missing.	The missing service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Configuration Logging Service. The service instance is missing.		Use the Reset-LogServiceGroupMembership cmdlet to refresh the list of addresses for the Configuration Service instance. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/ConfigLogging/Reset-LogServiceGroupMembership/).	Warning
2a786c62-82ac-4fe2-8231-63bc6d2a27e7	Missing Configuration Service instance for Citrix Delegated Administration Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Delegated Administration Service. The service instance {{serviceinstanceAddr}} is missing.	The missing service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Delegated Administration Service. The service instance is missing.		Use the Reset-AdminServiceGroupMembership cmdlet to refresh the list of addresses for the Configuration Service instance. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/DelegatedAdmin/Reset-AdminServiceGroupMembership/).	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
74849b91-28e8-4792-a0d3-6ba2e5e8c09e	Missing Configuration Service instance for Citrix Environment Test Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Environment Test Service. The service instance ([serviceinstanceAddr]) is missing.	The missing service instance address is ([serviceinstanceAddr]).	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Environment Test Service. The service instance is missing.		Use the Reset-EnvTestServiceGroupMembership cmdlet to refresh the list of addresses for the Configuration Service instance. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sd/EnvTest/Reset-EnvTestServiceGroupMembership/).	Warning
79b7b088-4c1a-46c4-a6ca-92ca83e045d	Missing Configuration Service instance for Citrix Host Availability Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Host Availability Service. The service instance ([serviceinstanceAddr]) is missing.	The missing service instance address is ([serviceinstanceAddr]).	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Host Availability Service. The service instance is missing.		Use the Reset-HypServiceGroupMembership cmdlet to refresh the list of addresses for the Configuration Service instance. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sd/HostService/Reset-HypServiceGroupMembership/).	Warning
1b48b634-282b-44e9-b6ce-80123b8c43e	Missing Configuration Service instance for Citrix Machine Creation Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Machine Creation Service. The service instance ([serviceinstanceAddr]) is missing.	The missing service instance address is ([serviceinstanceAddr]).	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Machine Creation Service. The service instance is missing.		Use the Reset-ProcServiceGroupMembership cmdlet to refresh the list of addresses for the Configuration Service instance. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sd/MachineCreation/Reset-ProcServiceGroupMembership/).	Warning
fd7259-677a-4903-bccc-3f2a811298f5	Missing Configuration Service instance for Citrix Monitor Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Monitor Service. The service instance ([serviceinstanceAddr]) is missing.	The missing service instance address is ([serviceinstanceAddr]).	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Monitor Service. The service instance is missing.		Use the Reset-MonitorServiceGroupMembership cmdlet to refresh the list of addresses for the Configuration Service instance. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sd/Monitor/Reset-MonitorServiceGroupMembership/).	Warning
a8688929-1809-4461-bf0c-2a35960841a	Missing Configuration Service instance for Citrix Storefront Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Storefront Service. The service instance ([serviceinstanceAddr]) is missing.	The missing service instance address is ([serviceinstanceAddr]).	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Storefront Service. The service instance is missing.		Use the Reset-SFServiceGroupMembership cmdlet to refresh the list of addresses for the Configuration Service instance. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sd/StorefrontService/Reset-SFServiceGroupMembership/).	Warning
0b61eec1-e427-4585-8326-28f25a5e1ce	Extra registered service instance for Citrix AD Identity Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix AD Identity Service. An extra service instance ([serviceinstanceAddr]), was found.	The extra service instance address is ([serviceinstanceAddr]).	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix AD Identity Service. An extra service instance was found.		Run the following cmdlets to register with the Central Configuration service: Get-AcctServiceInstance Unregister-ConfigRegisteredServiceInstance Get-AcctServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-AcctServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sd/).	Warning
0b09a3cd-6b15-42ff-b16a-873b1704ce60	Extra registered service instance for Citrix Analytics Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Analytics Service. An extra service instance ([serviceinstanceAddr]), was found.	The extra service instance address is ([serviceinstanceAddr]).	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Analytics Service. An extra service instance was found.		Run the following cmdlets to register with the Central Configuration service: Get-AnalyticsServiceInstance Unregister-ConfigRegisteredServiceInstance Get-AnalyticsServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-AnalyticsServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sd/).	Warning
0e90ea7d-cefb-4b45-a463-614514008a3c	Extra registered service instance for Citrix AppLibrary Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix App Library Service. An extra service instance ([serviceinstanceAddr]), was found.	The extra service instance address is ([serviceinstanceAddr]).	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix App Library Service. An extra service instance was found.		Run the following cmdlets to register with the Central Configuration service: Get-AppLibServiceInstance Unregister-ConfigRegisteredServiceInstance Get-AppLibServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-AppLibServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sd/).	Warning
c980a6b9-623b-44d6-992c-4a191a70452	Extra registered service instance for Citrix Broker Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Broker Service. An extra service instance ([serviceinstanceAddr]), was found.	The extra service instance address is ([serviceinstanceAddr]).	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Broker Service. An extra service instance was found.		Run the following cmdlets to register with the Central Configuration service: Get-BrokerServiceInstance Unregister-ConfigRegisteredServiceInstance Get-BrokerServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-BrokerServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sd/).	Warning
a4328776-5e93-437a-9a5e-1bab370c1bd6	Extra registered service instance for Citrix Configuration Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Configuration Service. An extra service instance ([serviceinstanceAddr]), was found.	The extra service instance address is ([serviceinstanceAddr]).	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Configuration Service. An extra service instance was found.		Run the following cmdlets to register with the Central Configuration service: Get-ConfigServiceInstance Unregister-ConfigRegisteredServiceInstance Get-ConfigServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-ConfigServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sd/).	Error
2dd0c976-b6f3-430d-8289-cb6695ff6fb	Extra registered service instance for Citrix Configuration Logging Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Configuration Logging Service. An extra service instance ([serviceinstanceAddr]), was found.	The extra service instance address is ([serviceinstanceAddr]).	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Configuration Logging Service. An extra service instance was found.		Run the following cmdlets to register with the Central Configuration service: Get-LogServiceInstance Unregister-ConfigRegisteredServiceInstance Get-LogServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-LogServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sd/).	Warning
a1c5b4cd-6307-4e11-b25b-da21741e5d2d	Extra registered service instance for Citrix Delegated Administration Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Delegated Administration Service. An extra service instance ([serviceinstanceAddr]), was found.	The extra service instance address is ([serviceinstanceAddr]).	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Delegated Administration Service. An extra service instance was found.		Run the following cmdlets to register with the Central Configuration service: Get-AdminServiceInstance Unregister-ConfigRegisteredServiceInstance Get-AdminServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-AdminServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sd/).	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
f5fa13b0-1bb1-42c3-941a-6e1898388013	Extra registered service instance for Citrix Environment Test Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Environment Test Service. An extra service instance, {{serviceinstanceAddr}}, was found.	The extra service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Environment Test Service. An extra service instance was found.		Run the following cmdlets to register with the Central Configuration service: Get-EnvTestServiceInstance Unregister-ConfigRegisteredServiceInstance Get-EnvTestServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-EnvTestServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Warning
311ea1de-d9c7-4c8d-8336-d70062317da	Extra registered service instance for Citrix Host Availability Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Host Availability Service. An extra service instance, {{serviceinstanceAddr}}, was found.	The extra service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Host Availability Service. An extra service instance was found.		Run the following cmdlets to register with the Central Configuration service: Get-HypServiceInstance Unregister-ConfigRegisteredServiceInstance Get-HypServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-HypServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Warning
4b6c1c77-e2af-4278-9e9f-f6ed8b0b6bd	Extra registered service instance for Citrix Machine Creation Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Machine Creation Service. An extra service instance, {{serviceinstanceAddr}}, was found.	The extra service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Machine Creation Service. An extra service instance was found.		Run the following cmdlets to register with the Central Configuration service: Get-ProdServiceInstance Unregister-ConfigRegisteredServiceInstance Get-ProdServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-ProdServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Warning
ee67548e-2553-430f-812e-0a713a8f543f	Extra registered service instance for Citrix Monitor Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Monitor Service. An extra service instance, {{serviceinstanceAddr}}, was found.	The extra service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Monitor Service. An extra service instance was found.		Run the following cmdlets to register with the Central Configuration service: Get-MonitorServiceInstance Unregister-ConfigRegisteredServiceInstance Get-MonitorServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-MonitorServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Warning
4d88e158-f07f-444d-9ba1-2497f6173387	Extra registered service instance for Citrix Storefront Service	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Storefront Service. An extra service instance, {{serviceinstanceAddr}}, was found.	The extra service instance address is {{serviceinstanceAddr}}.	The list of addresses where the Configuration Service can be reached is not up to date for the Citrix Storefront Service. An extra service instance was found.		Run the following cmdlets to register with the Central Configuration service: Get-SSServiceInstance Unregister-ConfigRegisteredServiceInstance Get-SSServiceInstance Register-ConfigServiceInstance Get-ConfigRegisteredServiceInstance -ServiceType Config Reset-SSServiceGroupMembership For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Warning
dc5c7bd-d270-433a-8925-39f89e6f6c6c	Citrix AD Identity Service failed to connect to Citrix Configuration Logging Service	The Citrix AD Identity Service failed to connect to the Citrix Configuration Logging Service. The AD Identity Service handles all computer accounts (identities) related to XenApp and XenDesktop physical and virtual machines. The Configuration Logging Service monitors and logs all configuration changes made within a Site, including all administrator activity, depending on its configuration, no site changes are possible when its database is unreachable.		The Citrix AD Identity Service failed to connect to the Citrix Configuration Logging Service.	[Bas Van Kaam](http://www.basvankaam.com), Citrix Technology Professional	Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Logging Service. To resolve this issue, perform the following actions: 1. Verify the Delivery Controller is powered on and connected to the internet. 2. Restart the Citrix Configuration Logging Service: Click "Start", type "services.msc", and then press "ENTER". From the Services console, select "Citrix Configuration Logging Service", and then click "Restart". 3. Restart the Citrix AD Identity Service: Click "Start", type "services.msc", and then press "ENTER". From the Services console, select "Citrix AD Identity Service", and then click "Restart".	Error
1216a60b-7f38-4298-926b-1bdbe3b8b957	Citrix Analytics Service failed to connect to Citrix Configuration Logging Service	The Citrix Analytics Service failed to connect to the Citrix Configuration Logging Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Analytics Service failed to connect to the Citrix Configuration Logging Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Logging Service.	Error
8ad147d1-15a2-49a7-bb1b-1fec152e4607	Citrix App Library Service failed to connect to Citrix Configuration Logging Service	The Citrix App Library Service failed to connect to the Citrix Configuration Logging Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix App Library Service failed to connect to the Citrix Configuration Logging Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Logging Service.	Error
eb3bc94-649f-4db9-a908-339151a062c5	Citrix Configuration Service failed to connect to Citrix Configuration Logging Service	The Citrix Configuration Service failed to connect to the Citrix Configuration Logging Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Configuration Service failed to connect to the Citrix Configuration Logging Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Logging Service.	Error
6d0a5a4-14c4-4c6d-a1fb-cd6e44727bb	Citrix Delegated Administration Service failed to connect to Citrix Configuration Logging Service	The Citrix Delegated Administrator Service failed to connect to the Citrix Configuration Logging Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Delegated Administrator Service failed to connect to the Citrix Configuration Logging Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Logging Service.	Error
4a02a836-0314-4955-a2cf-d11b98f412d6	Citrix Environment Test Service failed to connect to Citrix Configuration Logging Service	The Citrix Environment Test Service failed to connect to the Citrix Configuration Logging Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Environment Test Service failed to connect to the Citrix Configuration Logging Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Logging Service.	Error
89d686d5-7f6a-4dc4-a2a9-a550af9c5af4	Citrix Host Availability Service failed to connect to Citrix Configuration Logging Service	The Citrix Host Service failed to connect to the Citrix Configuration Logging Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Host Service failed to connect to the Citrix Configuration Logging Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Logging Service.	Error

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
e6a6913-1b26-4089-bc10-5641bbec8385	Citrix Machine Creation Service failed to connect to Citrix Configuration Logging Service	The Citrix Machine Creation Service failed to connect to the Citrix Configuration Logging Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Machine Creation Service failed to connect to the Citrix Configuration Logging Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Logging Service.	Error
5645e83-404b-4b2e-bb42-1ae2ad470b5	Citrix Monitor Service failed to connect to Citrix Configuration Logging Service	The Citrix Monitor Service failed to connect to the Citrix Configuration Logging Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Monitor Service failed to connect to the Citrix Configuration Logging Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Logging Service.	Error
41da72d-e904-4455-ad9-321fe4ee36e3	Citrix Storefront Service failed to connect to Citrix Configuration Logging Service	The Citrix Storefront Service failed to connect to the Citrix Configuration Logging Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Storefront Service failed to connect to the Citrix Configuration Logging Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Logging Service.	Error
8087efc-8e9f-4525-8c8a-51796d3f553	Citrix AD Identity Service failed to connect to Citrix Configuration Service	The Citrix AD Identity Service failed to connect to the Citrix Configuration Service. The AD Identity Service handles all computer accounts (identities) related to XenApp and XenDesktop physical and virtual machines. The Configuration Service handles all inter-service communication within the FlexCast Management Architecture (FMA). All FMA services are located at the center of the FlexCast Management Architecture.		The Citrix AD Identity Service failed to connect to the Citrix Configuration Service. The AD Identity Service handles all computer accounts (identities) related to XenApp and XenDesktop physical and virtual machines. The Configuration Service handles all inter-service communication within the FlexCast Management Architecture (FMA). All FMA services need to register with the Configuration Service on start-up so that it knows they are all good to go. Located at the center of the FlexCast Management Architecture.	[Bas Van Kaam](http://www.basvankaam.com), Citrix Technology Professional	Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Service. To resolve this issue, perform the following actions: 1. Verify the Delivery Controller is powered on and connected to the Internet. 2. Restart the Citrix Configuration Service: Click "Start", type "services.msc", and then press "ENTER". From the Services console, select "Citrix Configuration Service", and then click "Restart". 3. Restart the Citrix AD Identity Service: Click "Start", type "services.msc", and then press "ENTER". From the Services console, select "Citrix AD Identity Service", and then click "Restart".	Error
ea4d5115-d1d2-4a24-b888-188ed0a5544	Citrix Analytics Service failed to connect to Citrix Configuration Service	The Citrix Analytics Service failed to connect to the Citrix Configuration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Analytics Service failed to connect to the Citrix Configuration Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Service.	Error
82715b5e-24ce-418a-9c5a-2e2aa5f5c30	Citrix App Library Service failed to connect to Citrix Configuration Service	The Citrix App Library Service failed to connect to Citrix Configuration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix App Library Service failed to connect to Citrix Configuration Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Service.	Error
077687b7-28b4-4647-bf17-8a5a80823d39	Citrix Configuration Logging Service failed to connect to Citrix Configuration Service	The Citrix Configuration Logging Service failed to connect to the Citrix Configuration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Configuration Logging Service failed to connect to the Citrix Configuration Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Service.	Error
b67d1213-a6cf-447d-843b-97b66274ef44	Citrix Delegated Administration Service failed to connect to Citrix Configuration Service	The Citrix Delegated Administration Service failed to connect to the Configuration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Delegated Administration Service failed to connect to the Configuration Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Service.	Error
79147610-c21d-4440-9f00-d711bc6e27bb	Citrix Environment Test Service failed to connect to Citrix Configuration Service	The Citrix Environment Test Service failed to connect to the Citrix Configuration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Environment Test Service failed to connect to the Citrix Configuration Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Service.	Error
c8b2b38-226d-4b41-8b2f-d26c4d3d3b76	Citrix Host Availability Service failed to connect to Citrix Configuration Service	The Citrix Host Service failed to connect to the Citrix Configuration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Host Service failed to connect to the Citrix Configuration Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Service.	Error
8051abea-e53b-44ae-82b0-81a4439657b6	Citrix Machine Creation Service failed to connect to Citrix Configuration Service	The Citrix Machine Creation Service failed to connect to the Citrix Configuration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Machine Creation Service failed to connect to the Citrix Configuration Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Service.	Error
73746a4e-9813-427e-9dc6-c7be897499e	Citrix Monitor Service failed to connect to Citrix Configuration Service	The Citrix Monitor Service failed to connect to the Citrix Configuration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Monitor Service failed to connect to the Citrix Configuration Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Service.	Error

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
c226c358-da29-48df-b11b-6951e757e3c	Citrix Storefront Service failed to connect to Citrix Configuration Service	The Citrix Storefront Service failed to connect to the Citrix Configuration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Storefront Service failed to connect to the Citrix Configuration Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Configuration Service.	Error
49d98276-f009-41a8-8827-fdc38f694a4d	Citrix AD Identity Service failed to connect to Citrix Delegated Administration Service	The Citrix AD Identity Service failed to connect to the Citrix Delegated Administration Service. This alert could appear if: * The Citrix Delegated Administration Service is not running. * There is a problem with the registered endpoints list. This issue could occur if the Site was not created successfully or if an upgrade was not completed successfully.		The Citrix AD Identity Service failed to connect to the Citrix Delegated Administration Service. This alert could appear if: * The Citrix Delegated Administration Service is not running. * There is a problem with the registered endpoints list. This issue could occur if the Site was not created successfully or if an upgrade was not completed successfully. Possible impact: * Citrix administrators might not be able to run Studio to administer the Site.	[Bas Van Kaam](http://www.basvankaam.com), Citrix Technology Professional	Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Delegated Administration service. To resolve this issue, perform the following actions: 1. Verify the Delivery Controller is powered on and connected to the Internet. 2. Restart the Citrix Delegated Administration Service: Click "Start", type "services.msc", and then press "ENTER". From the Services console, select "Citrix Configuration Logging Service", and then click "Restart". 3. Restart the Citrix AD Identity Service: Click "Start", type "services.msc", and then press "ENTER". From the Services console, select "Citrix AD Identity Service", and then click "Restart".	Error
399b414-bf78-40f966d-0914863784b	Citrix Analytics Service failed to connect to Citrix Delegated Administration Service	The Citrix Analytics Service failed to connect to the Citrix Delegated Administration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Analytics Service failed to connect to the Citrix Delegated Administration Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Delegated Administration service.	Error
05001ba-0376-4aab-ab25-2969068cad9	Citrix App Library Service failed to connect to Citrix Delegated Administration Service	The Citrix App Library Service failed to connect to the Citrix Delegated Administration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix App Library Service failed to connect to the Citrix Delegated Administration Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Delegated Administration service.	Error
05621eeb-3a06-4796-a1a8-851f2832ab15	Citrix Configuration Service failed to connect to Citrix Delegated Administration Service	The Citrix Configuration Service failed to connect to the Citrix Delegated Administration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Configuration Service failed to connect to the Citrix Delegated Administration Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Delegated Administration service.	Error
53787ad-b3d4-4a60-bf0a-009f3d20525	Citrix Configuration Logging Administration Service failed to connect to Citrix Delegated Administration Service	The Citrix Configuration Logging Service failed to connect to the Citrix Delegated Administration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Configuration Logging Service failed to connect to the Citrix Delegated Administration Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Delegated Administration service.	Error
b647bb3-26b2-4f2d-9314-ceae3835044d	Citrix Environment Test Service failed to connect to Citrix Delegated Administration Service	The Citrix Environment Test Service failed to connect to the Citrix Delegated Administration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Environment Test Service failed to connect to the Citrix Delegated Administration Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Delegated Administration service.	Error
79f5a46a-1e5d-46e7-8d9f-3c3b466ef355	Citrix Host Availability Service failed to connect to Citrix Delegated Administration Service	The Citrix Host Service failed to connect to the Citrix Delegated Administration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Host Service failed to connect to the Citrix Delegated Administration Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Delegated Administration service.	Error
fbb13b59-6fd8-45d0-a0ae-547e902eba9	Citrix Machine Creation Service failed to connect to Citrix Delegated Administration Service	The Citrix Machine Creation Service failed to connect to the Citrix Delegated Administration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Machine Creation Service failed to connect to the Citrix Delegated Administration Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Delegated Administration service.	Error
54d92769-cae0-4cd0-94eb-a16c42f80cc	Citrix Monitor Service failed to connect to Citrix Delegated Administration Service	The Citrix Monitor Service failed to connect to the Citrix Delegated Administration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Monitor Service failed to connect to the Citrix Delegated Administration Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Delegated Administration service.	Error
14df5ded-c158-4069-aff1-075ab3b19032	Citrix Storefront Service failed to connect to Citrix Delegated Administration Service	The Citrix Storefront Service failed to connect to the Citrix Delegated Administration Service. For more information about XenDesktop services, see [CTX139415](http://support.citrix.com/article/CTX139415).		The Citrix Storefront Service failed to connect to the Citrix Delegated Administration Service.		Verify that the controller is turned on and network connectivity between controllers in the Site is available. Restart the Citrix Delegated Administration service.	Error
0587602b-6a76-4f12-8c13-344bc0801b07	Mismatched registered service instance for Citrix AD Identity Service	The service instance ([{serviceNameAddr}], includes the property [{mismatchedProperty}] with the value [{currentVal}]. This property does not match the service instance registered with the Configuration Service. The value of this property should be [{expectedVal}].	The mismatched service instance address is [{serviceNameAddr}]. The mismatched property is [{mismatchedProperty}]. The current value is [{currentVal}], the expected value is [{expectedVal}].	A service instance published by the Citrix AD Identity Service includes a property that does not match the service instance registered with the Configuration Service.		Use the Register-ConfigServiceInstance cmdlet to re-register all service instances published by the Citrix AD Identity Service with the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/Citrix/Config/Register-ConfigServiceInstance/).	Error

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
1423827-dee4-48b-880f-5b7be29029c	Unregistered service instance for Citrix Analytics Service	The service instance [{{serviceinstanceAddr}}], published by the Citrix Analytics Service, is not registered with the Configuration Service.	The missing service instance address is [{{serviceinstanceAddr}}].	A service instance published by the Citrix Analytics Service is not registered with the Configuration Service.		Use the Register-ConfigServiceInstance cmdlet to register all service instances published by the Citrix Analytics Service with the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Register-ConfigServiceInstance/).	Error
aa5925e4-e388-4487-954e-526f74b7725	Unregistered service instance for Citrix App Library Service	The service instance [{{serviceinstanceAddr}}], published by the Citrix App Library Service, is not registered with the Configuration Service.	The missing service instance address is [{{serviceinstanceAddr}}].	A service instance published by the Citrix App Library Service is not registered with the Configuration Service.		Use the Register-ConfigServiceInstance cmdlet to register all service instances published by the Citrix App Library Service with the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Register-ConfigServiceInstance/).	Error
ee665a62-1a2f4-6c6-8844-4643a0ca39ec	Unregistered service instance for Citrix Broker Service	The service instance [{{serviceinstanceAddr}}], published by the Citrix Broker Service, is not registered with the Configuration Service.	The missing service instance address is [{{serviceinstanceAddr}}].	A service instance published by the Citrix Broker Service is not registered with the Configuration Service.		Use the Register-ConfigServiceInstance cmdlet to register all service instances published by the Citrix Broker Service with the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Register-ConfigServiceInstance/).	Error
1a0d0f6f-692e-4111-ae08-168fa2ab1ad	Unregistered service instance for Citrix Configuration Service	The service instance [{{serviceinstanceAddr}}], published by the Citrix Configuration Service, is not registered with the Configuration Service.	The missing service instance address is [{{serviceinstanceAddr}}].	A service instance published by the Citrix Configuration Service is not registered with the Configuration Service.		Use the Register-ConfigServiceInstance cmdlet to register all service instances published by the Citrix Configuration Service with the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Register-ConfigServiceInstance/).	Error
a3cd61f0-3265-466-80a3-93d051116333	Unregistered service instance for Citrix Configuration Logging Service	The service instance [{{serviceinstanceAddr}}], published by the Citrix Configuration Logging Service, is not registered with the Configuration Service.	The missing service instance address is [{{serviceinstanceAddr}}].	A service instance published by the Citrix Configuration Logging Service is not registered with the Configuration Service.		Use the Register-ConfigServiceInstance cmdlet to register all service instances published by the Citrix Configuration Logging Service with the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Register-ConfigServiceInstance/).	Error
932c97e1-7e74-4449-89db-959f6d9d04f	Unregistered service instance for Citrix Delegated Administration Service	The service instance [{{serviceinstanceAddr}}], published by the Citrix Delegated Administration Service, is not registered with the Configuration Service.	The missing service instance address is [{{serviceinstanceAddr}}].	A service instance published by the Citrix Delegated Administration Service is not registered with the Configuration Service.		Use the Register-ConfigServiceInstance cmdlet to register all service instances published by the Citrix Delegated Administration Service with the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Register-ConfigServiceInstance/).	Error
f7c72884-ce73-46be-8156-812a0bb8e9f	Unregistered service instance for Citrix Environment Test Service	The service instance [{{serviceinstanceAddr}}], published by the Citrix Environment Test Service, is not registered with the Configuration Service.	The missing service instance address is [{{serviceinstanceAddr}}].	A service instance published by the Citrix Environment Test Service is not registered with the Configuration Service.		Use the Register-ConfigServiceInstance cmdlet to register all service instances published by the Citrix Environment Test Service with the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Register-ConfigServiceInstance/).	Error
0ab6668a-bb9f-4371-955a-f7ccac4beab	Unregistered service instance for Citrix Host Availability Service	The service instance [{{serviceinstanceAddr}}], published by the Citrix Host Availability Service, is not registered with the Configuration Service.	The missing service instance address is [{{serviceinstanceAddr}}].	A service instance published by the Citrix Host Availability Service is not registered with the Configuration Service.		Use the Register-ConfigServiceInstance cmdlet to register all service instances published by the Citrix Host Availability Service with the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Register-ConfigServiceInstance/).	Error
54837ff5-e67b-491b-8d91-c3aeed02e500	Unregistered service instance for Citrix Machine Creation Service	The service instance [{{serviceinstanceAddr}}], published by the Citrix Machine Creation Service, is not registered with the Configuration Service.	The missing service instance address is [{{serviceinstanceAddr}}].	A service instance published by the Citrix Machine Creation Service is not registered with the Configuration Service.		Use the Register-ConfigServiceInstance cmdlet to register all service instances published by the Citrix Machine Creation Service with the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Register-ConfigServiceInstance/).	Error
8882c557-c37-4335-bb26-20c56974c22	Unregistered service instance for Citrix Monitor Service	The service instance [{{serviceinstanceAddr}}], published by the Citrix Monitor Service, is not registered with the Configuration Service.	The missing service instance address is [{{serviceinstanceAddr}}].	A service instance published by the Citrix Monitor Service is not registered with the Configuration Service.		Use the Register-ConfigServiceInstance cmdlet to register all service instances published by the Citrix Monitor Service with the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Register-ConfigServiceInstance/).	Error
6a48f180-2300-4834-b494-c822a269804	Unregistered service instance for Citrix Storefront Service	The service instance [{{serviceinstanceAddr}}], published by the Citrix Storefront Service, is not registered with the Configuration Service.	The missing service instance address is [{{serviceinstanceAddr}}].	A service instance published by the Citrix Storefront Service is not registered with the Configuration Service.		Use the Register-ConfigServiceInstance cmdlet to register all service instances published by the Citrix Storefront Service with the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Register-ConfigServiceInstance/).	Error
a8836a8-0c77-4ef4-afad-b4620b17e03b	Extra registered service instance for Citrix AD Identity Service	A service instance for the Citrix AD Identity Service, [{{serviceinstanceAddr}}], has registered unexpectedly with the Configuration Service.	The extra service instance address is [{{serviceinstanceAddr}}].	A service instance for the Citrix AD Identity Service has registered unexpectedly with the Configuration Service.		Use the Unregister-ConfigRegisteredServiceInstance cmdlet to unregister the unexpected service instance from the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Unregister-ConfigRegisteredServiceInstance/).	Error

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
71d8ac9-99bd-4596-a4d2-af16030695d	Extra registered service instance for Citrix Analytics Service	A service instance for the Citrix Analytics Service, {{serviceinstanceAddr}}, has registered unexpectedly with the Configuration Service.	The extra service instance address is {{serviceinstanceAddr}}.	A service instance for the Citrix Analytics Service has registered unexpectedly with the Configuration Service.		Use the Unregister-ConfigRegisteredServiceInstance cmdlet to unregister the unexpected service instance from the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Unregister-ConfigRegisteredServiceInstance/).	Error
479b7be5-78c3-4eb5-b00c-5762e89312c8	Extra registered service instance for Citrix App Library Service	A service instance for the Citrix App Library Service, {{serviceinstanceAddr}}, has registered unexpectedly with the Configuration Service.	The extra service instance address is {{serviceinstanceAddr}}.	A service instance for the Citrix App Library Service has registered unexpectedly with the Configuration Service.		Use the Unregister-ConfigRegisteredServiceInstance cmdlet to unregister the unexpected service instance from the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Unregister-ConfigRegisteredServiceInstance/).	Error
a6996d96-44b1-41b4-a412-0dc29975892a	Extra registered service instance for Citrix Broker Service	A service instance for the Citrix Broker Service, {{serviceinstanceAddr}}, has registered unexpectedly with the Configuration Service.	The extra service instance address is {{serviceinstanceAddr}}.	A service instance for the Citrix Broker Service has registered unexpectedly with the Configuration Service.		Use the Unregister-ConfigRegisteredServiceInstance cmdlet to unregister the unexpected service instance from the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Unregister-ConfigRegisteredServiceInstance/).	Error
81269bdc-1f8c-4f09-b467-160bcca482b	Extra registered service instance for Citrix Configuration Service	A service instance for the Citrix Configuration Service, {{serviceinstanceAddr}}, has registered unexpectedly with the Configuration Service.	The extra service instance address is {{serviceinstanceAddr}}.	A service instance for the Citrix Configuration Service has registered unexpectedly with the Configuration Service.		Use the Unregister-ConfigRegisteredServiceInstance cmdlet to unregister the unexpected service instance from the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Unregister-ConfigRegisteredServiceInstance/).	Error
527e5f0-7302-4bbc-bb19-93c0d3c3316	Extra registered service instance for Citrix Configuration Logging Service	A service instance for the Citrix Configuration Logging Service has registered, {{serviceinstanceAddr}}, unexpectedly with the Configuration Service.	The extra service instance address is {{serviceinstanceAddr}}.	A service instance for the Citrix Configuration Logging Service has registered unexpectedly with the Configuration Service.		Use the Unregister-ConfigRegisteredServiceInstance cmdlet to unregister the unexpected service instance from the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Unregister-ConfigRegisteredServiceInstance/).	Error
2e63a14b-4105-428c-be2e-b87626561913	Extra registered service instance for Citrix Delegated Administration Service	A service instance for the Citrix Delegated Administration Service, {{serviceinstanceAddr}}, has registered unexpectedly with the Configuration Service.	The extra service instance address is {{serviceinstanceAddr}}.	A service instance for the Citrix Delegated Administration Service has registered unexpectedly with the Configuration Service.		Use the Unregister-ConfigRegisteredServiceInstance cmdlet to unregister the unexpected service instance from the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Unregister-ConfigRegisteredServiceInstance/).	Error
251513ba-251a-432d-a504-c05c0ad32435	Extra registered service instance for Citrix Environment Test Service	A service instance for the Citrix Environment Test Service, {{serviceinstanceAddr}}, has registered unexpectedly with the Configuration Service.	The extra service instance address is {{serviceinstanceAddr}}.	A service instance for the Citrix Environment Test Service has registered unexpectedly with the Configuration Service.		Use the Unregister-ConfigRegisteredServiceInstance cmdlet to unregister the unexpected service instance from the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Unregister-ConfigRegisteredServiceInstance/).	Error
0db0a1b2-c30a-476c-8160-09c2830c11c1	Extra registered service instance for Citrix Host Availability Service	A service instance for the Citrix Host Availability Service, {{serviceinstanceAddr}}, has registered unexpectedly with the Configuration Service.	The extra service instance address is {{serviceinstanceAddr}}.	A service instance for the Citrix Host Availability Service has registered unexpectedly with the Configuration Service.		Use the Unregister-ConfigRegisteredServiceInstance cmdlet to unregister the unexpected service instance from the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Unregister-ConfigRegisteredServiceInstance/).	Error
dbba075-526f-419a-997f-6555907627ae	Extra registered service instance for Citrix Machine Creation Service	A service instance for the Citrix Machine Creation Service, {{serviceinstanceAddr}}, has registered unexpectedly with the Configuration Service.	The extra service instance address is {{serviceinstanceAddr}}.	A service instance for the Citrix Machine Creation Service has registered unexpectedly with the Configuration Service.		Use the Unregister-ConfigRegisteredServiceInstance cmdlet to unregister the unexpected service instance from the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Unregister-ConfigRegisteredServiceInstance/).	Error
93f9063f-51d1-4452-b834-4b7ac6c3864b	Extra registered service instance for Citrix Monitor Service	A service instance for the Citrix Monitor Service, {{serviceinstanceAddr}}, has registered unexpectedly with the Configuration Service.	The extra service instance address is {{serviceinstanceAddr}}.	A service instance for the Citrix Monitor Service has registered unexpectedly with the Configuration Service.		Use the Unregister-ConfigRegisteredServiceInstance cmdlet to unregister the unexpected service instance from the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Unregister-ConfigRegisteredServiceInstance/).	Error
b2acc71-575d-4da4-9a61-9f9918b38727	Extra registered service instance for Citrix Storefront Service	A service instance for the Citrix Storefront Service, {{serviceinstanceAddr}}, has registered unexpectedly with the Configuration Service.	The extra service instance address is {{serviceinstanceAddr}}.	A service instance for the Citrix Storefront Service has registered unexpectedly with the Configuration Service.		Use the Unregister-ConfigRegisteredServiceInstance cmdlet to unregister the unexpected service instance from the Configuration Service. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/CentralConfig/Unregister-ConfigRegisteredServiceInstance/).	Error
21c180d-550f-4592-899d-d45034af0397	Identify not in AD for Citrix AD Identity Service	The Citrix AD Identity Service could not find the nominated account ({{ADAccountSid}}) in Active Directory. The account could be inaccessible or missing. This issue affects all Delivery Controllers in the Site.	The nominated account is {{ADAccountSid}}.	The Citrix AD Identity Service could not find a nominated account in Active Directory. The account could be inaccessible or missing. This issue affects all Delivery Controllers in the Site.		Verify that the account exists in Active Directory but is inaccessible for some reason. If necessary, create the account manually.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
aK39a6e-3d8d-42f3-b28c-982bd8e53c64	Identity tainted for Citrix AD Identity Service	The account <code>{{ADAccountName}}</code> with the SID <code>{{ADAccountSid}}</code> is known to the Citrix AD Identity Service and has been in use with an existing VM, but that VM has been deleted.	The account name is <code>{{ADAccountName}}</code> ; The account SID is <code>{{ADAccountSid}}</code> .	An Active Directory account is known to the Citrix AD Identity Service and has been in use with an existing VM, but that VM has been deleted.		Use the <code>Repair-AcctADAccount</code> cmdlet to recycle the account. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/ADIdentity/Repair-AcctADAccount/).	Warning
80e62690-7831-40ae-a565-a3c570cc45	Identity in use for Citrix AD Identity Service	The account <code>{{ADAccountName}}</code> with the SID <code>{{ADAccountSid}}</code> is known to the Citrix AD Identity Service, but is marked as being associated with an existing VM.	The account name is <code>{{ADAccountName}}</code> ; The account SID is <code>{{ADAccountSid}}</code> .	An Active Directory account is known to the Citrix AD Identity Service, but is marked as being associated with an existing VM.		The account has been used already to provision a VM and is not free for use.	Warning
887ed70d-cbc4-4c73-b4f3-43680de2e08	Identity error for Citrix AD Identity Service	The account <code>{{ADAccountName}}</code> with the SID <code>{{ADAccountSid}}</code> is known to the Citrix AD Identity Service, but is not in a usable state.	The account name is <code>{{ADAccountName}}</code> ; The account SID is <code>{{ADAccountSid}}</code> .	An Active Directory account is known to the Citrix AD Identity Service, but is not in a usable state.		Check Active Directory for details of this account. Use the <code>Repair-AcctADAccount</code> cmdlet to attempt to resolve this state. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/ADIdentity/Repair-AcctADAccount/).	Warning
2429ee7f-9050-445d-8234-81b127daa294	Invalid OU for Citrix AD Identity Service	The organizational unit (OU) in the domain <code>{{domain}}</code> , which is specified in the identity pool <code>{{identityPoolName}}</code> , was not found in Active Directory. Currently, this identity pool is suitable only for importing identities. This issue affects all Delivery Controllers in the Site.	The OU is <code>{{OU}}</code> ; The domain is <code>{{domain}}</code> ; The identity pool is <code>{{identityPoolName}}</code> .	An Active Directory organizational unit in the domain was not found in Active Directory. Currently, this identity pool is suitable only for importing identities. This issue affects all Delivery Controllers in the Site.		Before creating identities in this pool, specify an OU that exists in Active Directory to replace the current value.	Warning
8e921b8-2cdd-4863-b2ec-7c1413593faa	Identity pool locked for Citrix AD Identity Service	The identity pool being tested by the Citrix AD Identity Service is locked by another operation. This issue affects all Delivery Controllers in the Site.		The identity pool being tested by the Citrix AD Identity Service is locked by another operation. This issue affects all Delivery Controllers in the Site.		Wait for the current operation on the identity pool to finish (<code>Add-AcctADAccount</code> , <code>New-AcctADAccount</code> , <code>Remove-AcctADAccount</code>). If there is no operation in progress, unlock the identity pool using the <code>Unlock-AcctIdentityPool</code> cmdlet. For more information about these cmdlets, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/).	Warning
488516a7-1974-4288-bcf5-5b9d4cc40437	Naming scheme failed for Citrix AD Identity Service	There is no valid next account name for the naming scheme on the identity pool <code>{{identityPoolName}}</code> .	The identity pool is <code>{{identityPoolName}}</code> .	There is no valid next account name for the naming scheme on the identity pool.		Use the <code>Set-AcctIdentityPool</code> cmdlet to change the pool naming scheme. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/ADIdentity/Set-AcctIdentityPool/).	Warning
e8501b56-e2c3-4ef5-bbcc-e606808212c2	Next name exists for Citrix AD Identity Service	The next name <code>{{name}}</code> is already present in the database for the identity pool <code>{{identityPoolName}}</code> .	The next name is <code>{{name}}</code> ; The identity pool is <code>{{identityPoolName}}</code> .	The next name is already present in the database for the identity pool.		Use the <code>New-AcctADAccount</code> cmdlet to increase the pool start count and skip the pre-existing account name. For example: <code>New-AcctADAccount -identityPoolName <String> -Count <int32> -StartCount <int32></code> For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/ADIdentity/New-AcctADAccount/).	Warning
aKc93c1-f118-4e0c-e61a-98bd476da5ae	AD failed for Citrix AD Identity Service	The domain <code>{{domain}}</code> specified by the identity pool <code>{{identityPoolName}}</code> cannot be found.	The domain is <code>{{domain}}</code> ; The identity pool is <code>{{identityPoolName}}</code> .	The domain specified by the identity pool cannot be found.		Ensure the identity pool is associated with a valid and contactable domain.	Warning
c9bc77c2-410d-4545-887e-a361a32001a3	Next name in use for Citrix AD Identity Service	The next account name <code>{{accountName}}</code> , which would be generated from the <code>{{identityPoolName}}</code> pool naming scheme, is present in Active Directory.	The next account name is <code>{{accountName}}</code> ; The identity pool is <code>{{identityPoolName}}</code> .	The next account name which would be generated from the pool naming scheme, is present in Active Directory.		Use the <code>New-AcctADAccount</code> cmdlet to increase the pool start count and skip the pre-existing account name. For example: <code>New-AcctADAccount -identityPoolName <String> -Count <int32> -StartCount <int32></code> For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/ADIdentity/New-AcctADAccount/).	Warning
1eeaf2e3-3353-4293-9a2e-b904e5974862	Null object for Citrix AD Identity Service test	No object was specified for the Citrix AD Identity Service test. This issue affects all Delivery Controllers in the Site.		No object was specified for the Citrix AD Identity Service test. This issue affects all Delivery Controllers in the Site.		Specify an object for the test.	Warning
959b1d51-e10b-403b-bd0c-738e742b3d52	Incorrect object identifier for the Citrix AD Identity Service test	The object identifier <code>{{objectId}}</code> is incorrect for the <code>{{objectType}}</code> object type. This issue affects all Delivery Controllers in the Site.	The object type is <code>{{objectType}}</code> ; The object ID is <code>{{objectId}}</code> .	The object identifier is incorrect for the object type. This issue affects all Delivery Controllers in the Site.		Specify identity pool objects by GUID or account objects by SID (as a string in SDDL format).	Warning
f1f09b6b-57b7-4d61-9598-12138f2175e3	Incorrect database version for Citrix AD Identity Service	The current Site database version <code>{{dbCurrentVersion}}</code> is older than the database <code>{{dbName}}</code> on the server <code>{{dbServer}}</code> is too old for the Citrix AD Identity Service. The database version should be <code>{{dbExpectedVersion}}</code> . This issue affects all Delivery Controllers in the Site.	Expected database version is <code>{{dbExpectedVersion}}</code> ; Current database version is <code>{{dbCurrentVersion}}</code> ; Database Name is <code>{{dbName}}</code> ; Server Name is <code>{{dbServer}}</code> .	The current Site database version is too old for the Citrix AD Identity Service. This issue affects all Delivery Controllers in the Site.		Run Citrix Studio to upgrade the site database to the expected version.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
693d45c3-d692-4c6c-a110-4ab12a20e8a7	Incorrect database version for Citrix Analytics Service	The current Site database version -- {{dbCurrentVersion}} -- of the database {{dbName}} on the server {{dbServer}} is too old for the Citrix Analytics Service. The database version should be {{dbExpectedVersion}}. This issue affects all Delivery Controllers in the Site.	Expected database version is {{dbExpectedVersion}}. Current database version is {{dbCurrentVersion}}; Database Name is {{dbName}}; Server Name is {{dbServer}}.	The current Site database version is too old for the Citrix Analytics Service. This issue affects all Delivery Controllers in the Site.		Upgrade the Site database to the expected version.	Error
b1c58e2d-4fed-4d1c-9e70-1539cf358a4	Incorrect database version for Citrix App Library Service	The current Site database version -- {{dbCurrentVersion}} -- of the database {{dbName}} on the server {{dbServer}} is too old for the Citrix App Library Service. The database version should be {{dbExpectedVersion}}. This issue affects all Delivery Controllers in the Site.	Expected database version is {{dbExpectedVersion}}. Current database version is {{dbCurrentVersion}}; Database Name is {{dbName}}; Server Name is {{dbServer}}.	The current Site database version is too old for the Citrix App Library Service. This issue affects all Delivery Controllers in the Site.		Upgrade the Site database to the expected version.	Warning
e449c226-42d9-43bf-9eb7-1146662e414f	Incorrect database version for Citrix Broker Service	The current Site database version -- {{dbCurrentVersion}} -- of the database {{dbName}} on the server {{dbServer}} is too old for the Citrix Broker Service. The database version should be {{dbExpectedVersion}}. This issue affects all Delivery Controllers in the Site.	Expected database version is {{dbExpectedVersion}}. Current database version is {{dbCurrentVersion}}; Database Name is {{dbName}}; Server Name is {{dbServer}}.	The current Site database version is too old for the Citrix Broker Service. This issue affects all Delivery Controllers in the Site.		Verify the Site database version is supported for the version of XenApp and XenDesktop in use. If needed, upgrade the Site database to the supported version.	Warning
a2ff1234-5685-479d-8c62-adb588256c6b	Incorrect database version for Citrix Configuration Service	The current Site database version -- {{dbCurrentVersion}} -- of the database {{dbName}} on the server {{dbServer}} is too old for the Citrix Configuration Service. The database version should be {{dbExpectedVersion}}. This issue affects all Delivery Controllers in the Site.	Expected database version is {{dbExpectedVersion}}. Current database version is {{dbCurrentVersion}}; Database Name is {{dbName}}; Server Name is {{dbServer}}.	The current Site database version is too old for the Citrix Configuration Service. This issue affects all Delivery Controllers in the Site.		Upgrade the Site database to the expected version.	Warning
59f38c3-1b2d-4d4e-ada8-e49a1e698d4	Incorrect database version for Citrix Configuration Logging Service	The current Site database version -- {{dbCurrentVersion}} -- of the database {{dbName}} on the server {{dbServer}} is too old for the Citrix Configuration Logging Service. The database version should be {{dbExpectedVersion}}. This issue affects all Delivery Controllers in the Site.	Expected database version is {{dbExpectedVersion}}. Current database version is {{dbCurrentVersion}}; Database Name is {{dbName}}; Server Name is {{dbServer}}.	The current Site database version is too old for the Citrix Configuration Logging Service. This issue affects all Delivery Controllers in the Site.		Upgrade the Site database to the expected version.	Warning
78b94ed-dffe-4ea4-b1eb-ab7d9883c97	Incorrect database version for Citrix Delegated Administration Service	The current Site database version -- {{dbCurrentVersion}} -- of the database {{dbName}} on the server {{dbServer}} is too old for the Citrix Delegated Administration Service. The database version should be {{dbExpectedVersion}}. This issue affects all Delivery Controllers in the Site.	Expected database version is {{dbExpectedVersion}}. Current database version is {{dbCurrentVersion}}; Database Name is {{dbName}}; Server Name is {{dbServer}}.	The current Site database version is too old for the Citrix Delegated Administration Service. This issue affects all Delivery Controllers in the Site.		Upgrade the Site database to the expected version.	Warning
c9e8e08-8f45-469f-bc91-279a2069dc90	Incorrect database version for Citrix Environment Test Service	The current Site database version -- {{dbCurrentVersion}} -- of the database {{dbName}} on the server {{dbServer}} is too old for the Citrix Environment Test Service. The database version should be {{dbExpectedVersion}}. This issue affects all Delivery Controllers in the Site.	Expected database version is {{dbExpectedVersion}}. Current database version is {{dbCurrentVersion}}; Database Name is {{dbName}}; Server Name is {{dbServer}}.	The current Site database version is too old for the Citrix Environment Test Service. This issue affects all Delivery Controllers in the Site.		Upgrade the Site database to the expected version.	Warning
76e2d0dd-3655-4ec8-9e0e-a63cad5c31a2	Incorrect database version for Citrix Host Availability Service	The current Site database version -- {{dbCurrentVersion}} -- of the database {{dbName}} on the server {{dbServer}} is too old for the Citrix Host Availability Service. The database version should be {{dbExpectedVersion}}. This issue affects all Delivery Controllers in the Site.	Expected database version is {{dbExpectedVersion}}. Current database version is {{dbCurrentVersion}}; Database Name is {{dbName}}; Server Name is {{dbServer}}.	The current Site database version is too old for the Citrix Host Availability Service. This issue affects all Delivery Controllers in the Site.		Upgrade the Site database to the expected version.	Warning
a888e49-548a-45cf-9cb4-aaf55a85e824	Incorrect database version for Citrix Machine Creation Service	The current Site database version -- {{dbCurrentVersion}} -- of the database {{dbName}} on the server {{dbServer}} is too old for the Citrix Machine Creation Service. The database version should be {{dbExpectedVersion}}. This issue affects all Delivery Controllers in the Site.	Expected database version is {{dbExpectedVersion}}. Current database version is {{dbCurrentVersion}}; Database Name is {{dbName}}; Server Name is {{dbServer}}.	The current Site database version is too old for the Citrix Machine Creation Service. This issue affects all Delivery Controllers in the Site.		Upgrade the Site database to the expected version.	Warning
94f15d4a-aace-4c43-abe7-e6129a0978d	Incorrect database version for Citrix Monitor Service	The current Site database version -- {{dbCurrentVersion}} -- of the database {{dbName}} on the server {{dbServer}} is too old for the Citrix Monitor Service. The database version should be {{dbExpectedVersion}}. This issue affects all Delivery Controllers in the Site.	Expected database version is {{dbExpectedVersion}}. Current database version is {{dbCurrentVersion}}; Database Name is {{dbName}}; Server Name is {{dbServer}}.	The current Site database version is too old for the Citrix Monitor Service. This issue affects all Delivery Controllers in the Site.		Upgrade the Site database to the expected version.	Warning
5385c3e6-0c3b-4bfc-b3a5-35313b8125bd	Incorrect database version for Citrix Storefront Service	The current Site database version -- {{dbCurrentVersion}} -- of the database {{dbName}} on the server {{dbServer}} is too old for the Citrix Storefront Service. The database version should be {{dbExpectedVersion}}. This issue affects all Delivery Controllers in the Site.	Expected database version is {{dbExpectedVersion}}. Current database version is {{dbCurrentVersion}}; Database Name is {{dbName}}; Server Name is {{dbServer}}.	The current Site database version is too old for the Citrix Storefront Service. This issue affects all Delivery Controllers in the Site.		Upgrade the Site database to the expected version.	Warning
409f33be-5188-46f3-88d1-453c965193e8	Missing reference schema for Citrix ADIdentity Service	The database reference schema for the Citrix AD Identity Service cannot be found.		The database reference schema for the Citrix AD Identity Service cannot be found.		Verify that database updates (XDU) have been applied and are present in the database.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
029c8f4-0c3e-474b-9e23-e72bca84be	Database object changed for Citrix AD Identity Service	An object definition in the database {{dbName}} on the server {{dbServer}} does not match the expected reference schema for the Citrix AD Identity Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object definition in the database does not match the expected reference schema for the Citrix AD Identity Service.		Restore the database to the most recent backup.	Warning
a0053900-de75-4b7f-bcaf-b76829a13ff	Database object removed for Citrix AD Identity Service	An object in the database {{dbName}} on the server {{dbServer}} is missing from the database schema definition for the Citrix AD Identity Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is missing from the database schema definition for the Citrix AD Identity Service.		Restore the database to the most recent backup.	Warning
228b35f6-7221-4488-a2e9-b805bb40a7ed	Extra database object for Citrix AD Identity Service	An object in the database {{dbName}} on the server {{dbServer}} is present in the current database schema but not in the expected reference schema for the Citrix AD Identity Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is present in the current database schema but not in the expected reference schema for the Citrix AD Identity Service.		Restore the database to the most recent backup.	Warning
92a6715b-454b-486d-976c-9a8376d9fe3a	Missing reference schema for Citrix Analytics Service	The database reference schema for the Citrix Analytics Service cannot be found.		The database reference schema for the Citrix Analytics Service cannot be found.		Verify that database updates (XDU) have been applied and are present in the database.	Warning
1abc1961-9480-4026-80d7-6c4a17e82298	Database object changed for Citrix Analytics Service	An object definition in the database {{dbName}} on the server {{dbServer}} does not match the expected reference schema for the Citrix Analytics Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object definition in the database does not match the expected reference schema for the Citrix Analytics Service.		Restore the database to the most recent backup.	Warning
a00e661c-1397-4246-9c9c-157978240964	Database object removed for Citrix Analytics Service	An object in the database {{dbName}} on the server {{dbServer}} is missing from the database schema definition for the Citrix Analytics Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is missing from the database schema definition for the Citrix Analytics Service.		Restore the database to the most recent backup.	Warning
1d98f481-71eb-425d-abe6-49e7de986788	Extra database object for Citrix Analytics Service	An object in the database {{dbName}} on the server {{dbServer}} is present in the current database schema but not in the expected reference schema for the Citrix Analytics Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is present in the current database schema but not in the expected reference schema for the Citrix Analytics Service.		Restore the database to the most recent backup.	Warning
3f785649-63ea-4ff0-bb3d-aedbe5a0bb9a	Missing reference schema for Citrix App Library Service	Unable to find the database reference schema for the Citrix App Library Service.		Unable to find the database reference schema for the Citrix App Library Service.		Verify that database updates (XDU) have been applied and are present in the database.	Warning
4c514bca-80fd-427a-b2a6-b72ee96e1d51	Database object changed for Citrix App Library Service	An object definition in the database {{dbName}} on the server {{dbServer}} does not match the expected reference schema for the Citrix App Library Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object definition in the database does not match the expected reference schema for the Citrix App Library Service.		Restore the database to the most recent backup.	Warning
00284610-c8f2-4418-a06c-f64df8622a47	Database object removed for Citrix App Library Service	An object in the database {{dbName}} on the server {{dbServer}} is missing from the database schema definition for the Citrix App Library Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is missing from the database schema definition for the Citrix App Library Service.		Restore the database to the most recent backup.	Warning
68013b0f-0abe-4c42-a021-a4c017837f4e	Extra database object for Citrix App Library Service	An object in the database {{dbName}} on the server {{dbServer}} is present in the current database schema but not in the expected reference schema for the Citrix App Library Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is present in the current database schema but not in the expected reference schema for the Citrix App Library Service.		Restore the database to the most recent backup.	Warning
579b2911-58c2-4a58-b44f-3d594365c866	Missing reference schema for Citrix Broker Service	The database reference schema for Citrix Broker Service cannot be found.		The database reference schema for Citrix Broker Service cannot be found.		Verify that database updates (XDU) have been applied and are present in the database.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
19a7f78b-0684-4e98-93d5-e45a25b0d900	Database object changed for Citrix Broker Service	An object definition in the database {{dbName}} on the server {{dbServer}} does not match the expected reference schema for the Citrix Broker Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object definition in the database does not match the expected reference schema for the Citrix Broker Service.		Restore the database to the most recent backup.	Warning
46a9b70-9eb5-47e0-b421-984c5963abc9	Database object removed for Citrix Broker Service	An object in the database {{dbName}} on the server {{dbServer}} is missing from the database schema definition for the Citrix Broker Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is missing from the database schema definition for the Citrix Broker Service.		Restore the database to the most recent backup.	Warning
2f1dea4d-8347-4619-a3be-90d6c56ecc5	Extra database object for Citrix Broker Service	An object in the database {{dbName}} on the server {{dbServer}} is present in the current database schema but not in the expected reference schema for the Citrix Broker Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is present in the current database schema but not in the expected reference schema for the Citrix Broker Service.		Restore the database to the most recent backup.	Warning
3903e33-df13-4408-82b2-4b1a21f00a45	Missing reference schema for Citrix Configuration Service	The database reference schema for Citrix Configuration Service cannot be found.		The database reference schema for Citrix Configuration Service cannot be found.		Verify that database updates (XDU) have been applied and are present in the database.	Warning
40c3b5a2-41e3-40ff-9e81-e1610889fca2	Database object changed for Citrix Configuration Service	An object definition in the database {{dbName}} on the server {{dbServer}} does not match the expected reference schema for the Citrix Configuration Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object definition in the database does not match the expected reference schema for the Citrix Configuration Service.		Restore the database to the most recent backup.	Warning
74d70199-29e1-493e-b1a8-ea5623bed52	Database object removed for Citrix Configuration Service	An object in the database {{dbName}} on the server {{dbServer}} is missing from the database schema definition for the Citrix Configuration Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is missing from the database schema definition for the Citrix Configuration Service.		Restore the database to the most recent backup.	Warning
29514053-e3b9-4f7a-a121-44ec5123c1a7	Extra database object for Citrix Configuration Service	An object in the database {{dbName}} on the server {{dbServer}} is present in the current database schema but not in the expected reference schema for the Citrix Configuration Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is present in the current database schema but not in the expected reference schema for the Citrix Configuration Service.		Restore the database to the most recent backup.	Warning
3f83afb0-6f73-42cc-9947-3adc17e1dbce	Missing reference schema for Citrix Configuration Logging Service	The database reference schema for the Citrix Configuration Logging Service cannot be found.		The database reference schema for the Citrix Configuration Logging Service cannot be found.		Verify that database updates (XDU) have been applied and are present in the database.	Warning
d860d0c4-4241-429e-958b-396f096c1727	Database object changed for Citrix Configuration Logging Service	An object definition in the database {{dbName}} on the server {{dbServer}} does not match the expected reference schema for the Citrix Configuration Logging Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object definition in the database does not match the expected reference schema for the Citrix Configuration Logging Service.		Restore the database to the most recent backup.	Warning
72aebb8c-fce7-4b63-9e03-14b4a214791d	Database object removed for Citrix Configuration Logging Service	An object in the database {{dbName}} on the server {{dbServer}} is missing from the database schema definition for the Citrix Configuration Logging Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is missing from the database schema definition for the Citrix Configuration Logging Service.		Restore the database to the most recent backup.	Warning
12ab0ea9-9cd5-488e-be42-700f9354dc00	Extra database object for Citrix Configuration Logging Service	An object in the database {{dbName}} on the server {{dbServer}} is present in the current database schema but not in the expected reference schema for the Citrix Configuration Logging Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is present in the current database schema but not in the expected reference schema for the Citrix Configuration Logging Service.		Restore the database to the most recent backup.	Warning
c8f738bb-3dd4-429e-8510-47a6249dca87	Missing reference schema for Citrix Delegated Administration Service	The database reference schema for the Citrix Delegated Administration Service cannot be found.		The database reference schema for the Citrix Delegated Administration Service cannot be found.		Verify database updates (XDU) have been applied and are present in the database.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
5bd0fce-ca69-49c0-a798-29d030fbb39	Database object changed for Citrix Delegated Administration Service	An object definition in the database {{dbName}} on the server {{dbServer}} does not match the expected reference schema for the Citrix Delegated Administration Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object definition in the database does not match the expected reference schema for the Citrix Delegated Administration Service.		Restore the database to the most recent backup.	Warning
62477bd3-6f33-4599-8fb-bad487247c	Database object removed for Citrix Delegated Administration Service	An object in the database {{dbName}} on the server {{dbServer}} is missing from the database schema definition for the Citrix Delegated Administration Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is missing from the database schema definition for the Citrix Delegated Administration Service.		Restore the database to the most recent backup.	Warning
a7759367-9365-4379-b69c-0ca5ee8f9f4	Extra database object for Citrix Delegated Administration Service	An object in the database {{dbName}} on the server {{dbServer}} is present in the current database schema but not in the expected reference schema for the Citrix Delegated Administration Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is present in the current database schema but not in the expected reference schema for the Citrix Delegated Administration Service.		Restore the database to the most recent backup.	Warning
93a1679-1965-4ba3-9a7-142e66a319d	Missing reference schema for Citrix Environment Test Service	The database reference schema for Citrix Environment Test Service cannot be found.		The database reference schema for Citrix Environment Test Service cannot be found.		Verify that database updates (XDU) have been applied and are present in the database.	Warning
c8a95730-5000-415a-9491-179e447402	Database object changed for Citrix Environment Test Service	An object definition in the database {{dbName}} on the server {{dbServer}} does not match the expected reference schema for the Citrix Environment Test Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object definition in the database does not match the expected reference schema for the Citrix Environment Test Service.		Restore the database to the most recent backup.	Warning
32face7-9577-4ded-b03a-108b8528a089	Database object removed for Citrix Environment Test Service	An object in the database {{dbName}} on the server {{dbServer}} is missing from the database schema definition for the Citrix Environment Test Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is missing from the database schema definition for the Citrix Environment Test Service.		Restore the database to the most recent backup.	Warning
c89b585b-9f6a-416d-8850-16a1bbd1946	Extra database object for Citrix Environment Test Service	An object in the database {{dbName}} on the server {{dbServer}} is present in the current database schema but not in the expected reference schema for the Citrix Environment Test Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is present in the current database schema but not in the expected reference schema for the Citrix Environment Test Service.		Restore the database to the most recent backup.	Warning
b688bd93-1d7b-42d0-87d9-1c3d46a6069	Missing reference schema for Citrix Host Service	The database reference schema for the Citrix Host Service cannot be found.		The database reference schema for the Citrix Host Service cannot be found.		Verify that database updates (XDU) have been applied and are present in the database.	Warning
92b29d2-760a-4188-8a65-e4d73dbdb6d0	Database object changed for Citrix Host Service	An object definition in the database {{dbName}} on the server {{dbServer}} does not match the expected reference schema for the Citrix Host Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object definition in the database does not match the expected reference schema for the Citrix Host Service.		Restore the database to the most recent backup.	Warning
e9b6af9-1511-4161-b6ce-59f4ec9610d	Database object removed for Citrix Host Service	An object in the database {{dbName}} on the server {{dbServer}} is missing from the database schema definition for the Citrix Host Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is missing from the database schema definition for the Citrix Host Service.		Restore the database to the most recent backup.	Warning
500002f1-3200-45f6-8a5b-adf537d4644	Extra database object for Citrix Host Service	An object in the database {{dbName}} on the server {{dbServer}} is present in the current database schema but not in the expected reference schema for the Citrix Host Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is present in the current database schema but not in the expected reference schema for the Citrix Host Service.		Restore the database to the most recent backup.	Warning
2639a52f-f2a9-4928-8ad1-9a6b2bc20055	Missing reference schema for Citrix Machine Creation Service	The database reference schema for the Citrix Machine Creation Service cannot be found.		The database reference schema for the Citrix Machine Creation Service cannot be found.		Verify that database updates (XDU) have been applied and are present in the database.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
71e7a10f-022b-40ab-8ac1-76405067ee2b	Database object changed for Citrix Machine Creation Service	An object definition in the database {{dbName}} on the server {{dbServer}} does not match the expected reference schema for the Citrix Machine Creation Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object definition in the database does not match the expected reference schema for the Citrix Machine Creation Service.		Restore the database to the most recent backup.	Warning
fe6a50ae-d39c-4639-bc68-1cc506000666	Database object removed for Citrix Machine Creation Service	An object in the database {{dbName}} on the server {{dbServer}} is missing from the database schema definition for the Citrix Machine Creation Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is missing from the database schema definition for the Citrix Machine Creation Service.		Restore the database to the most recent backup.	Warning
2e9733ad-3774-43a6-b52c-20e99290633	Extra database object for Citrix Machine Creation Service	An object in the database {{dbName}} on the server {{dbServer}} is present in the current database schema but not in the expected reference schema for the Citrix Machine Creation Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is present in the current database schema but not in the expected reference schema for the Citrix Machine Creation Service.		Restore the database to the most recent backup.	Warning
9e7439fe-8116-4da1-a91d-37d5c4c60bbb	Missing reference schema for Citrix Monitor Service	The database reference schema for the Citrix Monitor Service cannot be found.		The database reference schema for the Citrix Monitor Service cannot be found.		Verify that database updates (XDU) have been applied and are present in the database.	Warning
7d787b2c-3600-4777-8d6a-1a63d6cf2b0b	Database object changed for Citrix Monitor Service	An object definition in the database {{dbName}} on the server {{dbServer}} does not match the expected reference schema for the Citrix Monitor Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object definition in the database does not match the expected reference schema for the Citrix Monitor Service.		Restore the database to the most recent backup.	Warning
5b1022af-0a14-4929-ab5a-4f1402122181	Database object removed for Citrix Monitor Service	An object in the database {{dbName}} on the server {{dbServer}} is missing from the database schema definition for the Citrix Monitor Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is missing from the database schema definition for the Citrix Monitor Service.		Restore the database to the most recent backup.	Warning
0482fd56-a188-4e95-9191-3420b1acdab8	Extra database object for Citrix Monitor Service	An object in the database {{dbName}} on the server {{dbServer}} is present in the current database schema but not in the expected reference schema for the Citrix Monitor Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is present in the current database schema but not in the expected reference schema for the Citrix Monitor Service.		Restore the database to the most recent backup.	Warning
39f3c086-9a7e-43a5-aef6-8e5c51b174e9	Missing reference schema for Citrix Storefront Service	The database reference schema for the Citrix Storefront Service cannot be found.		The database reference schema for the Citrix Storefront Service cannot be found.		Verify that database updates (XDU) have been applied and are present in the database.	Warning
d758153d-bc14-44ca-8941-adb41ae059f5	Database object changed for Citrix Storefront Service	An object definition in the database {{dbName}} on the server {{dbServer}} does not match the expected reference schema for the Citrix Storefront Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object definition in the database does not match the expected reference schema for the Citrix Storefront Service.		Restore the database to the most recent backup.	Warning
ba85eca0-79f8-427d-bcf9-1aae8f6490b0	Database object removed for Citrix Storefront Service	An object in the database {{dbName}} on the server {{dbServer}} is missing from the database schema definition for the Citrix Storefront Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is missing from the database schema definition for the Citrix Storefront Service.		Restore the database to the most recent backup.	Warning
d3c30ec8-084c-40d2-b311-f3e1621ab3de	Extra database object for Citrix Storefront Service	An object in the database {{dbName}} on the server {{dbServer}} is present in the current database schema but not in the expected reference schema for the Citrix Storefront Service. The object description is {{objDescription}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}; The object description is {{objDescription}}.	An object in the database is present in the current database schema but not in the expected reference schema for the Citrix Storefront Service.		Restore the database to the most recent backup.	Warning
71bc589d-a38d-47d5-b0c4-eea0f0ef8060	Read Committed Snapshot disabled for Site database.	The Read Committed Snapshot database option is disabled for the Site database {{dbName}} on the server {{dbServer}}.	Database Name is {{dbName}}; Server Name is {{dbServer}}.	The Read Committed Snapshot database option is disabled for the Site database.		Ensure Read Committed Snapshot support is enabled for database. For instructions, see [CTX137161](http://support.citrix.com/article/CTX137161) in the Citrix Knowledge Center.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
a4c3542-d18a-4275-818b-5cc00f442e0f	Unsupported SQL Server version	The current SQL Server version is not supported.		The current SQL Server version is not supported.		Upgrade to SQL Server 2008, 2012, 2014, or 2016. For more information, refer to the [XenApp and XenDesktop system requirements](https://docs.citrix.com/en-us/xenapp-and-xendesktop/7-11/system-requirements.html).	Warning
98de2259-a59f-4e67-bcab-f2eed83f9686	Pool database error occurred for Citrix AD Identity Service	The database error "[{errorMsg}]" occurred while looking up the identity pool [{identityPool}]. This issue affects all Delivery Controllers in the Site.	The identity pool is [{identityPool}]. The error message is [{errorMsg}].	A database error occurred while looking up an identity pool. This issue affects all Delivery Controllers in the Site.		Check the service logs and database logs to diagnose the cause of the error.	Warning
63822828-ae7-493d-a6ac-6e769799c977	Identity database error occurred for Citrix AD Identity Service	The database error "[{errorMsg}]" occurred while looking up the identity [{identity}]. This issue affects all Delivery Controllers in the Site.	The identity is [{identity}]. The error message is [{errorMsg}].	A database error occurred while looking up an identity pool. This issue affects all Delivery Controllers in the Site.		Check the service logs and database logs to diagnose the cause of the error.	Warning
9073a6ee-58d9-4e80-897e-16c4574544fc	Identity not found for Citrix AD Identity Service	The identity [{identity}] was not found for the Citrix AD Identity Service. This issue affects all Delivery Controllers in the Site.	The identity is [{identity}].	A database error occurred while looking up an identity pool. This issue affects all Delivery Controllers in the Site.		Review the source of the identifier used; it might refer to a valid account that is not part of an MCS provisioned catalog.	Warning
3b24f140-3c44-4ee3-b40a-6cb2226805f7	Identity pool not found for Citrix AD Identity Service	The identity pool [{identityPool}] was not found for Citrix AD Identity Service. This issue affects all Delivery Controllers in the Site.	The identity pool is [{identityPool}].	An identity pool was not found for Citrix AD Identity Service. This issue affects all Delivery Controllers in the Site.		Review the source of the identity pool used.	Warning
bbcb64d0-311a-48ea-816e-046b97d1293d	Naming scheme absent for Citrix AD Identity Service	The identity pool [{identityPool}] cannot be used for provisioning because no naming scheme has been specified for the Citrix AD Identity Service.	The identity pool is [{identityPool}].	An identity pool cannot be used for provisioning because no naming scheme has been specified for the Citrix AD Identity Service.		Use Set-AccidentIdentityPool to set a naming scheme for the identity pool. For more information about this cmdlet, refer to the [Citrix XenApp and XenDesktop PowerShell SDK Reference](https://citrix.github.io/delivery-controller-sdk/ADIdentity/Set-AccidentIdentityPool/).	Warning
b27e4286-a9cd-4f15-8dad-6842fbb397dc	Delivery group in maintenance mode	The Delivery Group is currently in maintenance mode and cannot deliver applications and desktops to users.		The Delivery Group is currently in maintenance mode and cannot deliver applications and desktops to users.		Disable maintenance mode for the delivery group to resume delivery of applications and desktops to users. For more information, see [Prevent users from connecting to a machine](https://docs.citrix.com/en-us/xenapp-and-xendesktop/7-11/install-configure/delivery-group-manage.html#anchor_7a252) on the Citrix Product Documentation web site.	Warning
50f96077-771d-4e28-aca4-39c6b367c2f0	Delivery group unavailable for connections	The current Delivery Group is not able to accept more connections.		The current Delivery Group is not able to accept more connections.		For VDI delivery groups, make sure at least one machine is ready to accept connections. For RDS delivery groups, make sure at least one VDA is not at full capacity and is either available or in use.	Warning
0ff87df1-7d22-4ff9-a421-fcb2a4a2086	Site database in invalid state	The Site database is in an invalid state. The service operations could not be completed because the database configured for the services is not available or cannot be contacted.		The Site database is in an invalid state. The service operations could not be completed because the database configured for the services is not available or cannot be contacted.		Verify the following conditions: * The service database is running. * The credentials used to access the database are correctly entered and have sufficient permissions for access. * The database is not in the process of being upgraded. Additionally, restarting the Environment Test Service can resolve some database connectivity issues. To do this: 1. On the affected machine, click "Start", type "services.msc", and then press "ENTER". 2. From the Services console, right-click the Environment Test Service and then click "Restart". 3. Verify the components installed on the current machine are compatible with Citrix LTSR. Smart Check only checks Delivery Controllers and VDA components for LTSR compatibility. To generate an LTSR Compliance report or scan other components, use the LTSR Assistant tool as described in [CTX209577](https://support.citrix.com/article/CTX209577). For more information about LTSR-compatible components, see the topic [Long Term Service Release (LTSR)](http://docs.citrix.com/en-us/xenapp-and-xendesktop/7-6/xad-whats-new/long-term-service-release.html) on the Citrix Product Documentation web site.	Error
61edf32a-17c9-47d2-9407-83a8f2c2a448	Components of target machine incompatible with Citrix LTSR	The current machine has components that are not compatible with your Citrix Long Term Service Release support agreement.		The current machine has components that are not compatible with your Citrix Long Term Service Release support agreement.		Verify the components installed on the current machine are compatible with Citrix LTSR. Smart Check only checks Delivery Controllers and VDA components for LTSR compatibility. To generate an LTSR Compliance report or scan other components, use the LTSR Assistant tool as described in [CTX209577](https://support.citrix.com/article/CTX209577). For more information about LTSR-compatible components, see the topic [Long Term Service Release (LTSR)](http://docs.citrix.com/en-us/xenapp-and-xendesktop/7-6/xad-whats-new/long-term-service-release.html) on the Citrix Product Documentation web site.	Warning
ad2b94fe-633c-11e3-b233-0cc6ef3bd45	Less than 10% free space on system drive	The system drive on the servers has less than 10% free space remaining. This condition might not cause issues in this environment; however, Citrix recommends that system drives have more space available.		The system drive on the servers has less than 10% free space remaining. This condition might not cause issues in this environment; however, Citrix recommends that system drives have more space available.		Check the free disk space available on the affected servers. You might need to determine whether you can free space on the system drive or replace the existing drive with a larger one. For more information about Citrix recommendations for XenApp and XenDesktop, see [CTX132799](https://support.citrix.com/article/CTX132799) in the Citrix Knowledge Center.	Warning
5217c142-4243-11e3-9910-0cc6ef3bd45	Unsupported version of XenDesktop 7.1 detected	An unsupported version of XenDesktop, such as a Beta or pre-release version, has been detected on the affected servers in the Site.		An unsupported version of XenDesktop, such as a Beta or pre-release version, has been detected on the affected servers in the Site.		Check the XenDesktop product version on the affected servers and, where applicable, upgrade to a supported version of XenDesktop. For supported versions of XenDesktop, visit the [XenDesktop download page](https://www.citrix.com/downloads/xendesktop) on the Citrix web site.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
bda64e-538e-11e3-bf62-0ec6e3bd45	Registry key to disable session sharing detected	A registry key for disabling Session Sharing has been detected.		A registry key for disabling Session Sharing has been detected.		Using a registry key to disable Session Sharing on the affected servers is not supported for XenDesktop 7.x. This method can cause issues that prevent users from launching applications. For more information about Seamless registry flags and how to remove the setting for disabling Session Sharing, see [CTX101644](https://support.citrix.com/article/CTX101644) in the Citrix Knowledge Center.	Warning
eb4422e-2117-11e4-895a-0ec6e3bd45	FMA service logs growing too large for XenDesktop 7.x	FMA service logs on the affected servers are currently larger than 100 MB. Allowing the service logs to use too much disk space can have an adverse impact on the performance and functioning of the server.		FMA service logs on the affected servers are currently larger than 100 MB. Allowing the service logs to use too much disk space can have an adverse impact on the performance and functioning of the server.		Turn off Controller service logging on the affected servers to prevent filling available disk space. To do this: 1. locate the service configuration file for each FMA service – typically, this is %Program Files%\Citrix\ServiceName\Service\Citrix.<ServiceName>.exe.Config. The Broker Service configuration file is located at %Program Files%\Citrix\Broker\Service\BrokerService.exe.Config. 2. in the appsettings section of the service configuration file, change the LogToCDF value to 0 (zero) and remove the LogFileName key and, if applicable, the OverwriteLogFile key. For more information about the FMA services included in XenDesktop, see [CTX139415](https://support.citrix.com/article/CTX139415). For more information about FMAControl, a tool for collecting FMA traces, see [CTX139415]. The minimum supported Citrix License Server version for XenDesktop 7.6 is 11.12.1. Ensure that your License Server is running at least this version in order to use XenDesktop 7.6. For more information on XenDesktop 7.6 system requirements, refer to the System Requirements [https://docs.citrix.com/en-us/enapp-and-xendesktop/7-6/xad-system-requirements-76.html] topic on the Citrix Product Documentation web site. To set the license server hostname for your Delivery Site, use Studio or use the following command: Set-ConfigSite -LicenseServerName <name or IP>	Warning
5879a3e-64ad-11e4-a277-0ec6e3bd45	Incompatible version of Citrix License Server detected in XenDesktop 7.6	An incompatible version of the Citrix License Server software was detected in your environment.		An incompatible version of the Citrix License Server software was detected in your environment.		The minimum supported Citrix License Server version for XenDesktop 7.6 is 11.12.1. Ensure that your License Server is running at least this version in order to use XenDesktop 7.6. For more information on XenDesktop 7.6 system requirements, refer to the System Requirements [https://docs.citrix.com/en-us/enapp-and-xendesktop/7-6/xad-system-requirements-76.html] topic on the Citrix Product Documentation web site. To set the license server hostname for your Delivery Site, use Studio or use the following command: Set-ConfigSite -LicenseServerName <name or IP>	Error
23d7ecfd-af8e-455b-b2c1-2de8bbebae11	Latest Flash redirection hotfix not installed on XenDesktop 7.5 (32-bit Windows Desktop OS)	The latest Flash Acceleration hotfix for 32-bit Windows VDAs was not detected in the Site.		The latest Flash Acceleration hotfix for 32-bit Windows VDAs was not detected in the Site.		Install the Flash Acceleration hotfix to ensure HDX MediaStream Flash Redirection behaves as expected for users. The hotfix patches only systems where Version 7.5 of the VDA Core Services for Windows Desktop (32-bit) is installed. For more information, see [CTX141446](https://support.citrix.com/article/CTX141446) in the Citrix Support Knowledge Center.	Warning
6342062c-d27b-4e59-8f3d-959221f932c	Latest Flash redirection hotfix not installed on XenDesktop 7.5 (64-bit Windows Desktop OS)	The latest Flash Acceleration hotfix for 64-bit Windows VDAs was not detected in the Site.		The latest Flash Acceleration hotfix for 64-bit Windows VDAs was not detected in the Site.		Install the Flash Acceleration hotfix to ensure HDX MediaStream Flash Redirection behaves as expected for users. The hotfix patches only systems where Version 7.5 of the VDA Core Services for Windows Desktop (64-bit) is installed. For more information, see [CTX141447](https://support.citrix.com/article/CTX141447) in the Citrix Support Knowledge Center.	Warning
d1949b4-0bba-11e5-9b40-0ec6e14b222	ListOfDDCs on the VDA is either missing information or is not formatted properly	The values in the ListOfDDCs registry key in the VDA configuration does not follow Citrix best practices for registry-based Delivery Controller registration. The list might be missing a Delivery Controller; a listed Delivery Controller might not be using the correct FQDN; or the list does not have spaces between the Controller names. As a result, users' session launches could be rejected or delayed.		The values in the ListOfDDCs registry key in the VDA configuration does not follow Citrix best practices for registry-based Delivery Controller registration. The list might be missing a Delivery Controller; a listed Delivery Controller might not be using the correct FQDN; or the list does not have spaces between the Controller names. As a result, users' session launches could be rejected or delayed.		Verify the values in the ListOfDDCs registry key conform to Citrix best practices for XenDesktop registry-based Delivery Controller registration: 1. Ensure all Delivery Controllers in the Site are included in the list. 2. Verify all listed Delivery Controllers map to valid FQDNs. 3. Ensure all Delivery Controller names in the list are separated with spaces. For more information about these best practices, see [CTX133384](https://support.citrix.com/article/CTX133384) in the Citrix Support Knowledge Center. For more information about how VDAs discover Delivery Controllers, see the Delivery Controllers [http://docs.citrix.com/en-us/enapp-and-xendesktop/7-12/manage-deployment/delivery-controllers.html] topic on the Citrix Product Documentation web site.	Error
be688a97-7162-48bd-ace8-193b41e93ad	VDA registration issue detected mismatched user notification/QueryUserToken failed	VDA registration failure has been detected due to that mismatched user notification on broker service		VDA registration failure has been detected due to that mismatched user notification on broker service		To work around this issue, forcibly terminate any disconnected sessions and contact Citrix Support for assistance.	Error
466a1497-a120-46b9-8d5a-6f00a9736a55	AppDisk creation failure detected	An AppDisk creation failure occurred because of a mismatch between the list of Delivery Controllers (ListOfDDCs) from the Delivery Site and the corresponding list in the registry.		An AppDisk creation failure occurred because of a mismatch between the list of Delivery Controllers (ListOfDDCs) from the Delivery Site and the corresponding list in the registry.		Manually update the ListOfDDCs using Citrix policy settings or the registry. For more information, see the "Self-manage" section in the Delivery Controller [http://docs.citrix.com/en-us/enapp-and-xendesktop/7-12/manage-deployment/delivery-controllers.html] topic on the Citrix Product Documentation web site.	Error
22b3135-3116-4784-b982-02d193d04e9	The installed hotfix ICATS76/WN64044 requires replacement	The hotfix ICATS76/WN64044 has been detected and needs to be replaced. This hotfix contains an issue where the mouse pointer might warp when hovering inside a published application in a multi-monitor environment. A replacement hotfix corrects this issue.		The hotfix ICATS76/WN64044 has been detected and needs to be replaced. This hotfix contains an issue where the mouse pointer might warp when hovering inside a published application in a multi-monitor environment. A replacement hotfix corrects this issue.		Install the replacement hotfix ICATS76/WN64044. For more information, see [CTX214888](http://support.citrix.com/article/CTX214888) in the Citrix Support Knowledge Center.	Error
0db3723-898d-4c63-9e1e-c59d02d847c	Citrix Studio 7.9 has App-V integration issue and requires hotfix	Citrix Studio 7.9 has been detected and requires a hotfix. When closing and reopening an instance of Citrix Studio 7.9 that is configured with App-V servers containing many packages, Studio remains in an expanding state and fails to open. A hotfix corrects this issue.		Citrix Studio 7.9 has been detected and requires a hotfix. When closing and reopening an instance of Citrix Studio 7.9 that is configured with App-V servers containing many packages, Studio remains in an expanding state and fails to open. A hotfix corrects this issue.		For 64-bit Studio consoles, install the hotfix DStudioW64_7_9_001. For more information about this hotfix, see [CTX214422](http://support.citrix.com/article/CTX214422). For 32-bit Studio consoles, install the hotfix DStudioW64_7_9_001. For more information about this hotfix, see [CTX214421](http://support.citrix.com/article/CTX214421). **Important:** DStudioW64_7_9_001 and DStudioW64_7_9_001 are Limited Release Hotfixes. To download these hotfixes, log on to the Citrix web site with your Citrix account credentials. If the download link for the hotfix is not accessible and you wish to obtain this limited release, visit http://www.citrix.com/support and open a support case using your Citrix account credentials. Alternatively, contact your reseller at http://www.citrix.com/partners/locator.	Warning
c7593426-f6d5-4098-af69-5f6b9b7bade	USB redirection issue detected: Redirected device is detected as new when reconnected	A USB Redirection issue was detected in your Delivery Site. When Generic USB Redirection is enabled, each time a generic redirected USB device is physically disconnected and reconnected within a session, it is treated as a new device. As a result, an additional GUID is created with each reconnection.		A USB Redirection issue was detected in your Delivery Site. When Generic USB Redirection is enabled, each time a generic redirected USB device is physically disconnected and reconnected within a session, it is treated as a new device. As a result, an additional GUID is created with each reconnection.		To resolve the issue on Server VDAs, install hotfix ServerVDACoreW64_7_9_303. To resolve the issue on Desktop VDAs, install the hotfix DesktopVDACoreW64_7_9_303 or DesktopVDACoreW64_7_9_303. For more information about these hotfixes, see the following articles on the Citrix Support Knowledge Center: * Hotfix ServerVDACoreW64_7_9_303: [CTX203895](http://support.citrix.com/article/CTX203895) * Hotfix DesktopVDACoreW64_7_9_303: [CTX203894](http://support.citrix.com/article/CTX203894) * Hotfix DesktopVDACoreW64_7_9_303: [CTX203893](http://support.citrix.com/article/CTX203893)	Warning
715c7e5e-5f40-44a8-8abd-g9fb3155078	Unregistered VDAs in Delivery Group	VDAs in the Delivery Group are unregistered and might not be communicating with the Site. This issue can occur if the VDAs were not added to the Site correctly, the VDA Firewall is blocking communication with the Site, or the DNS or network adapters on the VDA are not configured correctly. If the VDAs cannot register with the Site, users might not be able to connect to the applications and desktops hosted on the Site.		VDAs in the Delivery Group are unregistered and might not be communicating with the Site. This issue can occur if the VDAs were not added to the Site correctly, the VDA Firewall is blocking communication with the Site, or the DNS or network adapters on the VDA are not configured correctly. If the VDAs cannot register with the Site, users might not be able to connect to the applications and desktops hosted on the Site.		To resolve this issue, perform the following actions: 1. Using Studio or Director, verify the registration state of the machines in the Delivery Group. 2. Check the VDA event logs for entries indicating registration failure. 3. Perform the troubleshooting steps in [CTX126992](https://support.citrix.com/article/CTX126992) in the Citrix Knowledge Center. For more information about VDA registration, see VDA Registration with Front-End [http://docs.citrix.com/en-us/enapp-and-xendesktop/7-12/manage-deployment/delivery-controllers.html] topic on the Citrix Product Documentation web site.	Warning

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
534e32e7-bdfc-4a9f-aeef-5a8f712b6d3	VDA in maintenance mode	VDAs in the Delivery Group are in maintenance mode. Maintenance mode renders VDAs unavailable for connections. This issue can occur if the VDAs are included in a power management policy that is in the process of powering off machines, the VDAs are undergoing maintenance tasks, or the VDAs cannot register with the Site after powering on. By default, VDAs must be able to connect to the applications and desktops hosted on these machines.	VDAs in the Delivery Group are fully loaded. As a result, users might not be able to connect to the applications and desktops hosted on these machines. Fully loaded machines have a load index of 10000. By default, these machines can host up to 250 sessions; however, this number might be different depending on the Site's load management policy settings.	VDAs in the Delivery Group are in maintenance mode. Maintenance mode renders VDAs unavailable for connections. This issue can occur if the VDAs are included in a power management policy that is in the process of powering off machines, the VDAs are undergoing maintenance tasks, or the VDAs cannot register with the Site after 3 attempts, the VDAs are put into maintenance mode automatically. As a result, users cannot connect to the applications and desktops hosted on these machines.		To resolve this issue, perform the following steps: 1. Verify whether power management is active for the VDAs and they are being powered off according to a peak time schedule. 2. Verify whether the VDAs are currently undergoing maintenance. 3. Check the VDA event logs for entries indicating registration failure. If entries are found, refer to the troubleshooting steps in [CTX126992](https://support.citrix.com/article/CTX126992) in the Citrix Knowledge Center. 4. On the Delivery Controller, review the current registry settings for VDA Registrations to ensure maintenance mode is initiated appropriately for your organization. For more information about these settings, see the "VDA Registration" section of [CTX126704](https://support.citrix.com/article/CTX126704) in the Citrix Knowledge Center.	Warning
370927b1-d5c8-49e3-85a0-e88420eada0	Fully loaded VDAs in Delivery Group	VDAs in the Delivery Group are fully loaded. As a result, users might not be able to connect to the applications and desktops hosted on these machines. Fully loaded machines have a load index of 10000. By default, these machines can host up to 250 sessions; however, this number might be different depending on the Site's load management policy settings.	VDAs in the Delivery Group are fully loaded. As a result, users might not be able to connect to the applications and desktops hosted on these machines. Fully loaded machines have a load index of 10000. By default, these machines can host up to 250 sessions; however, this number might be different depending on the Site's load management policy settings.	VDAs in the Delivery Group are fully loaded. As a result, users might not be able to connect to the applications and desktops hosted on these machines. Fully loaded machines have a load index of 10000. By default, these machines can host up to 250 sessions; however, this number might be different depending on the Site's load management policy settings.		To resolve this issue, perform the following steps: 1. Log off any disconnected sessions and review your Site's session limit policy settings to ensure disconnected sessions are logged off appropriately. For more information, see the following topics on the Citrix Product Documentation web site: * Log off sessions: [Manage Delivery Groups](https://docs.citrix.com/en-us/xenapp-and-xendesktop/7-13/install-configure/delivery-group-management/manager_anchor.html#_g55). * Session limits in Citrix policies: [Session limits policy settings](https://docs.citrix.com/en-us/xenapp-and-xendesktop/7-13/policies/reference/ica-policy-settings/session-limits-policy-settings.html). * Configure Citrix policies: [Create policies](http://docs.citrix.com/en-us/xenapp-and-xendesktop/7-13/policies/policies-create.html). * Add/remove additional machines to the Machine Catalog associated with the affected Delivery Group: [Add/remove machines to Site Catalog](https://support.citrix.com/article/CTX126704) in the Citrix Knowledge Center.	Warning
37ef97b-8729-42ce-b6b8-4c0eaf80bb24	VDA domain membership verification failed	The VDA's domain membership cannot be confirmed. This issue can occur if: * The VDA did not join the domain correctly. * DNS name resolution might not be working. * The domain controller can't be reached. * There is no trust relationship between the VDA and the domain controller. The VDA must be joined successfully to the domain so the VDA can register with the Site. If the VDA can't register with the Site, users cannot access the applications and desktops that the VDA hosts.	The VDA's domain membership cannot be confirmed. This issue can occur if: * The VDA did not join the domain correctly. * DNS name resolution might not be working. * The domain controller can't be reached. * There is no trust relationship between the VDA and the domain controller. The VDA must be joined successfully to the domain so the VDA can register with the Site. If the VDA can't register with the Site, users cannot access the applications and desktops that the VDA hosts.	The VDA's domain membership cannot be confirmed. This issue can occur if: * The VDA did not join the domain correctly. * DNS name resolution might not be working. * The domain controller can't be reached. * There is no trust relationship between the VDA and the domain controller. The VDA must be joined successfully to the domain so the VDA can register with the Site. If the VDA can't register with the Site, users cannot access the applications and desktops that the VDA hosts.		To troubleshoot this issue: 1. Verify the VDA is part of the domain. You can find this information in the VDA's System Properties or in the DNS console of the domain controller. 2. Check the VDA's DNS and network settings to verify you can reach the domain controller from the VDA. 3. Check the trust relationship between the VDA and the domain controller by running <code>*netdiag /test:trust*</code> from the command prompt. If the test fails, you can determine the best correction method for your environment, such as manually rejoining the VDA to the domain or resetting the machine password.	Error
559323ab-475c-4db2-b2c7-6c7983ac7f1	VDA cannot communicate with Delivery Controllers	The VDA can't communicate with the Delivery Controllers in the Site. This issue can occur if: * There are network issues preventing communication between the VDA and Delivery Controllers. * The VDA or Delivery Controllers have incorrect DNS settings.	The VDA can't communicate with the Delivery Controllers in the Site. This issue can occur if: * There are network issues preventing communication between the VDA and Delivery Controllers. * The VDA or Delivery Controllers have incorrect DNS settings. * Active Directory OU-based discovery of Delivery Controllers is not configured correctly. * Delivery Controller host names in the ListOfDDCs do not resolve to the IP address of the Delivery Controller.	The VDA can't communicate with the Delivery Controllers in the Site. This issue can occur if: * There are network issues preventing communication between the VDA and Delivery Controllers. * The VDA or Delivery Controllers have incorrect DNS settings. * Active Directory OU-based discovery of Delivery Controllers is not configured correctly. * Delivery Controller host names in the ListOfDDCs do not resolve to the IP address of the Delivery Controller.		To resolve this issue: 1. Verify that Active Directory OU-based discovery is correctly configured. For more information, see [Active Directory OU-based Controller Discovery](https://docs.citrix.com/en-us/xenapp-and-xendesktop/7-6/oad-controller-intro/oad-controller-ou-discover.html) on the Citrix Product Documentation web site. 2. Verify the VDA's DNS settings are correctly configured so the Delivery Controller's FQDN can be resolved from the VDA. 3. Verify the VDA and the Delivery Controller can communicate on the same port. 4. Verify the ListOfDDCs is not empty. For more information, see [Best Practices for XenDesktop Registry-based DDC Registration](https://support.citrix.com/article/CTX133384) in the Citrix Knowledge Center.	Error
91865980-28d4-4d44-a1a1-56056a0778b0	Incorrect Windows Firewall configuration for Session Launch	The Windows Firewall configuration on the VDA is preventing inbound connections from Delivery Controllers in the Site. The VDA must allow <code>**inbound connections**</code> on the following ports: * ICA TCP port 1494 (default) * XTE TCP port 2598 (default) * HTMLS TCP port 8008 (default) * SSL TCP port 443 (default) * AudsRTP UDP ports 16500-16509 (default) * Spyder ICA UDP port 1494	The Windows Firewall configuration on the VDA is preventing inbound connections from Delivery Controllers in the Site. The VDA must allow <code>**inbound connections**</code> on the following ports: * ICA TCP port 1494 (default) * XTE TCP port 2598 (default) * HTMLS TCP port 8008 (default) * SSL TCP port 443 (default) * AudsRTP UDP ports 16500-16509 (default) * Spyder ICA UDP port 1494	The Windows Firewall configuration on the VDA is preventing inbound connections from Delivery Controllers in the Site. The VDA must allow <code>**inbound connections**</code> on the following ports: * ICA TCP port 1494 (default) * XTE TCP port 2598 (default) * HTMLS TCP port 8008 (default) * SSL TCP port 443 (default) * AudsRTP UDP ports 16500-16509 (default) * Spyder ICA UDP port 1494		To resolve this issue, verify the VDA's firewall rules allow inbound connections on each of the required ports. If no rules exist, configure new firewall rules. To configure new firewall rules: 1. On the VDA, launch Server Manager and click <code>**Tools > Windows Firewall with Advanced Security**</code> . 2. In the left pane, click <code>**Inbound Rules**</code> . 3. In the right pane, click <code>**New Rule**</code> . 4. Complete the New Inbound Rule wizard for each required port.	Error
ba347c1-20cc-452b-9094-939baf79fb5	System clocks on the VDA and Delivery Controller are not syn	The time difference between the VDA's system clock and the Delivery Controller's system clock is greater than the maximum difference that Kerberos allows. Kerberos requires the system clock on client computers (such as the VDA) to be within the allowed range of time difference to ensure authentication requests can be evaluated appropriately. By default, the maximum allowed difference is 5 minutes, but this value could be different in your environment. If this time difference is not within the allowed range, the VDA might not be able to register with the Site, preventing users from logging on and accessing their applications and desktops.	The time difference between the VDA's system clock and the Delivery Controller's system clock is greater than the maximum difference that Kerberos allows. Kerberos requires the system clock on client computers (such as the VDA) to be within the allowed range of time difference to ensure authentication requests can be evaluated appropriately. By default, the maximum allowed difference is 5 minutes, but this value could be different in your environment. If this time difference is not within the allowed range, the VDA might not be able to register with the Site, preventing users from logging on and accessing their applications and desktops.	The time difference between the VDA's system clock and the Delivery Controller's system clock is greater than the maximum difference that Kerberos allows. Kerberos requires the system clock on client computers (such as the VDA) to be within the allowed range of time difference to ensure authentication requests can be evaluated appropriately. By default, the maximum allowed difference is 5 minutes, but this value could be different in your environment. If this time difference is not within the allowed range, the VDA might not be able to register with the Site, preventing users from logging on and accessing their applications and desktops.		To resolve this issue: 1. Verify the DNS and network settings on the VDA are correct and that you can reach the Delivery Controller from the VDA. 2. If needed, adjust the system clock on the VDA to closely match the Delivery Controller's system clock.	Error
3b484a00-4123-49d0-a724-b393980ab5	VDA is not registered with the Site	This issue might occur if the VDA Desktop Service has an invalid status, the VDA can't reach the domain controller, the VDA can't communicate with the Site, or there are other undiagnosed conditions affecting the VDA. If the VDA can't register with the Site, users might not be able to log on and access their applications and desktops.	This issue might occur if the VDA Desktop Service has an invalid status, the VDA can't reach the domain controller, the VDA can't communicate with the Site, or there are other undiagnosed conditions affecting the VDA. If the VDA can't register with the Site, users might not be able to log on and access their applications and desktops.	This issue might occur if the VDA Desktop Service has an invalid status, the VDA can't reach the domain controller, the VDA can't communicate with the Site, or there are other undiagnosed conditions affecting the VDA. If the VDA can't register with the Site, users might not be able to log on and access their applications and desktops.		To troubleshoot this issue, perform the tasks described in the following Citrix articles: * [CTX136668](https://support.citrix.com/article/CTX136668) * [CTX126992](https://support.citrix.com/article/CTX126992) If no other alerts are displayed for this VDA, contact Citrix Technical Support for assistance.	Warning
5613c664-152d-421e-98c6-e8a7c96afbd	Ports used for VDA session launch are unavailable	One or more of the following ports are unavailable for VDAs in the Site to use: * ICA TCP port (1494) * XTE TCP port (2598) * HTMLS TCP port (8008) * SSL TCP port (443) * AudsRTP UDP ports (16500-16509) * Spyder ICA UDP port (1494)	One or more of the following ports are unavailable for VDAs in the Site to use: * ICA TCP port (1494) * XTE TCP port (2598) * HTMLS TCP port (8008) * SSL TCP port (443) * AudsRTP UDP ports (16500-16509) * Spyder ICA UDP port (1494)	One or more of the following ports are unavailable for VDAs in the Site to use: * ICA TCP port (1494) * XTE TCP port (2598) * HTMLS TCP port (8008) * SSL TCP port (443) * AudsRTP UDP ports (16500-16509) * Spyder ICA UDP port (1494)		To resolve this issue: 1. Review the ports currently in use in the Site. 2. Verify they are not being used by other applications. If needed, resolve port conflicts to ensure the ports are available for the VDAs to use. For a complete list of XenApp and XenDesktop ports, see [CTX101810](https://support.citrix.com/article/CTX101810)(XenDesktop_XenApp).	Error
753564d8-ed47-442e-ba3b-d873c436e0b	Session launches services display invalid status	One or more of the following services are not started, cannot be found, or have invalid permissions: * Citrix ICA Service * Citrix Encryption Service * Citrix Print Manager Service * Citrix Group Policy Engine * Citrix HDX MediaStream for Flash Service	One or more of the following services are not started, cannot be found, or have invalid permissions: * Citrix ICA Service * Citrix Encryption Service * Citrix Print Manager Service * Citrix Group Policy Engine * Citrix HDX MediaStream for Flash Service * Citrix Pvs for VMs agent (for MCS-provisioned VDAs only)	One or more of the following services are not started, cannot be found, or have invalid permissions: * Citrix ICA Service * Citrix Encryption Service * Citrix Print Manager Service * Citrix Group Policy Engine * Citrix HDX MediaStream for Flash Service * Citrix Pvs for VMs agent (for MCS-provisioned VDAs only)		To resolve this issue: 1. Verify all required services are installed, started, and configured to start automatically. If any services are not present, repair the VDA installation to install the missing services. If any services are not running, perform the following steps: * Click <code>**Start**</code> , type <code>**services.msc**</code> , and then press ENTER. 2. Locate each service in the list and verify the <code>**Status**</code> is <code>**Started**</code> . 3. For each service, verify the <code>**Startup Type**</code> is <code>**Automatic**</code> . If not, right-click the service and select <code>**Properties**</code> . In <code>**Startup Type**</code> , select <code>**Automatic**</code> . 2. Verify the services are configured to use valid credentials.	Error
1b402327-9134-4a0c-bf93-91af6372c26d	VDA software installation missing or corrupted	The Virtual Delivery Agent software installation on the machine is not functioning correctly. This issue can occur if the software was not installed correctly or does not support the current OS version on the machine.	The Virtual Delivery Agent software installation on the machine is not functioning correctly. This issue can occur if the software was not installed correctly or does not support the current OS version on the machine.	The Virtual Delivery Agent software installation on the machine is not functioning correctly. This issue can occur if the software was not installed correctly or does not support the current OS version on the machine.		To resolve this issue: 1. Verify the Virtual Delivery Agent software supports the machine's current OS version. 2. If needed, repair the VDA installation or reinstall the VDA software as described in [Install VDAs](http://docs.citrix.com/en-us/xenapp-and-xendesktop/7-14/install-configure/install-vdas.html). Be sure to download the version appropriate for the machine's operating system. For system requirements for Desktop and Server VDAs, see [System Requirements](http://docs.citrix.com/en-us/xenapp-and-xendesktop/7-14/system-requirements.html) on the Citrix Product Documentation web site.	Error
7a0bb1f5b0f4021-8a63-a19136d6e14	Citrix Desktop Service displays invalid status	The Citrix Desktop Service is not properly installed or registered on the machine or the service permissions might not be set correctly. This issue can occur if the service is not started or the system Event Log has traces of service-related issues. If the Citrix Desktop Service is not present or running, the VDA can't register with the Site, preventing users from accessing their applications and desktops.	The Citrix Desktop Service is not properly installed or registered on the machine or the service permissions might not be set correctly. This issue can occur if the service is not started or the system Event Log has traces of service-related issues. If the Citrix Desktop Service is not present or running, the VDA can't register with the Site, preventing users from accessing their applications and desktops.	The Citrix Desktop Service is not properly installed or registered on the machine or the service permissions might not be set correctly. This issue can occur if the service is not started or the system Event Log has traces of service-related issues. If the Citrix Desktop Service is not present or running, the VDA can't register with the Site, preventing users from accessing their applications and desktops.		To resolve this issue: 1. Launch the Services console: Click <code>**Start**</code> and then type <code>**Services**</code> . 2. Verify the Citrix Desktop Service is present, restart the service, and check the Event Log for any errors: From the Services console, right-click the Citrix Desktop Service and select <code>**Restart**</code> . 3. Verify the service's Startup Type is set to <code>**Automatic**</code> . If not, right-click the service, select <code>**Properties**</code> , and then, in <code>**Startup type**</code> , select <code>**Automatic**</code> . 4. Verify that the service is configured to run under the Network Service account. 5. If the Citrix Desktop Service is not present or you are still receiving this alert after performing the previous steps, you might need to	Error

ID	Title	Description	Instance description	Static description	Content credit	Fix description	Severity
2cb2523e-6751-4ef5-bc70-7ea73e2a7a1	VDA communication ports are not available	TCP port 80 is unavailable or might be in use by another application. This port is required for BrokerAgent.exe. If this port is blocked or in use by another application, the VDA cannot register with the Site. If this happens, users might not be able to log on and access their applications and desktops.		TCP port 80 is unavailable or might be in use by another application. This port is required for BrokerAgent.exe. If this port is blocked or in use by another application, the VDA cannot register with the Site. If this happens, users might not be able to log on and access their applications and desktops.		To resolve this issue, verify that no other applications use the ports needed for the VDA. For complete port information, see [CTX101810](https://support.citrix.com/article/CTX101810) in the Citrix Knowledge Center.	Error
a3547960-fdad-4594-96bd-ebf9d9f78fa	Invalid Windows Firewall configuration	The following Windows Firewall rules are not enabled on the VDA: * Inbound agent connections on TCP port 80 * Outbound Broker connections on TCP port 80 (default)		The following Windows Firewall rules are not enabled on the VDA: * Inbound agent connections on TCP port 80 * Outbound Broker connections on TCP port 80 (default)		To configure new firewall rules: 1. On the VDA, launch Server Manager and click **Tools > Windows Firewall with Advanced Security** . 2. In the left pane, click **Inbound Rules** or **Outbound Rules** as appropriate. 3. In the right pane, click **New Rule** . 4. Complete the New Rule wizard for each required port. For complete port information, see [CTX101810](https://support.citrix.com/article/CTX101810) in the Citrix Knowledge Center.	Error
f2996387-7ebd-455e-b36a-da83506fe104	Domain pass-through authentication to StoreFront fails to launch session	An issue was detected where the XML Service does not trust by default session requests that are sent without explicit authentication. As a result, attempts to launch sessions from StoreFront might fail.		To resolve this issue, see [CTX140045](https://support.citrix.com/article/CTX140045).		Legacy plugin alert	Warning
d5663bde-e93e-11e4-842c-0ce6e3bd45	XenDesktop 7 Controller rejects VDA registration	An issue was detected in your environment where the Delivery Controller is rejecting VDA registration attempts. When this issue occurs, Event ID 1048 appears in the Event log.		To resolve this issue, perform the following actions as applicable: * Upgrade the VDA software to Version 7.6. * Contact Citrix Technical Support for any private fixes that might be available.		Legacy plugin alert	Warning
74ebff6d-0105-11e5-8196-0ce6e14b222	Users connecting to Delivery Groups receive a "Cannot Start Desktop" Error on XenDesktop 7 and 7.1	Users connecting to Delivery Groups receive a "Cannot start desktop" error message. This occurs because desktops in the Delivery Group configured to shut down after use did not shut down, possibly because of a power action that did not reach the hypervisor. These "zained" desktops are not available for use until they are restarted.		Refer to [CTX138934](https://support.citrix.com/article/CTX138934) for resolution of this issue.		Legacy plugin alert	Error
b77e385e-d76b-11e4-8ea2-0ce6e14b222	Failed power action detected in XenDesktop 7	One or more failed power actions were detected in this environment.		To resolve this issue, modify the VDA registration timeouts. For more information, see [CTX126704](https://support.citrix.com/article/CTX126704).		Legacy plugin alert	Error
7d165a86-df34-4305-9a0a-bc0658b5c48e	Auto-creation failure: Missing driver detected	Printer driver auto-creation failure was detected due to a missing driver.		To resolve this issue, see [CTX137143](https://support.citrix.com/article/CTX137143).		Legacy plugin alert	Warning